Openwall Products Services Publications Resources What's new bringing security into open environments

Hash Suite - Windows password security audit tool. GUI, reports in PDF. [<prev] [next>] [day] [month] [year] [list]

Date: Mon, 26 Apr 2021 15:41:17 +0200
From: Matthias Gerstner <mgerstner@...e.de>
To: oss-security@...ts.openwall.com
Subject: virtualbox: CVE-2021-25319: missing sticky bit in openSUSE packaging
for /etc/box allows local root exploit for members of vboxusers group

somewhat related to CVE-2021-2264 I noticed an openSUSE specific security issue in the openSUSE packaging for virtualbox [1]. To enable the autostart feature in virtualbox as outlined in the upstream manual [2] our packagers introduced a group 'vboxusers' that is granted write access to the directory /etc/vbox as the "autostart DB". Contrary to what the manual says the directory was not packaged with the sticky bit set, however.

The file /etc/vbox/vbox.cfg is a configuration file for virtualbox. This file is sourced by other virtualbox bash scripts running as root like 'vboxautostart.sh', 'vboxdrv.sh' and 'vboxweb-service.sh'. Due to the missing sticky bit any member of the vboxusers group can replace the /etc/vbox/vbox.cfg file by a manipulated one, allowing for full code execution in the context of the root user once e.g. the vboxautostart systemd service runs.

Reproducer:

```
root# su -g vboxusers nobody
nobody$ cd /etc/vbox
nobody$ cp vbox.cfg vbox.cfg.new
nobody$ rm -f vbox.cfg
nobody$ m vbox.cfg.new vbox.cfg
nobody$ m vbox.cfg nobody$ m vbox.cfg
nobody$ exit
nobodyš exit
root# systemctl start vboxautostart.service
root# 1s -lh /root/evil
-rw-r--r- 1 root root 0 2. Mär 12:14 /root/evil
```

I have been looking into other distributions like Arch Linux, Fedora and also some of the RFMs distributed on www.virtualbox.org. They all package /etc/ybox as root:root mode 755 and are therefore not affected.

Updates for the openSUSE virtualbox packages are underway [3] that will fix the packaging error and also move the "autostart DB" directory from /etc/vbox to /etc/vbox/autostart.d to avoid mixing the autostart related files with the virtualbox system configuration file in the same

Cheers

Matthias

- [1]: https://build.opensuse.org/package/show/Virtualization/virtualbox [2]: https://www.virtualbox.org/manual/ch09.html#autostart-linux [3]: https://bugzilla.suse.com/show_bug.org/id=118291

--Matthias Gerstner <matthias.gerstner@...e.de> Dipl.-Wirtsch.-Inf. (FH), Security Engineer https://www.suse.com/security https://www.suse.com/security Phone: +49 911 740 53 290 GPG Key ID: 0x14C405C971923553 SUSE Software Solutions Germany GmbH HRB 36809, AG Nürnberg Geschäftsführer: Felix Imendörffer

Download attachment "signature.asc" of type "application/pgp-signature" (834 bytes)

Powered by blists - more mailing lists

Please check out the Open Source Software Security Wiki, which is counterpart to this mailing list.

Confused about mailing lists and their use? Read about mailing lists on Wikipedia and check out these guidelines on proper formatting of your messages.

OPENWALL A OPENV2