snyk Vulnerability DB

Snyk Vulnerability Database > NuGet > elfinder.net.core

Directory Traversal

Affecting elfinder.net.core package, versions [0,1.2.4)




Overview

elFinder.Net.Core is an An elFinder backend connector with less magic code and more compatibility. This enables .NET Standard 2.0 projects to easily integrate elFinder functionalities.

Affected versions of this package are vulnerable to Directory Traversal. The user-controlled file name is not properly sanitized before it is used to create a file system path.

PoC



Details

, instead of the expected volume folder

A Directory Traversal attack (also known as path traversal) aims to access files and directories that are stored outside the intended folder. By manipulating files with "dot-dot-slash (.../)" sequences and its variations, or by using absolute file paths, it may be possible to access arbitrary files and directories stored on file system, including application source code, configuration, and other critical system files.

Directory Traversal vulnerabilities can be generally divided into two types:

 Information Disclosure: Allows the attacker to gain information about the folder structure or read the contents of sensitive files on the system.

st is a module for serving static files on web pages, and contains a vulnerability of this type. In our example, we will serve files from the public route.

If an attacker requests the following URL from our server, it will in turn leak the sensitive private key of the root user.

curl http://localhost:8080/public/%2e%2e/%2e%2e/%2e%2e/%2e%2e/root/.ssh/id_rsa

Note $\,\%2e\,$ is the URL encoded version of . (dot).

Writing arbitrary files: Allows the attacker to create or replace existing files. This type of vulnerability is also known as Zip-Slip.

One way to achieve this is by using a malicious zip archive that holds path traversal filenames. When each filename in the zip archive gets concatenated to the target extraction folder, without validation, the final path ends up outside of the target folder. If an executable or a configuration file is overwritten with a file containing malicious code, the problem can turn into an arbitrary code execution issue quite easily.

The following is an example of a zip archive with one benign file and one malicious file. Extracting the malicious file will result in traversing out of the target folder, ending up in /root/.ssh/ overwriting the $authorized_keys$ file:

2018-04-15 22:04:29 19 19 good.txt 2018-04-15 22:04:42 20 20 ../../../../root/.ssh/authorized_keys

References

- GithHub Commit
- GitHub Release



Snyk CVSS			
Exploit Matur	ty	Proof of concept	•
Attack Compl	exity	Low	6
Confidentialit	/	HIGH	6
See more			
NVD Do your appli	cations use this vulnerab	7.5 HIG	Н
Do your appli In a few clicks what compon suggest you c	s we can analyze your en ents are vulnerable in yo	ole package?	
Do your appli In a few click: what compon suggest you o	s we can analyze your en ents are vulnerable in yo uick fixes.	ole package? tire application and se ur application, and	е
Do your applii In a few clicks what compon suggest you o	we can analyze your en ents are vulnerable in yo uick fixes. pplications	ole package? tire application and se ur application, and	e 52

Found a mistake?

Report a new vulnerability

PRODUCT Snyk Open Source Snyk Code Snyk Container Snyk Infrastructure as Code Test with Github Test with CLI RESOURCES Vulnerability DB Documentation Disclosed Vulnerabilities Blog FAQs COMPANY About Jobs Contact Policies Do Not Sell My Personal Information CONTACT US Support

FIND US ONLINE

TRACK OUR DEVELOPMENT



© 2022 Snyk Limited

Report a new vuln
Press Kit
Events

Registered in England and Wales. Company number: 09677925

Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.