# **snyk** Vulnerability DB

Snyk Vulnerability Database > npm > ua-parser-js

# Regular Expression Denial of Service (ReDoS)

Affecting ua-parser-js package, versions < 0.7.22



#### Overview

ua-parser-js is a lightweight JavaScript-based user-agent string parser

Affected versions of this package are vulnerable to Regular Expression Denial of Service (ReDoS) via the regex for Redmi Phones and Mi Pad Tablets UA.

## POC by Yeting Li

```
var blank = " "; for (let i = 1; i < 5000; i++) { blank = blank + " "; }
str_mi = "androidinipad" + blank + "!"; str_mi = str_mi + +blank + "!"; mi = /android.+(mi[s-]*(?:pad)(?:[s]*
[ws]*))s+build/i;

var count_mi = 0; for (let i = 0; i < 10; i++) { var time = Date.now(); mi.test(str_mi); var len = Date.now() - time;
count_mi = count_mi + len; console.log("mi:" + blank.length + ": " + len) } console.log(count_mi / 10);

str_redmi = "androidiredminote" + blank + "!"; redmi = /android.+(redmi[s-]*(?:note)?(?:[s]*[ws]+))s+build/i; var
count_redmi = 0; for (let i = 0; i < 10; i++) { var time = Date.now(); redmi.test(str_redmi); var len = Date.now() - time;
count_redmi = count_redmi + len; console.log("redmi:" + blank.length + ": " + len) } console.log(count_redmi / 10);</pre>
```

#### Details

Denial of Service (DoS) describes a family of attacks, all aimed at making a system inaccessible to its original and legitimate users. There are many types of DoS attacks, ranging from trying to clog the network pipes to the system by generating a large volume of traffic from many machines (a Distributed Denial of Service - DDoS - attack) to sending crafted requests that cause a system to crash or take a disproportional amount of time to process.

The Regular expression Denial of Service (ReDoS) is a type of Denial of Service attack. Regular expressions are incredibly powerful, but they aren't very intuitive and can ultimately end up making it easy for attackers to take your site down.

Let's take the following regular expression as an example:

```
Pegex = /A(B|C+)+D/
```

This regular expression accomplishes the following:

- A The string must start with the letter 'A'
- (B|C+)+ The string must then follow the letter A with either the letter 'B' or some number of occurrences of the letter 'C' (the + matches one or more times). The + at the end of this section states that we can look for one or more matches of this section.
- D Finally, we ensure this section of the string ends with a 'D'

The expression would match inputs such as  $\mbox{\sc abbd}$  ,  $\mbox{\sc abccccd}$  ,  $\mbox{\sc abccccd}$  and  $\mbox{\sc accccdd}$ 

It most cases, it doesn't take very long for a regex engine to find a match:

The entire process of testing it against a 30 characters long string takes around ~52ms. But when given an invalid string, it takes nearly two seconds to complete the test, over ten times as long as it took to test a valid string. The dramatic difference is due to the way regular expressions get evaluated.

Most Regex engines will work very similarly (with minor differences). The engine will match the first possible way to accept the current character and proceed to the next one. If it then fails to match the next one, it will backtrack and see if there was another way to digest the previous character. If it goes too far down the rabbit hole only to find out the string doesn't match in the end, and if many characters have multiple valid regex paths, the number of backtracking steps can become very large, resulting in what is known as catastrophic backtracking.

Let's look at how our expression runs into this problem, using a shorter string: "ACCCX". While it seems fairly straightforward, there are still four different ways that the engine could match those three C's:







Snyk CVSS	
Exploit Maturity	Proof of concept
Attack Complexity	Low
Availability	(HIGH)
Availability	(mon)
See more	
> NVD	(7.5 HIG
what components are v suggest you quick fixes	
what components are	rulnerable in your application, and s.
what components are v suggest you quick fixes	rulnerable in your application, and s.
what components are valued by suggest you quick fixes  Test your application  Snyk Learn	vulnerable in your application, and s.
what components are visuggest you quick fixes  Test your application  Snyk Learn	vulnerable in your application, and s.
what components are visuggest you quick fixes  Test your application  Snyk Learn  Learn about Regular Ex	vulnerable in your application, and s.
what components are visuggest you quick fixes  Test your application  Snyk Learn  Learn about Regular Exvulnerabilities in an interest of the start learning	vulnerable in your application, and s.  ns  spression Denial of Service (ReDoS) eractive lesson.
what components are visuggest you quick fixes  Test your application  Snyk Learn  Learn about Regular Exvulnerabilities in an interest of the start learning	vulnerable in your application, and s.
what components are suggest you quick fixes  Test your application  Snyk Learn  Learn about Regular Exvulnerabilities in an inter-	vulnerable in your application, and s.  ns  spression Denial of Service (ReDoS) eractive lesson.
what components are visuggest you quick fixes  Test your application  Snyk Learn  Learn about Regular Exvulnerabilities in an interest your application  Start learning  Snyk ID	vulnerable in your application, and s.  pression Denial of Service (ReDoS) eractive lesson.

Report a new vulnerability Found a mistake?

# 3. C+CC

## 4. C+C+C.

The engine has to try each of those combinations to see if any of them potentially match against the expression. When you combine that with the other steps the engine must take, we can use RegEx 101 debugger to see the engine has to take a total of 38 steps before it can determine the string doesn't match.

From there, the number of steps the engine must use to validate a string just continues to grow.

String	Number of C's	Number of steps
ACCCX	3	38
ACCCCX	4	71
ACCCCCX	5	136
ACCCCCCCCCCCX	14	65,553

By the time the string includes 14 C's, the engine has to take over 65,000 steps just to see if the string is valid. These extreme situations can cause them to work very slowly (exponentially related to input size, as shown above), allowing an attacker to exploit this and can cause the service to excessively consume CPU, resulting in a Denial of Service.

# References

## • GitHub Commit

PRODUCT
Snyk Open Source
Snyk Code

Snyk Container

Snyk Infrastructure as Code

Test with Github

Test with CLI

RESOURCES

Vulnerability DB

Documentation

Disclosed Vulnerabilities

Blog

FAQs

COMPANY

About

Jobs

Contact

Policies

Do Not Sell My Personal Information

CONTACT US

Support

Report a new vuln

Press Kit

Events

FIND US ONLINE

TRACK OUR DEVELOPMENT





© 2022 Snyk Limited

Registered in England and Wales. Company number: 09677925

Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.