


Symlink Directory Exposes Webapp Directory Contents

Low waynebeaton published GHSA-j6qj-j888-vvgq on Apr 1, 2021

Package

 org.eclipse.jetty:jetty-deploy (Maven)

Affected versions

9.4.32-9.4.38, 10.0.0.beta2-10.0.1, 11.0.0.beta2-11.0.1

Patched versions

9.4.39, 10.0.2, 11.0.2

Description

Impact

If the `${jetty.base}` directory or the `${jetty.base}/webapps` directory is a symlink (soft link in Linux), the contents of the `${jetty.base}/webapps` directory may be deployed as a static web application, exposing the content of the directory for download.

For example, the problem manifests in the following `${jetty.base}` :

```
demo-base/  
├─ etc  
├─ lib  
├─ resources  
├─ start.d  
├─ deploy  
│   └─ async-rest.war  
└─ webapps -> deploy
```

Workarounds

Do not use a symlink

Severity

Low 2.7 / 10

CVSS base metrics	
Attack vector	Network
Attack complexity	Low
Privileges required	High
User interaction	None
Scope	Unchanged
Confidentiality	Low
Integrity	None
Availability	None

CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:U/C:L/I:N/A:N

CVE ID

CVE-2021-28163

Weaknesses

CWE-200

Credits

 svarovski