TOUCH SCREEN LCD S.

STATUS INDICATOR LAMP



- *For Hospital and Clinics
- *User Friendly
- *LoRa Modulation
- *Low Power consumption

PRODUCT SPECIFICATIONS:

Triage Lamp (Emergency Room)

RF Spec	Frequency	433MHZ
	Modulation	LoRa
	Max. TX Power	18dBm
	Sensitivity	-136dBm
LED	Red	1W
	Yellow	1W
	Green	1W
Tech Spec	Power Input	AC100V-230V/50HZ-60HZ
	Max. Power Consumption	4W
	Standby Power Consumption	Less than 0.1W
	Working Temperature	0°C to 40°C
	Working Humidity	10% to 90 %
	Size	288*50mm*50mm
	Net Weight	230 gram



Touch Screen LCD



Server	Touch LCD	10.1 inch, 1280*800
	DDR2+EMMC	2GB+32GB
	CPU	Intel Atom Z3735F 1.33GHz
	Wifi	IEEE 802.11 b/g/n
	Bluetooth:	4.0
	Operation System	Linux
RF	Frequency	433MHz
	Modulation	LoRa
	Max Tx. Power	18dBm
	Sensitivity	-136dBm
General	Power Input	Adaptor DC5V
	Max. Consumption	10W
	Standby Power	Less than 0.1W
	Working Temperature	0°C to 40°C
	Working Humidity	10% to 90 %
	Size	300*190mm*22mm
	Net Weight	950g

PT. SEMESTA MEDIKA MAKMUR

Jl. Kamal Raya Outer Ring Road, Ruko Mutiara Taman Palem Blok A2 No. 28 Cengkareng Timur - Jakarta Barat 11730 Telp (021) 2951 7888 / 5439 6999, www.semestamedika.com