

The background is a vibrant blue with stylized white and yellow gears. A large magnifying glass with a yellow handle is positioned on the right, focusing on a dark brown bug with yellow and black stripes. The text is overlaid on a dark blue rectangular area.

CISC/CMPE 327 Software Quality Assurance

Queen's University, 2019–fall

Lecture #11 Black Box Unit Testing

Black Box Unit Testing

- Black box **method** testing
 - Test **harnesses**
 - Role of code-level specifications (**assertions**)
 - **Automating** black box unit testing
- Black box **class** testing ("**interface testing**")
 - Class **trace** specifications
 - **Executable** assertions

Black Box Unit Testing

- We can use black box testing to test individual **units** (methods or classes) as we develop them
- Because this kind of unit testing is **black box**, we still have the advantage that tests can be created in **parallel** with coding
- Moreover, black box **unit** testing is earlier and more precise than black box **system** testing
 - It can find errors very early, even before the entire first version is finished

Black Box Unit Testing

- To use black box testing on code units, we need to figure out what corresponds to **requirements**, **inputs**, and **outputs** for units
- Once we know these, test cases can be created according to any of the black box testing criteria:
 - **functionality** coverage
 - **input** coverage
 - **output** coverage

Black Box Testing of **Single Methods**

- If the unit we are testing is a **method** (or function or procedure), then:
 - “**requirements**” = the method’s specification
 - “**input**” = value of parameters, instance variables, global variables used by the method
 - “**output**” = return value, changed instance variables, global variables, and thrown exceptions; together these are referred to as the **outcome** in unit testing

Black Box Testing of **Single Methods**

1. Identify the *input*

1. Identify the *output* (= *outcome*)

Black Box Testing of **Single Methods**

1. Identify the *input*

- method parameters
- instance variables
- global variables
- file I/O, standard input, network reads, ...

2. Identify the *output (= outcome)*

- changed instance variables
- changed global variables
- file I/O, standard output, network writes, ...
- return value **or** thrown exception

Black Box Testing of Single Methods

- For the **push()** method in a **Stack** class implementing stacks of integers
 - **void push (int x)**
throws (stackOverflow)
- The **input** is...
- The **output** is...

Black Box Testing of Single Methods

- For the **push()** method in a **Stack** class implementing stacks of integers
 - **void push (int x)**
throws (StackOverflow)
- The **input** is the current state of the **Stack** object and the parameter value of **x** to push onto it
- The **output** is the new state of the **Stack** object and the exception thrown
- We can then apply, for example, **input partitioning** to create test partitions:
 - P1 **Stack** empty, **x** = 1
 - P2 **Stack** nonempty, **x** = 1
 - P3 **Stack** full, **x** = 1

Executing Unit Tests

- Once we have test cases for a method, we need a way to run them
- A **method** is not a standalone **program**, so we need a special standalone program that calls the method: a **test harness**, which **automates** testing by:
 - Running test cases
 - Generating test reports

Executing Unit Tests

- The test harness sets up an appropriate **environment** to use the unit and invokes it with test input, checking the test **outcome**, and reporting any failure
- The set of test cases are **programmed** in the harness as a sequence of **calls** or uses of the tested unit with the test inputs, with code to check the outcome after each call

Test Harnesses

```
// A test harness to test the push() method
import Stack;
public class TestPush {
    public static void main (String[] args) {
        // Create a Stack object
        Stack s = new Stack();

        // P1 - empty Stack, X=1
        s.Push(1);

        // Check result
        assert s.Depth() == 1
        assert s.TopValue() == 1
        ...
    }
}
```

Independent Unit Testing

- **Factoring Out Unit Dependencies**
 - A problem with unit testing is that units are usually **interdependent**:
the method we are testing may call other methods or use other classes in the software
 - In the worst case, they all call one another
 - So how can we unit test them **individually**?

Independent Unit Testing

- Factoring Out Unit Dependencies
 - The test harness can provide "**stubs**" for the other units
 - The unit being tested then uses the stub method or class instead of the real thing
 - Stub methods are programmed to give "**typical**" outcomes of the real methods they take the place of, instead of a real outcome
 - This allows us to test independently of the real unit the stub replaces

Independent Unit Testing

```
// A stub for a random number generator  
public int randomInt(int a, int b) {  
    return 1;  
}
```

Stub in practice

```
static class TestClass {  
  
    public String getThing() {  
        return "Thing";  
    }  
  
    public String getOtherThing() {  
        return getThing();  
    }  
}  
  
public static void main(String[] args) {  
  
    final TestClass testClass = Mockito.spy(new TestClass());  
  
    Mockito.when(testClass.getThing()).thenReturn("Some Other thing");  
  
    System.out.println(testClass.getOtherThing());  
  
}
```


Things Go Better with a Specification

- **Assertions, Please**
 - When black box unit testing, explicit **pre-** and **post-conditions** for the method we are testing help a lot
 - Pre- and post-conditions help in input and output **coverage analysis**, but more importantly, they help in automating the checking of **outcomes**
 - If an outcome meets the post condition, then we can normally accept it as correct
 - If the pre- and post-conditions are accurate enough, we can even **automate** the black box **testing process** to a large extent

Automating Black Box Unit Testing

- Testing Tools

- Tools such as **Jtest** and **C++test** take advantage of explicit pre-, post-, and invariant assertions in code to **automatically** do naive black box unit testing
- Given **method** and **class** interface specifications explicitly coded as **pre-**, **post-**, and **invariant** assertions written in a special, rich formal **assertion notation**, these tools can provide several benefits

```
public int ItemLength (ItemClass item) {  
    /**  
     * @pre item != null  
     * @post $result > 0  
     */  
    ...  
}
```

Automating Black Box Unit Testing

- Testing Tools

- Automatically generate a **test harness** for the unit
- Automatically provide **stubs** for any other units used by the method or class under test
- Automatically generate some naive **input coverage test cases** and the harness code to run them
- Automation is **naive**, so you can add your own test cases too

Automating Black Box Unit Testing

- Problems with Testing Tools
 - There are some limitations with unit testing tools
 1. Outcomes must be **checked by hand** (at least on the first run) since the tool cannot tell all of what was intended
 - Assertions alone are usually **insufficient**
 2. The tool can't provide **stubs** unless it knows everything that is **called** or **used** by the unit under test, that is, unless it already has the code for the unit
 - Hence, not really **black box** tests

Black Box Class Testing

- Testing a Class Interface
 - Naive black box **class testing** such as that done by the **JTest** and **C++Test** tools simply unit test each method of a class separately
 - In naive class testing, for each method tested,
 - the "**input**" is the current state of all class, object, and global variables as well as the parameters to the method
 - the "**output**" is the new state of all class, object, and global variables as well as the result values and exceptions of the method
 - The class specification usually has an **invariant** assertion that applies to the outcome of every method, as well as the **pre-** and **post-** assertions for each method itself

Class Traces

- Sequences of Method Calls
 - Even very simple classes cannot be well specified, and hence well unit tested, simply by understanding them as a set of **independent** methods
 - The **real** specification of a class often needs to reason about interdependent **sequences** of method calls, not just independent individual calls
 - For example , `stack.pop()` cannot be called before `stack.push()`
 - Assertions are not well suited to specifying this kind of **sequential dependency**

Trace Specifications

- Specifying Sequences
 - Trace specifications are an explicit method for specifying the behaviour of sequences of method calls
 - Trace specifications use trace expressions to specify the legal sequences of method calls to an object in the class
 - A trace expression is a sequence of method calls with inputs and outcomes explicitly specified in the sequence

Trace Specifications

- Example of Specifying Sequences

`s.new() , s.Empty() == true`

`s.new() , s.Push(Y) , s.Pop() == Y , s.Empty() == true`

`s.new() , s.Push(Y) , s.TopValue() == Y ,
s.Pop() == Y , s.Empty() == true`

`s.new() , s.Push(Y) , s.Push(Z) , s.TopValue() == Z ,
s.Pop() == Z , s.Pop() == Y , s.Empty() == true`

Black Box Testing

Using Trace Specifications

- Legal and Illegal Traces
 - Trace specifications constrain the behaviour of a class using both:
 - legal traces (sequences that can or must happen), and
 - illegal traces (sequences that must never happen)
 - Trace specifications not only give us the ability to automate creation of the test harness and naive black box test cases, they also make it easy to generate black box test cases for method call sequences as well

Implementing Assertions

- If we use pre-, post-, and invariant **assertions** to specify our method and class interfaces, it is good practice to actually implement (check) them at **run time** on each method call
- Some languages automatically provide **assertion checking** when the assertions are given as boolean expressions in the language (which may not always be possible)

Implementing Assertions

- Checked assertions help with **every** kind of systematic testing, not just black box unit testing
- Assertions are checked every time the method or class is used, no matter what kind of testing
 - This finds errors **earlier** and pinpoints their **cause** more specifically than simply a bad outcome, because we can see exactly which assertion failed
- It is good practice to always document your specifications, assumptions, and intentions using assertions
 - Helps in **finding errors**, and helps other programmers to understand your **assumptions** and **intentions**

Black Box Integration Testing

- Testing Subsystems

- Black box **integration testing** applies the same ideas to testing **subsystems** integrated from smaller units
- If we began with black box **unit** testing, we can smoothly move into black box integration testing by gradually replacing each **stub** unit in a unit's test harness with the corresponding **real** unit once each has been independently unit tested
- As stubs are replaced and the **combined units** (subsystems) are re-tested at each integration, we gradually build up to the black box testing of the entire integrated system

Summary

- **Black Box Unit Testing**

- Black box testing can also be applied to **unit testing** of individual methods and classes
- **Test harnesses** are special programs written to exercise individual units under test
- **Assertion** and **trace** specifications provide interface level specifications for black box unit testing

- **References**

- Lamb, Software Engineering: Planning for Change, Ch. 13: Trace Specifications

- **Next Week: white box** testing