

Scan Report

May 9, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “scan-frontend-local”. The scan started at Sat May 9 11:07:24 2026 UTC and ended at Sat May 9 12:20:45 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.65.254	2
2.1.1	Medium 8090/tcp	2
2.1.2	Medium 135/tcp	3
2.1.3	Medium 8081/tcp	5
2.1.4	Low general/tcp	6

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.65.254 host.docker.internal	0	0	3	1	0	0
Total: 1	0	0	3	1	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 4 results selected by the filtering described above. Before filtering there were 65 results.

2 Results per Host

2.1 192.168.65.254

Host scan start Sat May 9 11:09:31 2026 UTC

Host scan end Sat May 9 12:20:41 2026 UTC

Service (Port)	Threat Level
8090/tcp	Medium
135/tcp	Medium
8081/tcp	Medium
general/tcp	Low

2.1.1 Medium 8090/tcp

Medium (CVSS: 4.8)

NVT: Cleartext Transmission of Sensitive Information via HTTP

Summary

The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.

... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): http://host.docker.internal:8090/login:j_password
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution: Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure url: https://cwe.mitre.org/data/definitions/319.html

[[return to 192.168.65.254](#)]

2.1.2 Medium 135/tcp

Medium (CVSS: 5.0)

NVT: DCE/RPC and MSRPC Services Enumeration Reporting

Summary

Distributed Computing Environment / Remote Procedure Calls (DCE/RPC) or MSRPC based service enumeration reporting.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

Here is the list of DCE/RPC or MSRPC services running on this host via the TCP protocol:

Port: 49664/tcp

UUID: 12345778-1234-abcd-ef00-0123456789ac, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49664]

Named pipe : lsass

Win32 service or process : lsass.exe

Description : SAM access

UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49664]

Annotation: Ngc Pop Key Service

UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49664]

Annotation: Ngc Pop Key Service

UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2

Endpoint: ncacn_ip_tcp:127.0.0.1[49664]

Annotation: KeyIso

Port: 49665/tcp

UUID: d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49665]

Port: 49666/tcp

UUID: 3a9ef155-691d-4449-8d05-09ad57031823, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49666]

UUID: 86d35949-83c9-4044-b424-db363231fd0c, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49666]

Port: 49667/tcp

UUID: f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49667]

Annotation: Windows Event Log

Port: 49669/tcp

UUID: 0b6edbfa-4a24-4fc6-8a23-942b1eca65d1, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49669]

UUID: 12345678-1234-abcd-ef00-0123456789ab, version 1

Endpoint: ncacn_ip_tcp:127.0.0.1[49669]

Named pipe : spoolss

Win32 service or process : spoolsv.exe

Description : Spooler service

UUID: 4a452661-8290-4b36-8fbe-7f4093a94978, version 1

... continues on next page ...

...continued from previous page ... Endpoint: ncacn_ip_tcp:127.0.0.1[49669] UUID: 76f03f96-cdfd-44fc-a22c-64950a001209, version 1 Endpoint: ncacn_ip_tcp:127.0.0.1[49669] UUID: ae33069b-a2a8-46ee-a235-ddfd339be281, version 1 Endpoint: ncacn_ip_tcp:127.0.0.1[49669] Port: 49689/tcp UUID: 367abb81-9844-35f1-ad32-98f038001003, version 2 Endpoint: ncacn_ip_tcp:127.0.0.1[49689] Note: DCE/RPC or MSRPC services running on this host locally were identified. Reporting this list is not enabled by default due to the possible large size of this list. See the script preferences to enable this reporting.
Impact An attacker may use this information to gain more knowledge about the remote host and to conduct further attacks based on it.
Solution: Solution type: Mitigation Filter incoming traffic to this ports.
Affected Software/OS All systems exposing / disclosing information via DCE/RPC or MSRPC services.
Vulnerability Insight DCE/RPC or MSRPC services running on the remote host can be enumerated by connecting on port 135 and doing the appropriate queries.
Vulnerability Detection Method Reports previously collected (via 'DCE/RPC and MSRPC Services Enumeration' OID: 1.3.6.1.4.1.25623.1.0.108044) DCE/RPC or MSRPC services. This VT is reporting a severity by default. If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN': Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288) In this case a 'Log' level result is used instead. Details: DCE/RPC and MSRPC Services Enumeration Reporting OID:1.3.6.1.4.1.25623.1.0.10736 Version used: 2025-11-26T05:40:08Z

[\[return to 192.168.65.254 \]](#)

2.1.3 Medium 8081/tcp

Medium (CVSS: 4.8) NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): <code>http://host.docker.internal:8081/login:password</code>
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution: Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure url: https://cwe.mitre.org/data/definitions/319.html

[\[return to 192.168.65.254 \]](#)

2.1.4 Low general/tcp

Low (CVSS: 2.6) NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 1063808310 Packet 2: 1063809394
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[\[return to 192.168.65.254 \]](#)

This file was automatically generated.