
The copying, distribution and utilistion of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

Mechanical data (according to IEC 61076-2-101)		Material	
no. of poles / coding	12 / A (with shield connection)	contacts / surface	CuZn with gold layer
contact termination	dip solder / socket	contact carrier colour	PA6T/66 black
contact-Ø	12xØ0,6mm		
temperature range	-40 °C to +105 °C	sealing gasket	FKM
protection class	IP67		
mating cycles	>100		

further information:
- see technical data M12-3


While mounting the insulating body with o-ring into the housing, the axial mounting force on each connnector shouldn't be higher than 80N.
Avoid radial forces!



All specified data refers to the mounted M12 installation plugs ≥ IP54 and requires that the connector pair be correctly plugged and locked. Influences from wires, cables or PCB mounting are also to be taken into consideration.

drilling plan
component side (front view PC-Board)

* measure X depends on the installed housing, see installation recommendation of the housing series M12 DSIV



further dimensioning see page 2

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen.
CONINVERS GmbH Heisenbergstrasse 1 D-71083 Herrenberg


general tolerance acc. to DIN ISO 2768-c			technical changes reserved	Index 3 / 2012-06-25	scale: 2:1
	date	name	Series DSIV M12-socket-contact carrier 12-pole socket/A-coding/angled/shield connection		page: 1 of: 2
design	2012-03-23	Hieber			
chk.					
			drawing-no.: BS-12S2NF20000	doc.-no.: 00655507	
			order-no.: 1424199		
			article designation: SACC-CI-M12FS-12CON-L90 SH		


The copying, distribution and utilistion of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem §18 UWG verboten. soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen. CONINVERS GmbH Heisenbergstrasse 1 D-71083 Herrenberg

drilling plan

component side (front view PC-Board)





dimensioning in relation to reference point

bore	X	Y
1	6,07	4,3
2	8,93	4,3
3	10,17	2,9
4	10,3	1,27
5	9,27	-0,2
6	7,5	-0,2
7	5,73	-0,2
8	4,7	1,27
9	4,83	2,9
10	7,5	2,9
11	8,45	1,27
12	6,55	1,27

general tolerance acc. to DIN ISO 2768-c			technical changes reserved	Index 3 / 2012-06-25	scale: 4:1
	date	name	Series DSIV M12-socket-contact carrier 12-pole socket/A-coding/angled/shield connection		page: 2 of: 2
design	2012-03-23	Hieber			
chk.					
			drawing-no.:	BS-12S2NF20000	doc.-no.: 00655507
			order-no.:	1424199	
			article designation:	SACC-C1-M12FS-12CON-L90 SH	

PHOENIX CONTACT