
The copying, distribution and utilistion of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

| Mechanical data (according to IEC 61076-2-101) | |
|---|---|
| no. of poles / coding | 5 / A |
| contact termination | dip solder / socket |
| contact-Ø | 5xØ1mm |
| temperature range | -40 °C to +105 °C |
| protection class | IP67 |
| mating cycles | >100 |

| Material | |
|---|---|
| contacts / surface | CuZn with gold layer |
| contact carrier colour | PA6T / 66 black |
| sealing gasket | FKM |


further information:
- see technical data M12-3

While mounting the insulating body with o-ring into the housing, the axial mounting force on each connnector shouldn't be higher than 80N.
Avoid radial forces!




All specified data refers to the mounted M12 installation plugs >IP54 and requires that the connector pair be correctly plugged and locked. Influences from wires, cables or PCB mounting are also to be taken into consideration.

# drilling plan
## component side (front view PC-Board)




* measure X depends on the installed housing, see installation recommendation of the housing series M12 DSIV

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen.
PHOENIX CONTACT Connector Technology GmbH Heisenbergstrasse 1 D-71083 Herrenberg

| general tolerance acc. to DIN ISO 2768-c | | |
|---|---|---|
| | date | name |
| design | 2012-06-19 | Thumm |
| chk. | | |
| | | |

technical changes reserved | Index 1 / 2012-06-19 | scale: 2:1

Series DSIV
M12-socket-contact carrier
5-pole socket/A-coding/angled

page: 1 of: 1

| | | | |
|---|---|---|---|
| drawing-no.: | BS-05S2ND20000 | doc.-no.: | 00667978 |
| order-no.: | 1436644 | | |
| article designation: | SACC-CI-M12FS-5CON-L90 SCO | | |