

Introductory Applied Machine Learning

Naïve Bayes

Victor Lavrenko and Charles Sutton
School of Informatics

- Naïve Bayes classifier
 - components and their function
 - independence assumption
 - dealing with missing data
- Continuous example
- Discrete example
- Pros and cons

Copyright © Victor Lavrenko, 2011

Bayesian classification

- Goal: learning function $f(x) \rightarrow y$
 - y ... one of k classes (e.g. spam/ham, digit 0-9)
 - $x = x_1 \dots x_n$ – values of attributes (numeric or categorical)
- Probabilistic classification:
 - most probable class given observation: $\hat{y} = \underset{y}{\arg \max} P(y|x)$
- Bayesian probability of a class:

$$P(y|x) = \frac{\overbrace{P(x|y)}^{\text{class model}} \overbrace{P(y)}^{\text{prior}}}{\underbrace{\sum_{y'} P(x|y') P(y')}_{\text{normalizer } P(x)}}$$

Bayesian classification: components

$$P(y|x) = \frac{P(x|y)P(y)}{\sum_{y'} P(x|y')P(y')}$$

Example:
 y ... patient has Avian flu
 x ... observed symptoms


- $P(y)$: prior probability of each class
 - encodes how which classes are common, which are rare
 - apriori much more likely to have common cold than Avian flu
- $P(x|y)$: class-conditional model
 - describes how likely to see observation x for class y
 - assuming it's Avian flu, do the symptoms look plausible?
- $P(x)$: normalize probabilities across observations

Bayesian classification: normalization

Normalizer: $P(x) = \sum_{y'} P(x|y')P(y')$

- an “outlier” has a low probability under every class

$$P(X=x_1 | Y=3) < P(X=x_2 | Y=3)$$




normalizer makes $P(Y=3|X=x_1)$ comparable to non-outliers

Copyright © Victor Lavrenko, 2011

Naïve Bayes: a generative model

- A complete probability distribution for each class
 - defines likelihood for any point x
 - $P(\text{class})$ via $P(\text{observation})$ $P(y|x) \propto P(x|y)P(y)$
 - can “generate” synthetic observations
 - will share many properties of the original data
- Not all probabilistic classifiers do this
 - possible to estimate $P(y|x)$ directly
 - e.g. log-linear model


$$P(y|x) = \frac{1}{z_y} \exp\left(\sum_i \lambda_i g_i(y, x)\right)$$



Copyright © Victor Lavrenko, 2011

Independence assumption

- Compute $P(x_1 \dots x_n | y)$ for every observation $x_1 \dots x_n$
 - class-conditional “counts”, based on training data
 - problem: may not have seen every $x_1 \dots x_n$ for every y
 - digits: 2^{400} possible black/white patterns (20x20)
 - spam: every possible combination of words: $2^{10,000}$
 - often have observations for individual x_i for every class
- Main idea: assume $x_1 \dots x_n$ independent given y



$$P(x_1 \dots x_d | y) = \underbrace{\prod_{i=1}^d P(x_i | x_1 \dots x_{i-1}, y)}_{\text{chain rule (exact)}} = \underbrace{\prod_{i=1}^d P(x_i | y)}_{\text{independence}}$$


Copyright © Victor Lavrenko, 2011

Conditional independence

- Probabilities of going to the beach and getting a heat stroke are not independent: $P(B, S) > P(B)P(S)$
- May be independent if we know the weather is hot

$$P(B, S | H) = P(B | H)P(S | H)$$

- Hot weather “explains” all the dependence between beach and heatstroke
- In classification:
 - class value explains all the dependence between attributes



Example © Amos Storkey, 2007

Copyright © Victor Lavrenko, 2011

Overview

- Naïve Bayes classifier
- Continuous example
 - general concepts
 - working example
 - example of failure
- Discrete example
 - general concepts
 - problems with Naïve Bayes
- Pros and cons


Continuous example

- Distinguish children from adults based on size
 - classes: $\{a, c\}$, attributes: height [cm], weight [kg]
 - training examples: $\{h_i, w_i, y_i\}$, 4 adults, 12 children
- Class probabilities: $P(a) = \frac{4}{4+12} = 0.25$; $P(c) = 0.75$
- Model for adults:
 - height \sim Gaussian with mean, variance
 - weight \sim Gaussian $(\mu_{w,a}, \sigma_{w,a}^2)$
 - assume height and weight independent
- Model for children: same, using $(\mu_{h,c}, \sigma_{h,c}^2), (\mu_{w,c}, \sigma_{w,c}^2)$

Copyright © Victor Lavrenko, 2011


Copyright © Victor Lavrenko, 2011

Continuous example



Copyright © Victor Lavrenko, 2011

Problems with Naïve Bayes



Copyright © Victor Lavrenko, 2011

Discrete example: spam

- Separate spam from valid email, attributes = words

D1: "send us your password" **spam**
 D2: "send us your review" **ham**
 D3: "review your password" **ham**
 D4: "review us" **spam**
 D5: "send your password" **spam**
 D6: "send us your account" **spam**

new email: "review us **now**"

P (spam) = 4/6 P (ham) = 2/6		
spam	ham	
2/4	1/2	password
1/4	2/2	review
3/4	1/2	send
3/4	1/2	us
3/4	1/2	your
1/4	0/2	account

$$P(\text{review us} | \text{spam}) = P(0, 1, 0, 1, 0, 0 | \text{spam}) = (1 - \frac{2}{4}) (\frac{1}{4}) (1 - \frac{3}{4}) (\frac{3}{4}) (1 - \frac{3}{4}) (1 - \frac{1}{4})$$

$$P(\text{review us} | \text{ham}) = P(0, 1, 0, 1, 0, 0 | \text{ham}) = (1 - \frac{1}{2}) (\frac{2}{2}) (1 - \frac{1}{2}) (\frac{1}{2}) (1 - \frac{1}{2}) (1 - \frac{0}{2})$$

$$P(\text{ham} | \text{review us}) = \frac{0.0625 \times 2/6}{0.0625 \times 2/6 + 0.0044 \times 4/6} = 0.87 \text{ (note identical example)}$$

Copyright © Victor Lavrenko, 2011

Overview

- Naïve Bayes classifier
- Continuous example
- Discrete example
- Pros and Cons
 - dealing with missing data
 - computational cost and incremental updates

Copyright © Victor Lavrenko, 2011

Problems with Naïve Bayes

- Zero-frequency problem

- any mail containing "account" is spam: $P(\text{account} | \text{ham}) = 0/2$

- solution: never allow zero probabilities

- Laplace smoothing: add a small positive number to all counts:

$$P(w|c) = \frac{\text{num}(w, c) + \epsilon}{\text{num}(c) + 2\epsilon}$$

- may use global statistics in place of ϵ : $\text{num}(w) / \text{num}$

- very common problem (Zipf's law: 50% words occur once)

- Assumes word independence

- every word contributes independently to $P(\text{spam} | \text{email})$

- fooling NB: add lots of "hammy" words into spam email

Copyright © Victor Lavrenko, 2011

Missing data

- Suppose don't have value for some attribute X_i

- applicant's credit history unknown
- some medical test not performed on patient
- how to compute $P(X_1=x_1 \dots X_j=? \dots X_d=x_d | y)$

- Easy with Naïve Bayes

- ignore attribute in instance where its value is missing
- compute likelihood based on observed attributes
- no need to "fill in" or explicitly model missing values
- based on conditional independence between attributes


$$P(x_1 \dots \boxed{X_j} \dots x_d | y) = \prod_{i \neq j}^d P(x_i | y)$$

Copyright © Victor Lavrenko, 2011

Missing data (2)

- Ex: three coin tosses: Event = $\{X_1=H, X_2=?, X_3=T\}$

- event = head, unknown (either head or tail), tail
- event = $\{H,H,T\} + \{H,T,T\}$
- $P(\text{event}) = P(H,H,T) + P(H,T,T)$



- General case: X_j has missing value

$$P(x_1 \dots x_j \dots x_d | y) = P(x_1 | y) \dots P(x_j | y) \dots P(x_d | y)$$

$$\begin{aligned} \sum_{x_j} P(x_1 \dots x_j \dots x_d | y) &= \sum_{x_j} P(x_1 | y) \dots P(x_j | y) \dots P(x_d | y) \\ &= P(x_1 | y) \dots \left[\sum_{x_j} P(x_j | y) \right] \dots P(x_d | y) \\ &= P(x_1 | y) \dots [1] \dots P(x_d | y) \end{aligned}$$

Copyright © Victor Lavrenko, 2011

Computational complexity

- One of the fastest learning methods
- $O(ndc)$ time complexity
 - c ... number of classes
 - n ... number of instances
 - d ... number of dimensions (attributes)
 - both learning and prediction
 - no hidden constants (number of iterations, etc.)
- $O(dc)$ space complexity
 - only decision trees are more compact

Copyright © Victor Lavrenko, 2011

Incremental updates

- Allows incremental updates: $O(d)$ insertion / deletion
- Bernoulli: store raw counts instead of probabilities
 - new example of class c :
 - $n_{cd} += x_d$ for each d , $n_c += 1$, $n += 1$
 - when need to classify:
 - $P(x_d=1 | c) = n_{cd} / n_c$
 - $P(c) = n_c / n$
- Gaussian: store partial sums instead of mean/variance
 - $s_{cd} += x_d$ $s_{cd}^2 += x_d^2$
 - when need to classify:
 - mean = s_{cd} / n variance = $s_{cd}^2 / n - \text{mean}^2$

Copyright © Victor Lavrenko, 2011

General structure for Naïve Bayes

- **Task**
 - k -class classification ($k \geq 2$)
- **Model structure**
 - $k \times d$ independent distributions
 - continuous: Gaussian, discrete: Bernoulli
- **Score function**
 - class-conditional likelihood
- **Optimization / search method**
 - analytic solution

Copyright © Victor Lavrenko, 2011

Summary

- Naïve Bayes classifier
 - explicitly handles class priors
 - “normalizes” across observations: outliers comparable
 - naturally handles missing data
 - assumption: all dependence is “explained” by class label
- Continuous example
 - unable to handle correlated data
- Discrete example
 - fooled by repetitions
 - must deal with zero-frequency problem
 - Pros: missing data, computational complexity, updates