

Nama : REZA MIFTAHUL RIZKI

NIM : L200170108

Kelas : C

## KEGIATAN 1

### Tugas 1A:

1. Pilih pada bagian Network Devices → Switches → pilih tipe 2950-24 → letakkan 3 switch
2. Pilih pada bagian End Devices → Generic Computer → letakkan 3 computer
3. Hubungkan dengan kabel. Pilih connections → pilih gambar petir lalu sambungkan

### Tugas 2A:

→

Switch 1

Switch>enable

Switch#conf term


Switch(config)#hostname SW1

SW1(config)#


Begitupun dengan switch yang lain

### Tugas 4A:

- SW1



## - SW2



```

SW2
Physical Config CLI Attributes
IOS Command Line Interface

%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up


Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname SW2
SW2(config)#exit
SW2#
%SYS-5-CONFIG_I: Configured from console by console

SW2#show spanning-tree
VLAN0001
  Spanning tree enabled protocol ieee
    Root ID    Priority    32769
              Address    0000.0C49.161A
              Cost      19
              Port      3(FastEthernet0/3)
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

    Bridge ID  Priority    32769 (priority 32768 sys-id-ext 1)
              Address    0001.42D4.E166
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
              Aging Time 20

Interface      Role Sts Cost      Prio.Nbr Type
-----
Fa0/3          Root FWD 19        128.3   P2p
Fa0/1          Desg FWD 19        128.1   P2p
Fa0/2          Desg FWD 19        128.2   P2p
  
```

## -SW3



```

SW3
Physical Config CLI Attributes
IOS Command Line Interface

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up

Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname SW3
SW3(config)#exit
SW3#
%SYS-5-CONFIG_I: Configured from console by console

SW3#show spanning-tree
VLAN0001
  Spanning tree enabled protocol ieee
    Root ID    Priority    32769
              Address    0000.0C49.161A
              This bridge is the root
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

    Bridge ID  Priority    32769 (priority 32768 sys-id-ext 1)
              Address    0000.0C49.161A
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
              Aging Time 20

Interface      Role Sts Cost      Prio.Nbr Type
-----
Fa0/1          Desg FWD 19        128.1   P2p
Fa0/2          Desg FWD 19        128.2   P2p
Fa0/3          Desg FWD 19        128.3   P2p
  
```

**Tugas 4B:**

-SW1

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0030.A3B7.A5A0 |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

-SW2

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0001.42D4.E166 |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

- SW3

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0000.0C49.161A |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

**Tugas 4C:**

- root bridge: SW3

- designed bridge: SW2

- root port: SW1(fa 0/3) dan SW2(fa 0/3)

- designed port: SW1(fa 0/1), SW2(fa 0/1; fa 0/2), dan SW3(fa 0/1; fa 0/2; fa 0/3)

#### ***Tugas 4D:***

- forwarding:


- SW1(fa 0/1; fa 0/3)
- SW2(fa 0/1; fa 0/2; fa 0/3)
- SW3(fa 0/1; fa 0/2; fa 0/3)

- blocking

- SW1(fa 0/2)

#### **Tugas 5A:**

1. Klik pada pc leo
2. Pilih tab desktop
3. Pilih command prompt
4. Tuliskan ping 172.21.1.3



```
Packet Tracer PC Command Line 1.0
C:\>ping 172.21.1.3

Pinging 172.21.1.3 with 32 bytes of data:

Reply from 172.21.1.3: bytes=32 time=37ms TTL=128
Reply from 172.21.1.3: bytes=32 time=3ms TTL=128
Reply from 172.21.1.3: bytes=32 time<1ms TTL=128
Reply from 172.21.1.3: bytes=32 time<1ms TTL=128

Ping statistics for 172.21.1.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 37ms, Average = 10ms

C:\>|
```


#### ***Tugas 6A:***

1. Pilih file
2. Pilih save
3. Beri nama lab2 yang akan berkestensi sesuai aplikasi yang digunakan


## Kegiatan 2:

### Tugas 9A:


- SW1



-SW2



-SW3



-SW1

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0030.A3B7.A5A0 |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

-SW2

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0001.42D4.E166 |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

- SW3

| No | Variabel          | Nilai          |
|----|-------------------|----------------|
| 1  | Root ID           | 32769          |
| 2  | Priority          | 32768          |
| 3  | MAC Address       | 0000.0C49.161A |
| 4  | Bridge ID         | 32769          |
| 5  | Cost(0/1;0/2;0/3) | 19             |
| 6  | Hello Time        | 2 sec          |
| 7  | MaxAge            | 20 sec         |
| 8  | Fordward Delay    | 15 sec         |

- root bridge: SW3

- designed bridge: SW1, SW2

- root port: SW1(fa 0/3) dan SW2(fa 0/3)

- designed port: SW1(fa 0/1), SW2(fa 0/1), dan SW3(fa 0/1; fa 0/2; fa 0/3)

- forwarding:

- SW1(fa 0/1; fa 0/3)
- SW2(fa 0/1; fa 0/3)
- SW3(fa 0/1; fa 0/2; fa 0/3)

- blocking: tidak ada yang terblock