


Nama : TYAS MELANI

Nim : L200170111

Kelas : C

## Kegiatan 1

Untuk langkah no 1,2,3



#### Langkah No 4.

Physical

Config

CLI

Attributes

IOS Command Line Interface

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan zodiak 1
^
% Invalid input detected at '^' marker.

Switch(config)#vlan 10
Switch(config-vlan)#name zodiak1
Switch(config-vlan)#exit
Switch(config)#vlan 20
Switch(config-vlan)#name zodiak2
Switch(config-vlan)#exit
Switch(config)#vlan 30
Switch(config-vlan)#name zodiak3
Switch(config-vlan)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#enable
Switch#show vlan brief
```

VLAN	Name	Status	Ports
1	default	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24
10	zodiak1	active	
20	zodiak2	active	
30	zodiak3	active	
1002	fddi-default	active	
1003	token-ring-default	active	
1004	fddinet-default	active	

Ctrl+F6 to exit CLI focus

## Langkah No 5.

Physical
Config
CLI
Attributes

IOS Command Line Inter

```

Switch#enable
Switch#show vlan brief

VLAN Name                Status    Ports
-----
1    default                active    Fa0/1, Fa0/2, Fa0/3, Fa0/4
                                           Fa0/5, Fa0/6, Fa0/7, Fa0/8
                                           Fa0/9, Fa0/10, Fa0/11, Fa0/12
                                           Fa0/13, Fa0/14, Fa0/15, Fa0/16
                                           Fa0/17, Fa0/18, Fa0/19, Fa0/20
                                           Fa0/21, Fa0/22, Fa0/23, Fa0/24
10   zodiak1                active
20   zodiak2                active
30   zodiak3                active
1002 fddi-default          active
1003 token-ring-default    active
1004 fddinet-default       active
1005 trnet-default         active
Switch#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#interface FastEthernet 0/1
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#interface FastEthernet 0/4
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#exit
Switch(config)#
%LINK-5-CHANGED: Interface FastEthernet0/6, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/6, changed state to down

%LINK-5-CHANGED: Interface FastEthernet0/6, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/6, changed state to up

Switch(config)#int Fa 0/1
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 10

```

Ctrl+F6 to exit CLI focus

Physical	Config	CLI	Attributes
----------	--------	-----	------------

IOS Command Line Interface

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/6, changed state to up

Switch(config)#int Fa 0/1
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 10
Switch(config-if)#int Fa 0/4
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 10
Switch(config-if)#exit
Switch(config)#int Fa 0/2
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#int Fa 0/5
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#exit
Switch(config)#int Fa 0/3
Switch(config-if)#sw mode access vlan 30'
^
% Invalid input detected at '^' marker.

Switch(config-if)#sw mode access vlan 30
^
% Invalid input detected at '^' marker.

Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 30
Switch(config-if)#int Fa 0/6
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 30
Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show id 10
^
% Invalid input detected at '^' marker.
```

Ctrl+F6 to exit CLI focus

Langkah No 6.

Physical

Config

CLI

Attributes

IOS Command Line Interface

Switch(config-if)#sw access vlan 30

Switch(config-if)#int Fa 0/6

Switch(config-if)#sw mode access

Switch(config-if)#sw access vlan 30

Switch(config-if)#exit

Switch(config)#exit

Switch#

%SYS-5-CONFIG\_I: Configured from console by console

Switch#show id 10

^

% Invalid input detected at '^' marker.

Switch#show vlan brief

VLAN Name	Status	Ports
1 default	active	Fa0/7, Fa0/8, Fa0/9, Fa0/10 Fa0/11, Fa0/12, Fa0/13, Fa0/14 Fa0/15, Fa0/16, Fa0/17, Fa0/18 Fa0/19, Fa0/20, Fa0/21, Fa0/22 Fa0/23, Fa0/24
10 zodiak1	active	Fa0/1, Fa0/4
20 zodiak2	active	Fa0/2, Fa0/5
30 zodiak3	active	Fa0/3, Fa0/6
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 vtrnet-default	active	

Switch#show vlan id 10

VLAN Name	Status	Ports
10 zodiak1	active	Fa0/1, Fa0/4

VLAN Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
10	enet	100010	1500	-	-	-	-	0	0

Ctrl+F6 to exit CLI focus

Physical
Config
CLI
Attributes

IOS Command Line Interface

```

10 zodiak1 active Fa0/1, Fa0/4
20 zodiak2 active Fa0/2, Fa0/5
30 zodiak3 active Fa0/3, Fa0/6
1002 fddi-default active
1003 token-ring-default active
1004 fddinet-default active
1005 trnet-default active
Switch#show vlan id 10

VLAN Name                Status    Ports
-----
10 zodiak1                active    Fa0/1, Fa0/4

VLAN Type  SAID      MTU   Parent RingNo BridgeNo Stp   BrdgMode Trans1 Trans2
-----
10  enet  100010   1500   -     -     -     -     -         0       0

Switch#show vlan id 20

VLAN Name                Status    Ports
-----
20 zodiak2                active    Fa0/2, Fa0/5

VLAN Type  SAID      MTU   Parent RingNo BridgeNo Stp   BrdgMode Trans1 Trans2
-----
20  enet  100020   1500   -     -     -     -     -         0       0

Switch#show vlan id 30

VLAN Name                Status    Ports
-----
30 zodiak3                active    Fa0/3, Fa0/6

VLAN Type  SAID      MTU   Parent RingNo BridgeNo Stp   BrdgMode Trans1 Trans2
-----
30  enet  100030   1500   -     -     -     -     -         0       0

Switch#

```

Ctrl+F6 to exit CLI focus

Tugas 6A :

No	Variabel	Nilai		
1.	Nomor Vlan	10	20	30
2.	Nama Vlan	zodiak1	zodiak2	zodiak3
3.	Port	Fa 0/1, Fa 0/4	Fa 0/2, Fa 0/5	Fa 0/3, Fa 0/6
4.	Status	Active	Active	Active

Tugas 6B :


Penjelasan dari table diatas :

- Nomor Vlan 10 nama Vlan zodiak1, memiliki port Fa 0/2(leo) dan Fa 0/4 (Libra). Yang sudah di konfigurasi sesuai dengan yang ada di modul yang statusnya bersifat active. Yang setiap PC sudah mempunyai Ip nya masing masing
- Nomor Vlan 20 nama Vlan zodiak1, memiliki port Fa 0/2(Aries) dan Fa 0/5 (Taurus). Yang sudah di konfigurasi sesuai dengan yang ada di modul yang statusnya bersifat active. Yang setiap PC sudah mempunyai Ip nya masing masing

- Nomor Vlan 30 nama Vlan zodiak1, memiliki port Fa 0/3(virgo) dan Fa 0/6 (Scorpio). Yang sudah di konfigurasi sesuai dengan yang ada di modul yang statusnya bersifat active. Yang setiap PC sudah mempunyai Ip nya masing masing

## Kegiatan 2

Untuk langkah nomor 1,2,3,4



5. untuk SW1 Sudah di sertakan pada SS an kegiatan pertama

Untuk SW2 :

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/7, changed state to up
```

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 10
Switch(config-vlan)#name zodiak1
Switch(config-vlan)#exit
Switch(config)#vlan 20
Switch(config-vlan)#name zodiak2
Switch(config-vlan)#exit
Switch(config)#vlan 30
Switch(config-vlan)#name zodiak3
Switch(config-vlan)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console
```

```
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#inter Fa 0/1
Switch(config-if)#switchport mode acces
Switch(config-if)#switchport access vlan 10
Switch(config-if)#inter Fa 0/2
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#exit
Switch(config)#int Fa 0/3
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#inter Fa 0/4
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#exit
Switch(config)#inter Fa 0/5
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 30
```

Ctrl+F6 to exit CLI focus



Untuk langkah Nomor 6 dan 7

IOS Command Line Interface

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#interface fa 0/7
Switch(config-if)#switchport mode trunk

Switch(config-if)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/7, changed state to down
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/7, changed state to up

Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show interface trunk
Port      Mode      Encapsulation  Status        Native vlan
Fa0/7     on        802.1q         trunking      1

Port      Vlans allowed on trunk
Fa0/7     1-1005

Port      Vlans allowed and active in management domain
Fa0/7     1,10,20,30

Port      Vlans in spanning tree forwarding state and not pruned
Fa0/7     1,10,20,30

Switch#show vlan

VLAN Name                Status    Ports
-----
1    default              active    Fa0/8, Fa0/9, Fa0/10, Fa0/11
                                           Fa0/12, Fa0/13, Fa0/14, Fa0/15
                                           Fa0/16, Fa0/17, Fa0/18, Fa0/19
                                           Fa0/20, Fa0/21, Fa0/22, Fa0/23
                                           Fa0/24
10   zodiakl              active    Fa0/1, Fa0/4
```

Physical
Config
CLI
Attributes

IOS Command Line Interface

```

Switch#show interface trunk
Port      Mode      Encapsulation  Status      Native vlan
Fa0/7     on        802.1q         trunking    1

Port      Vlans allowed on trunk
Fa0/7     1-1005

Port      Vlans allowed and active in management domain
Fa0/7     1,10,20,30

Port      Vlans in spanning tree forwarding state and not pruned
Fa0/7     1,10,20,30

Switch#show vlan

VLAN Name                Status    Ports
-----
1    default                active    Fa0/8, Fa0/9, Fa0/10, Fa0/11
                                           Fa0/12, Fa0/13, Fa0/14, Fa0/15
                                           Fa0/16, Fa0/17, Fa0/18, Fa0/19
                                           Fa0/20, Fa0/21, Fa0/22, Fa0/23
                                           Fa0/24
10   zodiak1                 active    Fa0/1, Fa0/4
20   zodiak2                 active    Fa0/2, Fa0/5
30   zodiak3                 active    Fa0/3, Fa0/6
1002 fddi-default           active
1003 token-ring-default    active
1004 fddinet-default        active
1005 trnet-default          active

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp    BrdgMode Trans1 Trans2
-----
1    enet    100001    1500    -      -      -      -      -      0      0
10   enet    100010    1500    -      -      -      -      -      0      0
20   enet    100020    1500    -      -      -      -      -      0      0
30   enet    100030    1500    -      -      -      -      -      0      0
--More--

```


Ctrl+F6 to exit CLI focus

## 7A: Penjelasan

Hasil yang diperoleh pada mode privileged pada switch 1 yaitu pada vlans allowed on trunk mempunyai nilai 1-1005 pada port fa 0/7 yang artinya menggunakan jaringan skala kecil dan menengah. Vlan allowed and active in management domain (config untuk manajemen switch) memiliki nilai 1,10,20,30. vlans spanning tree forwarding state and not pruned mempunyai nilai 1,10,20,30.

Mempunyai status trunking mode on, encapsulation 802.1q ( protokol umum yang didukung oleh banyak vektor)

## 8. ping PC leo dan PC pisces



The screenshot shows the 'Command Prompt' window within the Packet Tracer interface. The window title is 'Command Prompt'. The text inside the window is as follows:

```
Packet Tracer PC Command Line 1.0
C:\>ping 172.21.3.3

Pinging 172.21.3.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.


Ping statistics for 172.21.3.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>
```

Penjelasan :

Hasil ping dari pc leo ke pc pisces bukanlah reply, tetapi request timed out (RTO), karena permintaan koneksi yang lama dan subnet address nya sudah berbeda.

## 9.



The screenshot shows a network switch configuration session. The text inside the window is as follows:

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#interface fa 0/7
Switch(config-if)#sw mode trunk
Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#
```

## 10. pada Mode privileged

Physical

Config

CLI

Attributes

IOS Command Line Interface

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#interface fa 0/7
Switch(config-if)#sw mode trunk
Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show vlan
```

VLAN Name	Status	Ports
1 default	active	Fa0/6, Fa0/8, Fa0/9, Fa0/10 Fa0/11, Fa0/12, Fa0/13, Fa0/14 Fa0/15, Fa0/16, Fa0/17, Fa0/18 Fa0/19, Fa0/20, Fa0/21, Fa0/22 Fa0/23, Fa0/24
10 zodiak1	active	Fa0/1, Fa0/2
20 zodiak2	active	Fa0/3, Fa0/4
30 zodiak3	active	Fa0/5
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
10	enet	100010	1500	-	-	-	-	-	0	0
20	enet	100020	1500	-	-	-	-	-	0	0
30	enet	100030	1500	-	-	-	-	-	0	0

--More--

Ctrl+F6 to exit CLI focus

Physical
Config
CLI
Attributes

IOS Command Line Interface

```

Switch#show interface trunk
Port      Mode      Encapsulation  Status      Native vlan
Fa0/7     on        802.1q         trunking    1

Port      Vlans allowed on trunk
Fa0/7     1-1005

Port      Vlans allowed and active in management domain
Fa0/7     1,10,20,30

Port      Vlans in spanning tree forwarding state and not pruned
Fa0/7     1,10,20,30

Switch#show vlan

VLAN Name                Status    Ports
-----
1    default                active    Fa0/8, Fa0/9, Fa0/10, Fa0/11
                                           Fa0/12, Fa0/13, Fa0/14, Fa0/15
                                           Fa0/16, Fa0/17, Fa0/18, Fa0/19
                                           Fa0/20, Fa0/21, Fa0/22, Fa0/23
                                           Fa0/24
10   zodiak1                 active    Fa0/1, Fa0/4
20   zodiak2                 active    Fa0/2, Fa0/5
30   zodiak3                 active    Fa0/3, Fa0/6
1002 fddi-default           active
1003 token-ring-default    active
1004 fddinet-default        active
1005 trnet-default          active

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp    BrdgMode Trans1 Trans2
-----
1    enet    100001    1500   -      -      -      -      -      0      0
10   enet    100010    1500   -      -      -      -      -      0      0
20   enet    100020    1500   -      -      -      -      -      0      0
30   enet    100030    1500   -      -      -      -      -      0      0
--More--

```

Ctrl+F6 to exit CLI focus

Penjelasan 10A :

Hasil yang diperoleh pada mode privileged pada switch 1 yaitu pada vlans allowed on trunk mempunyai nilai 1-1005 pada port fa 0/7 yang artinya menggunakan jaringan skala kecil dan menengah. Vlan allowed and active in management domain (config untuk manajemen switch) memiliki nilai 1,10,20,30. vlans spanning tree forwarding state and not pruned mempunyai nilai 1,10,20,30.

Mempunyai status trunking mode on, encapsulation 802.1q ( protokol umum yang didukung oleh banyak vektor)

11.

Physical	Config	CLI	Attributes
----------	--------	-----	------------

IOS Command Line Interface

```
%LINEPROTO-S-UPDOWN: Line protocol on Interface FastEthernet0/6, changed state to up

Switch(config)#int Fa 0/1
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 10
Switch(config-if)#int Fa 0/4
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 10
Switch(config-if)#exit
Switch(config)#int Fa 0/2
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#int Fa 0/5
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 20
Switch(config-if)#exit
Switch(config)#int Fa 0/3
Switch(config-if)#sw mode access vlan 30'
      ^
% Invalid input detected at '^' marker.

Switch(config-if)#sw mode access vlan 30
      ^
% Invalid input detected at '^' marker.

Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 30
Switch(config-if)#int Fa 0/6
Switch(config-if)#sw mode access
Switch(config-if)#sw access vlan 30
Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show id 10
      ^
% Invalid input detected at '^' marker.
```

Ctrl+F6 to exit CLI focus

12.

a) Ping PC leo ke PC aries

```
C:\>ping 172.21.1.2

Pinging 172.21.1.2 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.1.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>|
```

- b) Ping PC leo ke PC aquarius

```
C:\>ping 172.21.1.3

Pinging 172.21.1.3 with 32 bytes of data:

Reply from 172.21.1.3: bytes=32 time<1ms TTL=128
Reply from 172.21.1.3: bytes=32 time<1ms TTL=128
Reply from 172.21.1.3: bytes=32 time<1ms TTL=128
Reply from 172.21.1.3: bytes=32 time<1ms TTL=128

Ping statistics for 172.21.1.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>|
```

- c) Ping PC leo ke PC pisces

```
C:\>ping 172.21.3.4

Pinging 172.21.3.4 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.3.4:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>|
```

- d) Ping PC libra ke PC cancer

```
Packet Tracer PC Command Line 1.0
C:\>ping 172.21.2.3

Pinging 172.21.2.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.2.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>|
```

e) Ping PC libra ke PC leo

```
C:\>ping 172.21.1.1

Pinging 172.21.1.1 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.1.1:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>|
```

12A:

Penjelasan :

Hasil ping PC leo ke PC pisces adalah request time out permintaan koneksi yang lama dan karena subnet address nya sudah berbeda.