


NAMA : Alvian Harisnur
NIM : L200170132
KELAS : C
MODUL : 11



KONFIGURASI SETIAP ROUTER

LAB JARKOM

IOS Command Line Interface

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname Jarkom
Jarkom(config)#int fa0/0
Jarkom(config-if)#ip address 172.16.0.1 255.255.255.0
Jarkom(config-if)#no shut

Jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0,
changed state to up

Jarkom(config-if)#exit
Jarkom(config)#int fa1/0
Jarkom(config-if)#ip address 172.16.0.1 255.255.255.0
Jarkom(config-if)#no shut

Jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0,
changed state to up
```

LAB RPL

IOS Command Line Interface

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname RPL
RPL(config)#int fa0/0
RPL(config-if)#ip address 172.18.0.1 255.255.255.0
RPL(config-if)#no shut

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up


%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0,
changed state to up

RPL(config-if)#exit
RPL(config)#int fa1/0
RPL(config-if)#ip address 172.16.0.3 255.255.255.0
RPL(config-if)#no shut

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0,
changed state to up
```

LAB SI



The screenshot shows a window titled 'lab si' with tabs for Physical, Config, CLI, and Attributes. The CLI tab is active, displaying the IOS Command Line Interface. The configuration process is as follows:

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname SistemInformasi
SistemInformasi(config)#int fa0/0
SistemInformasi(config-if)#ip address 172.17.0.1 255.255.255.0
SistemInformasi(config-if)#no shut

SistemInformasi(config-if)#
%LINK-S-CHANGED: Interface FastEthernet0/0, changed state to up


%LINEPROTO-S-UPDOWN: Line protocol on Interface FastEthernet0/0,
changed state to up

SistemInformasi(config-if)#exit
SistemInformasi(config)#int fa1/0
SistemInformasi(config-if)#ip address 172.15.0.2 255.255.255.0
SistemInformasi(config-if)#no shut

SistemInformasi(config-if)#
%LINK-S-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-S-UPDOWN: Line protocol on Interface FastEthernet1/0,
changed state to up
```

GATEWAY



The screenshot shows a window titled 'gateway' with tabs for Physical, Config, CLI, and Attributes. The CLI tab is active, displaying the IOS Command Line Interface. The configuration process is as follows:

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname UMS
UMS(config)#int fa0/0
UMS(config-if)#ip address 172.19.0.1 255.255.255.0
UMS(config-if)#no shut

UMS(config-if)#
%LINK-S-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-S-UPDOWN: Line protocol on Interface FastEthernet0/0,
changed state to up

UMS(config-if)#exit
UMS(config)#int fa1/0
UMS(config-if)#ip address 172.15.0.4 255.255.255.0
UMS(config-if)#no shut

UMS(config-if)#
%LINK-S-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-S-UPDOWN: Line protocol on Interface FastEthernet1/0,
changed state to up
```

KONFIGURASI ROUTER TABLE

JARKOM

```
Jarkom(config-if)#exit
Jarkom(config)#router rip
Jarkom(config-router)#network 172.15.0.0
Jarkom(config-router)#network 172.16.0.0
Jarkom(config-router)#network 172.17.0.0
Jarkom(config-router)#network 172.18.0.0
Jarkom(config-router)#network 172.19.0.0
Jarkom(config-router)#
```

RPL

```
RPL#conf term
Enter configuration commands, one per line. End with CNTL/Z.
RPL(config)#router rip
RPL(config-router)#network 172.15.0.0
RPL(config-router)#network 172.16.0.0
RPL(config-router)#network 172.17.0.0
RPL(config-router)#network 172.18.0.0
RPL(config-router)#network 172.19.0.0
RPL(config-router)#
```

SI

```
SistemInformasi(config-if)#exit
SistemInformasi(config)#router rip
SistemInformasi(config-router)#network 172.15.0.0
SistemInformasi(config-router)#network 172.16.0.0
SistemInformasi(config-router)#network 172.17.0.0
SistemInformasi(config-router)#network 172.18.0.0
SistemInformasi(config-router)#network 172.19.0.0
SistemInformasi(config-router)#
```

GATEWAY

```
UMS(config-if)#exit
UMS(config)#router rip
UMS(config-router)#network 172.15.0.0
UMS(config-router)#network 172.16.0.0
UMS(config-router)#network 172.17.0.0
UMS(config-router)#network 172.18.0.0
UMS(config-router)#network 172.19.0.0
UMS(config-router)#
```

KONFIGURASI SETIAP PC

pc jarkom

Physical Config **Desktop** Programming Attributes

☐ DHCP ☒ Static

IP Address 172.16.0.2

Subnet Mask 255.255.255.0

Default Gateway 172.16.0.1

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /

Link Local Address FE80::202:4AFF:FE07:57DB

IPv6 Gateway

IPv6 DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

PC rpl

Physical Config **Desktop** Programming Attributes

☐ DHCP ☒ Static

IP Address 172.18.0.2

Subnet Mask 255.255.255.0

Default Gateway 172.18.0.1

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /

Link Local Address FE80::201:42FF:FEE7:DD99

IPv6 Gateway

IPv6 DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

PC si

Physical Config **Desktop** Programming Attributes

☐ DHCP ☒ Static

IP Address 172.17.0.2

Subnet Mask 255.255.255.0

Default Gateway 172.17.0.1

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /

Link Local Address FE80::2E0:A3FF:FE79:D0DE

IPv6 Gateway

IPv6 DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

PC admin

Physical Config **Desktop** Programming Attributes

☐ DHCP ☒ Static

IP Address 172.19.0.2

Subnet Mask 255.255.255.0

Default Gateway 172.19.0.1

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /

Link Local Address FE80::2D0:D3FF:FE9A:C498

IPv6 Gateway

IPv6 DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

MELAKUKAN PENGUJIAN ICMP REQUEST UNTUK TEST KONEKSI


```
Pinging 172.16.0.2 with 32 bytes of data:

Reply from 172.16.0.2: bytes=32 time=1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.16.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>ping 172.17.0.2

Pinging 172.17.0.2 with 32 bytes of data:

Reply from 172.17.0.2: bytes=32 time=1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.17.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:

Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time<1ms TTL=126
Reply from 172.18.0.2: bytes=32 time<1ms TTL=126
```