PRAKTIKUM JARINGAN KOMPUTER MODUL 4

Nama: Tasya Farah Putri A.

Kelas : D


NIM : L200170146

Kegiatan 1:1. Topologi 1

1. Membuat topologi berikut ini menggunakan packet tracer

2. Memberi nama masing masing perangkat


a. Switch: SW
b. Pc0: Leo
c. Pc1: Aries
d. Pc2: Virgo
e. Pc3: Libra
f. Pc4: Taurus
g. Pc5: Scorpio





3. Merubah konfigurasi tiap PC


a. Leo : 172.21.1.1/24
b. Aries : 172.21.1.2/24
c. Virgo : 172.21.1.3/24
d. Libra : 172.21.1.4/24
e. Taurus : 172.21.1.5/24
f. Scorpio: 172.21.1.6/24


/24 maksudnya adalah masuk kelas c











- 4. Membuat 3 buah Vlan dengan nama zodiak1, zodiak2, dan zodiak3
- 5. Selanjutnya pada mode konfigurasi, kelompokkan port-port switch ke dalam VLAN zodiak1, zodiak2, dan zodiak3. Pengaturannya sebagai berikut :

Zodiak1 : leo dan libraZodiak2 : aries dan TaurusZodiak3 : virgo dan scorpio

```
SW1
  Physical Config CLI Attributes
                                                                      IOS C
   Switch>enable
   Switch#conf term
   Enter configuration commands, one per line. End with CNTL/Z. Switch(config) \sharpvlan 10
   Switch(config-vlan)#name zodiak1
   Switch(config-vlan) #exit
   Switch(config) #vlan 20
   Switch(config-vlan) #name zodiak2
   Switch(config-vlan) #exit
   Switch(config) #vlan 30
   Switch(config-vlan) #name zodiak3
   Switch(config-vlan) #exit
   Switch(config) #int fa 0/1
   Switch(config-if) #sw mode access
   Switch(config-if) #sw access vlan 10
   Switch(config-if) #int fa 0/4
   Switch(config-if) #sw mode access
Switch(config-if) #sw access vlan 10
   Switch(config-if) #int fa 0/2
   Switch(config-if) #sw mode access
   Switch(config-if) #sw access vlan 20
Switch(config-if) #int fa 0/3
   Switch(config-if) #sw mode access
   Switch(config-if) #sw access vlan 30
   Switch(config-if) #int fa 0/5
   Switch(config-if) #sw mode access
   Switch(config-if) #sw access vlan 20
   Switch(config-if) #sw mode access
   Switch(config-if) #sw access vlan 30
   Switch(config-if)#end
```

6. Menampilkan informasi Vlan secara keseluruhan

```
Switch#
%SYS-5-CONFIG_I: Configured from console by console
Switch#show vlan brief
VLAN Name
                                               Ports
                                               Fa0/6, Fa0/7, Fa0/8, Fa0/9
  default
                                     active
                                               Fa0/10, Fa0/11, Fa0/12, Fa0/13
                                               Fa0/14, Fa0/15, Fa0/16, Fa0/17
Fa0/18, Fa0/19, Fa0/20, Fa0/21
                                               Fa0/22, Fa0/23, Fa0/24
10
   zodiak1
                                     active
                                               Fa0/1, Fa0/4
20 zodiak2
                                              Fa0/2
                                     active
30
    zodiak3
                                               Fa0/3, Fa0/5
                                     active
1002 fddi-default
                                     active
1003 token-ring-default
                                     active
1004 fddinet-default
                                     active
1005 trnet-default
                                     active
Switch#show vlan id 10
VLAN Name
                                     Status Ports
10 zodiak1
                                     active Fa0/1, Fa0/4
VLAN Type SAID
                    MTU Parent RingNo BridgeNo Stp BrdgMode Trans1 Trans2
    enet 100010 1500 -
```

7. Menampilkan informasi vlan 10, 20,dan 30

Switch#show vlan id 10												
VLAN	LAN Name					Status P			Ports			
10	zodia)	t1			a		ve					
		SAID										
		100010										
Switch#show vlan id 20												
VLAN							us					
	zodia)						ve					
		SAID				_	_		-	_		Trans2
		100020										0
Switch#show vlan id 30												
	Name						us					
	zodia)				a		ve					
VLAN	Type	SAID	MTU	Parent	Ring	gNo	Bridge	eNo	Stp	BrdgMode	Trans1	Trans2
30	enet	100030	1500	-	-		-		-	-	0	0
Switch#												

8. Informasi VLAN 2

No	variabel	Nilai		
1	Nomor VLAN	10		
2	Nama VLAN	zodiak1		
3	Port	fa 0/1, fa 0/4		
4	Status	active		

Informasi VLAN 3

No	variabel	Nilai		
1	Nomor VLAN	20		
2	Nama VLAN	zodiak2		
3	Port	fa 0/2		
4	Status	active		


Informasi VLAN 4

No	variabel	Nilai		
1	Nomor VLAN	30		
2	Nama VLAN	zodiak3		
3	Port	fa 0/3, fa 0/5		
4	Status	active		

Kegiatan 2. Topologi 2

- 1. Membuat topologi berikut ini menggunakan packet tracer
- 2. Memberi nama masing masing perangkat

a.	Switch1	. : SW1	h. Switch2	2 : SW2
b.	Pc0	: Leo	i. Pc6	: Aquarius
c.	Pc1	: Aries	j. Pc7	: Gemini
d.	Pc2	: Virgo	k. Pc8	: Cancer
e.	Pc3	: Libra	l. Pc9	: Sagitarius
f.	Pc4	: Taurus	m. Pc10	: Capricornus
g.	Pc5	: Scorpio	n. Pc11	: Pisces





9. Merubah konfigurasi tiap PC


a. Leo: 172.21.1.1/24


b. Aries : 172.21.1.2/24 : 172.21.2.1/24 c. Virgo : 172.21.2.2/24 d. Libra : 172.21.3.1/24 e. Taurus f. Scorpio : 172.21.3.2/24 : 172.21.1.3/24 g. Aquarius : 172.21.1.4/24 h. Gemini : 172.21.2.3/24 i. Cancer j. Sagitarius : 172.21.2.4/24 k. Capricornus: 172.21.3.3/24 : 172.21.3.4/24 I. Pisces


/24 maksudnya adalah masuk kelas c

















IPv6 DNS Server

____ Тор