

Nama : Dandi Katerpillarifai

NIM : L200170168

Kelas : D


## MODUL 9

### Pengenalan Static Network Address Translation

#### Pada Router Cisco

#### Kegiatan Praktikum.

##### 1. Topologi.



## 2. Konfigurasi Router Internet.

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname Internet
Internet(config)#int fa0/0
Internet(config-if)#ip address 10.0.0.1 255.0.0.0
Internet(config-if)#no shutdown
Internet(config-if)#exit
Internet(config)#int se2/0
Internet(config-if)#ip address 20.0.0.2 255.0.0.0
Internet(config-if)#no shutdown
Internet(config-if)#exit
Internet(config)#ip route 30.0.0.0 255.0.0.0 20.0.0.1
Internet(config)#ip nat inside source static 10.0.0.2 50.0.0.1
Internet(config)#int fa0/0
Internet(config-if)#ip nat inside
Internet(config-if)#exit
Internet(config)#int se2/0
Internet(config-if)#ip nat outside
Internet(config-if)#exit
Internet(config)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up
```

## 3. Konfigurasi Router Lokal.

```
Router>en
Router#conf term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname Lokal
Lokal(config)#int fa0/0
Lokal(config-if)#ip address 30.0.0.1 255.0.0.0
Lokal(config-if)#no shutdown

Lokal(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Lokal(config-if)#exit
Lokal(config)#int se2/0
Lokal(config-if)#ip address 20.0.0.1 255.0.0.0
Lokal(config-if)#clock rate 64000
Lokal(config-if)#bandwidth 64
Lokal(config-if)#no shutdown

Lokal(config-if)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

Lokal(config-if)#exit
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Lokal(config)#exit
Lokal#
%SYS-5-CONFIG_I: Configured from console by console
```

#### 4. Uji coba koneksi dari PC Lokal ke Web Server

```
C:\>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 30.0.0.1: Destination host unreachable.
Reply from 30.0.0.1: Destination host unreachable.
Request timed out.
Reply from 30.0.0.1: Destination host unreachable.

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Request timed out.
Reply from 50.0.0.1: bytes=32 time=1ms TTL=126
Reply from 50.0.0.1: bytes=32 time=1ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126

Ping statistics for 50.0.0.1:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 2ms, Average = 1ms


C:\>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1: bytes=32 time=1ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=1ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126

Ping statistics for 50.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 2ms, Average = 1ms
```

## 5. Mengembangkan Topologi.



PC0

Physical

Config

Desktop

Programming

Attributes

IP Configuration

X

IP Configuration

DHCP

Static

IP Address

30.0.0.3

Subnet Mask

255.0.0.0

Default Gateway

30.0.0.1

DNS Server

0.0.0.0

IPv6 Configuration

DHCP

Auto Config

Static

IPv6 Address

/

Link Local Address

FE80::260:70FF:FE7D:9E69

IPv6 Gateway

IPv6 DNS Server

Top

PC1

Physical

Config

Desktop

Programming

Attributes

IP Configuration

X

IP Configuration

DHCP

Static

IP Address

30.0.0.4

Subnet Mask

255.0.0.0

Default Gateway

30.0.0.1

DNS Server

0.0.0.0

IPv6 Configuration

DHCP

Auto Config

Static

IPv6 Address

/

Link Local Address

FE80::201:63FF:FE90:E0CB

IPv6 Gateway

IPv6 DNS Server

Top

PC 0

```
C:\>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 30.0.0.1: Destination host unreachable.
Reply from 30.0.0.1: Destination host unreachable.
Reply from 30.0.0.1: Destination host unreachable.
Reply from 30.0.0.1: Destination host unreachable.

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=1ms TTL=126
Reply from 50.0.0.1: bytes=32 time=1ms TTL=126

Ping statistics for 50.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 2ms, Average = 1ms
```

PC 1

```
C:\>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 30.0.0.1: Destination host unreachable.
Request timed out.
Reply from 30.0.0.1: Destination host unreachable.
Reply from 30.0.0.1: Destination host unreachable.

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126
Reply from 50.0.0.1: bytes=32 time=2ms TTL=126

Ping statistics for 50.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 2ms, Average = 2ms
```