Nama : Nugroho Prihananto

NIM : L200170186

Kelas : D

MODUL 11

Kegiatan

1. Topologi



2. Konfigurasi semua router
   - Konfigurasi router jarkom

lab jarkom

Physical | Config | CLI | Attributes

IOS Commar

```
Router>en
Router#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#hostname jarkom
jarkom(config)#int fa0/0
jarkom(config-if)#ip address 172.16.0.1 255.255.255.0
jarkom(config-if)#no shutdown

jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

jarkom(config-if)#exit
jarkom(config)#int fa1/0
jarkom(config-if)#ip address 172.15.0.1 255.255.255.0
jarkom(config-if)#no shutdown

jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

jarkom(config-if)#exit
```

- Konfigurasi router system informasi

lab si

Physical | Config | CLI | Attributes

IOS Co

```
Router>en
Router#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#hostname SistemInformasi
SistemInformasi(config)#int fa0/0
SistemInformasi(config-if)#ip address 172.17.0.1 255.255.255.0
SistemInformasi(config-if)#no shutdown

SistemInformasi(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

SistemInformasi(config-if)#exit
SistemInformasi(config)#int fa1/0
SistemInformasi(config-if)#ip address 172.15.0.2 255.255.255.0
SistemInformasi(config-if)#no shutdown

SistemInformasi(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

SistemInformasi(config-if)#exit
```

- Konfigurasi router RPL

lab rpl

Physical | Config | CLI | Attributes

IOS Command Li

```
Router>en
Router#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#hostname RPL
RPL(config)#int fa0/0
RPL(config-if)#ip address 172.18.0.1 255.255.255.0
RPL(config-if)#no shutdown

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

RPL(config-if)#exit
RPL(config)#int fa1/0
RPL(config-if)#ip address 172.15.0.3 255.255.255.0
RPL(config-if)#no shutdown

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

RPL(config-if)#exit
```

- Konfigurasi router gateway

gateway

Physical | Config | CLI | Attributes

IOS Con

```
Router>en
Router#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#hostname UMS
UMS(config)#int fa0/0
UMS(config-if)#ip address 172.19.0.1 255.255.255.0
UMS(config-if)#no shutdown

UMS(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

UMS(config-if)#exit
UMS(config)#int fa1/0
UMS(config-if)#ip address 172.15.0.4 255.255.255.0
UMS(config-if)#no shutdown

UMS(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

UMS(config-if)#exit
```

3. Konfigurasi routing tabel pada 4 router
   - Membuat routing table pada router 1/jarkom

lab jarkom

Physical | Config | CLI | Attributes

IO

```
jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

jarkom(config-if)#exit
jarkom(config)#
jarkom(config)#router rip
jarkom(config-router)#network 172.15.0.0
jarkom(config-router)#network 172.16.0.0
jarkom(config-router)#network 172.17.0.0
jarkom(config-router)#network 172.18.0.0
jarkom(config-router)#network 172.19.0.0
jarkom(config-router)#exit
jarkom(config)#
```

- Membuat routing table pada router 2/SI

lab si

Physical | Config | CLI | Attributes

IOS

```
SistemInformasi(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

SistemInformasi(config-if)#exit
SistemInformasi(config)#
SistemInformasi(config)#router rip
SistemInformasi(config-router)#network 172.15.0.0
SistemInformasi(config-router)#network 172.16.0.0
SistemInformasi(config-router)#network 172.17.0.0
SistemInformasi(config-router)#network 172.18.0.0
SistemInformasi(config-router)#network 172.19.0.0
SistemInformasi(config-router)#exit
SistemInformasi(config)#
```

- Membuat routing table pada router 3/RPL



- Membuat routing table pada router 4 / gateway UMS



4. Konfigurasi IP pada masing – masing PC
   - Setting IP untuk PC lab RPL dengan ip 172.18.0.2/24



- Setting IP untuk PC lab Jarkom dengan ip 172.16.0.2



- Setting IP untuk PC lab SI dengan ip 172.17.0.2



- Setting IP untuk PC gateway dengan ip 172.19.0.2



5. Pengujian ICMP request (ping) untuk test koneksi
   - PC admin ke pc jarkom(172.16.0.2)



   - PC admin ke pc RPL (172.17.0.2)

```
C:\>ping 172.17.0.2

Pinging 172.17.0.2 with 32 bytes of data:

Reply from 172.17.0.2: bytes=32 time=1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.17.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

- PC admin ke pc SI (172.18.0.2)

```
C:\>ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:

Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time<1ms TTL=126
Reply from 172.18.0.2: bytes=32 time=11ms TTL=126

Ping statistics for 172.18.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 11ms, Average = 3ms
```