PRAKTIKUM SISTEM OPERASI MODUL 1

Nama : GUNTUR JATMIKO

NIM : L200180039

• ASCII (American Standard Code for Information Interchange)

Suatu standar internasional dalam kode huruf dan simbol seperti Hex dan Unicode tetapi ASCII lebih bersifat universal, contohnya 124 adalah untuk karakter "|". Ia selalu digunakan oleh komputer dan alat komunikasi lain untuk menunjukkan teks.

Sedangkan fungsi dari kode ASCII ialah digunakan untuk mewakili karakter-karakter angka maupun huruf didalam komputer,

Dalam sistem operasi Windows dan MS-DOS, pengguna dapat menggunakan karakter ASCII dengan menekan tombol Alt+[nomor nilai ANSI (desimal)].

• Kode ASCII

Binary	Oct	Dec	Hex	Glyph
010 0000	040	32	20	
010 0001	041	33	21	!
010 0010	042	34	22	"
010 0011	043	35	23	#
010 0100	044	36	24	\$
010 0101	045	37	25	%
010 0110	046	38	26	&
010 0111	047	39	27	•
010 1000	050	40	28	(
010 1001	051	41	29)
010 1010	052	42	2A	*
010 1011	053	43	2B	+
010 1100	054	44	2C	,
010 1101	055	45	2D	-
010 1110	056	46	2E	
010 1111	057	47	2F	/
011 0000	060	48	30	0
011 0001	061	49	31	1
011 0010	062	50	32	2
011 0011	063	51	33	3
011 0100	064	52	34	4
011 0101	065	53	35	5
011 0110	066	54	36	6
011 0111	067	55	37	7
011 1000	070	56	38	8
011 1001	071	57	39	9
011 1010	072	58	3A	:
011 1011	073	59	3B	;
011 1100	074	60	3C	<
011 1101	075	61	3D	=
011 1110	076	62	3E	>
011 1111	077	63	3F	?
100 0000	100	64	40	@
100 0001	101	65	41	A
100 0010	102	66	42	В
100 0011	103	67	43	С
100 0100	104	68	44	D
100 0101	105	69	45	Е
100 0110	106	70	46	F
100 0111	107	71	47	G

100 1000	110	72	48	Н
100 1000	111	73	49	I
100 1001	112	74	49 4A	J
100 1010	113	75	4A 4B	K
100 1011	114	76	4B 4C	
100 1100		77	4C 4D	L M
	115			
100 1110	116	78	4E	N
100 1111	117	79	4F	0
101 0000	120	80	50	P
101 0001	121	81	51	Q
101 0010	122	82	52	R
101 0011	123	83	53	S
101 0100	124	84	54	T
101 0101	125	85	55	U
101 0110	126	86	56	V
101 0111	127	87	57	W
101 1000	130	88	58	X
101 1001	131	89	59	Y
101 1010	132	90	5A	Z
101 1011	133	91	5B	
101 1100	134	92	5C	\
101 1101	135	93	5D	j
101 1110	136	94	5E	٨
101 1111	137	95	5F	
110 0000	140	96	60	
110 0000	141	97	61	a
110 0001	142	98	62	b
110 0010	143	99	63	c
110 1000	144	100	64	d
110 1000	145	100	65	
	145	101	66	e f
110 0110	146			
110 0111		103	67	g
110 1000	150	104	68	h
110 1001	151	105	69	i
110 1010	152	106	6A	j
110 1011	153	107	6B	k
110 1100	154	108	6C	1
110 1101	155	109	6D	m
110 1110	156	110	6E	n
110 1111	157	111	6F	О
111 0000	160	112	70	p
111 0001	161	113	71	q
111 0010	162	114	72	r
111 0011	163	115	73	S
111 0100	164	116	74	t
111 0101	165	117	75	u
111 0110	166	118	76	V
111 0111	167	119	77	W
111 1000	170	120	78	X
111 1001	171	121	79	у
111 1010	172	122	7A	Z
111 1011	173	123	7B	{
111 1100	174	124	7C	
111 1100	-,.			

111 1101	175	125	7D	}
111 1110	176	126	7E	~

• Daftar perintah Bahasa assembly

- 1. Assembly Directive (yaitu merupakan kode yang menjadi arahan bagi assembler/compiler untuk menata program)
- 2. Instruksi (yaitu kode yang harus dieksekusi oleh CPU mikrokontroler dengan melakukan operasi tertentu sesuai dengan daftar yang sudah tertanam dalam CPU)

• Daftar Assembly Directive

Assembly Directive	Keterangan
EQU	Pendefinisian konstanta
DB	Pendefinisian data dengan ukuran satuan 1 byte
DW	Pendefinisian data dengan ukuran satuan 1 word
DBIT	Pendefinisian data dengan ukuran satuan 1 bit
DS	Pemesanan tempat penyimpanan data di RAM
ORG	Inisialisasi alamat mulai program
END	Penanda akhir program
CSEG	Penanda penempatan di code segment
XSEG	Penanda penempatan di external data segment
DSEG	Penanda penempatan di internal direct data segment
ISEG	Penanda penempatan di internal indirect data segment
BSEG	Penanda penempatan di bit data segment
CODE	Penanda mulai pendefinisian program
XDATA	Pendefinisian external data
DATA	Pendefinisian internal direct data
IDATA	Pendefinisian internal indirect data
BIT	Pendefinisian data bit
#INCLUDE	Mengikutsertakan file program lain

• Daftar Instruksi

Instruksi	Keterangan Singkatan
ACALL	Absolute Call
ADD	Add

ADDC	Add with Carry	
AJMP	Absolute Jump	
ANL	AND Logic	
CJNE	Compare and Jump if Not Equal	
CLR	Clear	
CPL	Complement	
DA	Decimal Adjust	
DEC	Decrement	
DIV	Divide	
DJNZ	Decrement and Jump if Not Zero	
INC	Increment	
JB	Jump if Bit Set	
JBC	Jump if Bit Set and Clear Bit	
JC	Jump if Carry Set	
JMP	Jump to Address	
JNB	Jump if Not Bit Set	
JNC	Jump if Carry Not Set	
JNZ	Jump if Accumulator Not Zero	
JZ	Jump if Accumulator Zero	
LCALL	Long Call	
LJMP	Long Jump	
MOV	Move from Memory	
MOVC	Move from Code Memory	
MOVX	Move from Extended Memory	
MUL	Multiply	
NOP	No Operation	
ORL	OR Logic	
POP	Pop Value From Stack	
PUSH	Push Value Onto Stack	
RET	Return From Subroutine	
RETI	Return From Interrupt	

Rotate Left
Rotate Left through Carry
Rotate Right
Rotate Right through Carry
Set Bit
Short Jump
Subtract With Borrow
Swap Nibbles
Exchange Bytes
Exchange Digits
Exclusive OR Logic