


Nama = Putri Siwi Utami

NIM = L200180146

Kelas = D

Praktikum 1 membuat DHCP SERVER



Server Side

Server0

Physical Config Services Desktop Programming Attributes

GLOBAL

Settings

Algorithm Settings

INTERFACE

FastEthernet0

FastEthernet0

Port Status ☒ On

Bandwidth ☒ 100 Mbps ☐ 10 Mbps ☒ Auto

Duplex ☐ Half Duplex ☒ Full Duplex ☒ Auto

MAC Address 000C.CF38.C546

IP Configuration

☐ DHCP

☒ Static

IP Address 192.168.123.1

Subnet Mask 255.255.255.0

IPv6 Configuration

☐ DHCP

☐ Auto Config

☒ Static

IPv6 Address

Link Local Address: FE80::20C:CFFF:FE38:C546

☐ Top

Server0

Physical Config Services Desktop Programming Attributes

SERVICES

HTTP

DHCP

DHCPv6

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

IoT

VM Management

DHCP

Interface FastEthernet0 Service ☒ On ☐ Off

Pool Name serverPool

Default Gateway 192.168.123.1

DNS Server 0.0.0.0

Start IP Address : 192 168 123 19

Subnet Mask: 255 255 255 0

Maximum Number of Users : 5

TFTP Server: 0.0.0.0

WLC Address: 0.0.0.0

Add Save Remove

Pool Name	Default Gateway	DNS Server	Start IP Address	Subnet Mask	Max User	TFTP Server	WLC Address
serverPool	192.168.123.1	0.0.0.0	192.168.123...	255.255.255.0	5	0.0.0.0	0.0.0.0

☐ Top

Client side

PC0

Physical Config Desktop Programming Attributes

IP Configuration X

IP Configuration

☒ DHCP ☐ Static DHCP request successful.

IP Address 192.168.123.19

Subnet Mask 255.255.255.0

Default Gateway 192.168.123.1

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /


Link Local Address FE80::2D0:97FF:FEA0:1E6A

IPv6 Gateway

IPv6 DNS Server

☐ Top

Hasil



The screenshot shows a Windows desktop environment with a window titled "PC0". Inside the window, there are tabs for "Physical", "Config", "Desktop", "Programming", and "Attributes". The "Desktop" tab is active, displaying a "Command Prompt" window. The Command Prompt shows the results of three ping commands executed from the C:\ prompt.

```
PC0
Physical Config Desktop Programming Attributes
Command Prompt
Pinging 192.168.123.19 with 32 bytes of data:
Reply from 192.168.123.19: bytes=32 time=4ms TTL=128
Reply from 192.168.123.19: bytes=32 time=4ms TTL=128
Reply from 192.168.123.19: bytes=32 time=4ms TTL=128
Reply from 192.168.123.19: bytes=32 time=3ms TTL=128

Ping statistics for 192.168.123.19:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 3ms, Maximum = 8ms, Average = 4ms

C:\>ping 192.168.123.20

Pinging 192.168.123.20 with 32 bytes of data:
Reply from 192.168.123.20: bytes=32 time=117ms TTL=128
Reply from 192.168.123.20: bytes=32 time<1ms TTL=128
Reply from 192.168.123.20: bytes=32 time<1ms TTL=128
Reply from 192.168.123.20: bytes=32 time<1ms TTL=128



Ping statistics for 192.168.123.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 117ms, Average = 29ms

C:\>ping 192.168.123.21

Pinging 192.168.123.21 with 32 bytes of data:
Reply from 192.168.123.21: bytes=32 time<1ms TTL=128
Reply from 192.168.123.21: bytes=32 time<1ms TTL=128
Reply from 192.168.123.21: bytes=32 time<1ms TTL=128
Reply from 192.168.123.21: bytes=32 time<1ms TTL=128



Ping statistics for 192.168.123.21:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

At the bottom left of the Command Prompt window, there is a checkbox labeled "Top" which is currently unchecked.



PRAKTIKUM 2 MEMBUAT WEB SERVER


Server Side



Client Side



Tugas



Server Side

The configuration window for Server1 shows the FastEthernet0 interface settings. The interface is configured with a static IP address of 192.168.24.1 and a subnet mask of 255.255.255.0. The MAC address is 0002.4ADD.594E. The interface is set to 100 Mbps, Full Duplex, and Auto. The IPv6 configuration is set to Static, with an IPv6 address of FE80::202:4AFF:FEDD:594E and a link local address of FE80::202:4AFF:FEDD:594E.

GLOBAL

- Settings
- Algorithm Settings
- INTERFACE**
- FastEthernet0

FastEthernet0

Port Status: ☒ On

Bandwidth: ☒ 100 Mbps ☐ 10 Mbps ☒ Auto

Duplex: ☐ Half Duplex ☒ Full Duplex ☒ Auto

MAC Address: 0002.4ADD.594E

IP Configuration

- ☐ DHCP
- ☒ Static

IP Address: 192.168.24.1

Subnet Mask: 255.255.255.0

IPv6 Configuration

- ☐ DHCP
- ☐ Auto Config
- ☒ Static

IPv6 Address:

Link Local Address: FE80::202:4AFF:FEDD:594E

☐ Top

Server1

Physical

Config

Services

Desktop

Programming

Attributes

SERVICES

HTTP

DHCP

DHCPv6

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

IoT

VM Management

DHCP

Interface

FastEthernet0

Service

On

Off

Pool Name

serverPool

Default Gateway

192.168.24.1

DNS Server

192.168.24.1

Start IP Address :

192

168

24

2

Subnet Mask:

255

255

255

0

Maximum Number of Users :

20

TFTP Server:

0.0.0.0

WLC Address:

0.0.0.0

Add

Save

Remove

Pool Name	Default Gateway	DNS Server	Start IP Address	Subnet Mask	Max User	TFTP Server	WLC Address
serverPool	192.168.24.1	192.168.24.1	192.168.24.2	255.255.255.0	20	0.0.0.0	0.0.0.0

Top

Server1

Physical

Config

Services

Desktop

Programming

Attributes

SERVICES

HTTP

DHCP

DHCPv6

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

IoT

VM Management

HTTP

On

Off

HTTPS

On

Off


File Manager

	File Name	Edit	Delete
1	copyrights.html	(edit)	(delete)
2	cscoptlogo177x111.jpg		(delete)
3	helloworld.html	(edit)	(delete)
4	image.html	(edit)	(delete)
5	index.html	(edit)	(delete)


New File

Import

Top



Client Side





Hasil

```
PC6
Physical Config Desktop Programming Attributes
Command Prompt
X

Pinging 192.168.24.9 with 32 bytes of data:

Reply from 192.168.24.9: bytes=32 time=46ms TTL=128
Reply from 192.168.24.9: bytes=32 time<1ms TTL=128
Reply from 192.168.24.9: bytes=32 time<1ms TTL=128
Reply from 192.168.24.9: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.24.9:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 46ms, Average = 11ms

C:\>ping 192.168.24.11

Pinging 192.168.24.11 with 32 bytes of data:

Reply from 192.168.24.11: bytes=32 time<1ms TTL=128
Reply from 192.168.24.11: bytes=32 time<1ms TTL=128
Reply from 192.168.24.11: bytes=32 time<1ms TTL=128
Reply from 192.168.24.11: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.24.11:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>ping 192.168.24.13

Pinging 192.168.24.13 with 32 bytes of data:

Reply from 192.168.24.13: bytes=32 time=2ms TTL=128
Reply from 192.168.24.13: bytes=32 time<1ms TTL=128
Reply from 192.168.24.13: bytes=32 time<1ms TTL=128
Reply from 192.168.24.13: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.24.13:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 2ms, Average = 0ms

☐ Top
```

