

Nama : Viola Lovitasari

NIM : 173

Kelas : G

TUGAS MODUL 3

No 1.

```
1.py - C:\Users\viola\Documents\173_Modul1_G\1.py (2.7.10)
File Edit Format Run Options Window Help

a = [[1,2],[3,4]]
b = [[5,6],[7,8]]
c = [[12,3,"y"],[12,33,4]]
d = [[3,4],[2,4],[1,5]]
e = [[5,6,7],[7,8,9]]
f = [[2,3],[4,5,6],[7,8,9]]

def cekKonsis(n):
    x = len(n[0])
    y = type(n[0][0])
    z = 0
    a = True
    for i in range(len(n)):
        for j in range(len(n[i])):
            #mengecek apakah matriks mempunyai isi yg bertipe sama
            c = type(n[i][j])
            if (c!=y):
                a = False
                break
            #mengecek apakah matriks mempunyai ukuran yg sama
            if (len(n[i]) == x):
                z+=1

    if(z == len(n) and a==True):
        print("matriks konsisten")
    else:
        print("matrik tidak konsisten")

cekKonsis(a)
cekKonsis(f)
cekKonsis(c)

def cekInt(n):
    x = 0
    y = 0
    for i in n:
        for j in i:
            y+=1
            if (str(j).isdigit()==False):
                print("tidak semua isi matriks adalah angka")
                break
        x+=1

cekInt(a)
cekInt(b)
cekInt(c)

def ordo(n):
    x,y = 0,0
    for i in range(len(n)):
        x+=1
        y = len(n[i])
        print(len(n))
        print("mempunyai ordo "+str(x)+"x"+str(y))

ordo(a)
ordo(b)
ordo(d)
ordo(f)

def jumlah(n,m):
    x,y = 0,0
    for i in range(len(n)):
        x+=1
        y = len(n[i])
        xy = [[0 for j in range(x)] for i in range(y)]

    z = 0
    if(len(n)==len(m)):
        for i in range(len(n)):
            if(len(n[i]) == len(m[i])):
                z+=1
    if(z==len(n) and z==len(m)):
        print("ukuran sama")
        for i in range(len(n)):
            for j in range(len(n[i])):
                xy[i][j] = n[i][j] + m[i][j]
        print(xy)
    else:
```

```
Python 2.7.10 Shell
File Edit Shell Debug Options Window Help

Python 2.7.10 (default, May 23 2015, 09:40:32) [MSC v.150
n32
Type "copyright", "credits" or "license()" for more infor
>>> ===== RESTART =====
>>>
matriks konsisten
matrik tidak konsisten
matrik tidak konsisten
semua isi matriks adalah angka
semua isi matriks adalah angka
tidak semua isi matriks adalah angka
2
mempunyai ordo 2x2
2
mempunyai ordo 2x2
3
mempunyai ordo 3x2
3
mempunyai ordo 3x3
ukuran sama
[[6, 8], [10, 12]]
ukuran beda
bisa dikalikan
[[0], [0]]
[[14], [14]]
bisa dikalikan
[[0, 0], [0, 0]]
[[19, 22], [43, 50]]
bisa dikalikan
[[0, 0, 0], [0, 0, 0]]
[[19, 22, 25], [43, 50, 57]]
tidak memenuhi syarat
13
-6
200
330
tidak bisa dihitung determinan, bukan matrix bujursangkar
tidak bisa dihitung determinan, bukan matrix bujursangkar
>>> |
```

```
1.py - C:\Users\viola\Documents\173_Modul1_G\1.py (2.7.10)
File Edit Format Run Options Window Help

        else:
            x+=1
        if(x==y):
            print("semua isi matriks adalah angka")

cekInt(a)
cekInt(b)
cekInt(c)

def ordo(n):
    x,y = 0,0
    for i in range(len(n)):
        x+=1
        y = len(n[i])
        print(len(n))
        print("mempunyai ordo "+str(x)+"x"+str(y))

ordo(a)
ordo(b)
ordo(d)
ordo(f)

def jumlah(n,m):
    x,y = 0,0
    for i in range(len(n)):
        x+=1
        y = len(n[i])
        xy = [[0 for j in range(x)] for i in range(y)]

    z = 0
    if(len(n)==len(m)):
        for i in range(len(n)):
            if(len(n[i]) == len(m[i])):
                z+=1
    if(z==len(n) and z==len(m)):
        print("ukuran sama")
        for i in range(len(n)):
            for j in range(len(n[i])):
                xy[i][j] = n[i][j] + m[i][j]
        print(xy)
    else:
```

1.py - C:\Users\viola\Documents\173_Modul1_G\1.py (2.7.10)

File Edit Format Run Options Window Help

```
    else:
        print("ukuran beda")

jumlah(a,b)
jumlah(a,d)

def kali(n,m):
    aa = 0
    x,y = 0,0
    for i in range(len(n)):
        x+=1
        y = len(n[i])
    v,w = 0,0
    for i in range(len(m)):
        v+=1
        w = len(m[i])

    if (y==v):
        print("bisa dikalikan")
        vwxy = [[0 for j in range(w)] for i in range(x)]
        print(vwxy)
        for i in range(len(n)):
            for j in range(len(m[0])):
                for k in range(len(m)):
                    #print(n[i][k], m[k][j])
                    vwxy[i][j] += n[i][k] * m[k][j]

        print(vwxy)

    else:
        print("tidak memenuhi syarat")

zz = [[1,2,3],[1,2,3]]
zx = [[1],[2],[3]]
kali(zz,zx)
kali(a,b)
kali(a,e)
kali(a,zx)

def determHitung(A, total=0):
```

1.py - C:\Users\viola\Documents\173_Modul1_G\1.py (2.7.10)

File Edit Format Run Options Window Help

```
def determHitung(A, total=0):
    x = len(A[0])
    z = 0
    for i in range(len(A)):
        if (len(A[i]) == x):
            z+=1
    if (z == len(A)):
        if (x==len(A)):
            indices = list(range(len(A)))
            if len(A) == 2 and len(A[0]) == 2:
                val = A[0][0] * A[1][1] - A[1][0] * A[0][1]
                return val
            for fc in indices:
                As = A
                As = As[1:]
                height = len(As)
                for i in range(height):
                    As[i] = As[i][0:fc] + As[i][fc+1:]
                sign = (-1) ** (fc % 2)
                sub_det = determHitung(As)
                total += sign * A[0][fc] * sub_det
            else:
                return "tidak bisa dihitung determinan, bukan matrix bujursangkar"
        else:
            return "tidak bisa dihitung determinan, bukan matrix bujursangkar"
    return total

z = [[3,1],[2,5]]
x = [[1,2,1],[3,3,1],[2,1,2]]
v = [[1,-2,0,0],
      [3,2,-3,1],
      [4,0,5,1],
      [2,3,-1,4]]
r = [[10,23,45,12,13],
      [1,2,3,4,5],
      [1,2,3,4,6],
      [4,2,3,4,8],
      [1,4,5,6,10]]
print(determHitung(z))
print(determHitung(x))
print(determHitung(v))
```

No 2.

```
2.py - C:\Users\viola\Documents\173_Modul1_G\2.py (2.7.10)
File Edit Format Run Options Window Help
def buatNol(n,m=None):
    if(m==None):
        m=n
    print("membuat matriks 0 dengan ordo "+str(n)+"x"+str(m))
    print([[0 for j in range(m)] for i in range(n)])

buatNol(2,4)
buatNol(3)

def buatIden(n):
    print("membuat matriks identitas dengan ordo"+str(n)+"x"+str(n))
    print([[1 if j==i else 0 for j in range(n)] for i in range(n)])

buatIden(4)
buatIden(2)
```

```
Python 2.7.10 Shell
File Edit Shell Debug Options Window Help
Python 2.7.10 (default, May 23 2015, 09:40:32) [MSC v.1500 :
n32
Type "copyright", "credits" or "license()" for more informa
>>> ===== RESTART =====
>>>
membuat matriks 0 dengan ordo 2x4
[[0, 0, 0, 0], [0, 0, 0, 0]]
membuat matriks 0 dengan ordo 3x3
[[0, 0, 0], [0, 0, 0], [0, 0, 0]]
membuat matriks identitas dengan ordo4x4
[[1, 0, 0, 0], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]]
membuat matriks identitas dengan ordo2x2
[[1, 0], [0, 1]]
>>> |
```

No 3.

```
3.py - C:\Users\asus\OneDrive\Desktop\3.py (3.8.2)
File Edit Format Run Options Window Help
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
class LinkedList:
    def __init__(self):
        self.head = None
    def tambahDepan(self, new_data):
        new_node = Node(new_data)
        new_node.next = self.head
        self.head = new_node
    def tambahAkhir(self, data):
        if (self.head == None):
            self.head = Node(data)
        else:
            current = self.head
            while (current.next != None):
                current = current.next
            current.next = Node(data)
        return self.head
    def tambah(self, data, pos):
        node = Node(data)
        if not self.head:
            self.head = node
        elif pos==0:
            node.next = self.head
            self.head = node
        else:
            prev = None
            current = self.head
            current_pos = 0
            while (current_pos < pos) and current.next:
                prev = current
                current = current.next
                current_pos +=1
            node.next = prev.next
            prev.next = node
        return self.head
    def hapus(self, position):
        if self.head == None:
```

3.py - C:\Users\asus\OneDrive\Desktop\3.py (3.8.2)

File Edit Format Run Options Window Help

```
    if self.head == None:
        return
    temp = self.head
    if position == 0:
        self.head = temp.next
        temp = None
        return
    for i in range(position):
        prev = temp
        temp = temp.next
        if temp is None:
            break
    if temp is None:
        return
    if temp.next is None:
        return
    prev.next = temp.next
    temp = None

def cari(self, x):
    current = self.head
    while current != None:
        if current.data == x:
            return "True"
        current = current.next
    return "False"
def display(self):
    current = self.head
    while current is not None:
        print(current.data, end = ' ')
        current = current.next

l1list = LinkedList()
l1list.tambahDepan(21)
l1list.tambahDepan(22)
l1list.tambahDepan(12)
l1list.tambahDepan(14)
l1list.tambahDepan(2)
l1list.tambahDepan(19)
l1list.tambahAkhir(9)
l1list.display()
l1list.hapus(5)
l1list.tambah(1,5)
print(l1list.cari(21))
print(l1list.cari(29))
l1list.display()
```

Python 3.8.2 Shell

File Edit Shell Debug Options Window

Python 3.8.2 (tags/v3.8.2:7b3e2e3, Mar 10 2020) on win32

Type "help", "copyright", "credits()", or "license()" for more

```
>>>
===== RESTART: C:\Python38\python.exe
19 2 14 12 22 21 9 False
False
19 2 14 12 22 1 9
>>> |
```

No 4.

4.py - C:\Users\viola\Documents\173_Modul1_G\4.py (2.7.10)

File Edit Format Run Options Window Help

```
class Node:
    def __init__(self, data):
        self.data = data
        self.prev = None
class DoublyLinkedList:
    def __init__(self):
        self.head = None
    def awal(self, new_data):
        print("menambah pada awal", new_data)
        new_node = Node(new_data)
        new_node.next = self.head
        if self.head is not None:
            self.head.prev = new_node
        self.head = new_node
    def akhir(self, new_data):
        print("menambah pada akhir", new_data)
        new_node = Node(new_data)
        new_node.next = None
        if self.head is None:
            new_node.prev = None
            self.head = new_node
        return
    last = self.head
    while (last.next is not None):
        last = last.next
    last.next = new_node
    new_node.prev = last
    return
    def printList(self, node):
        print("\nDari Depan :")
        while (node is not None):
            print(" % d" %(node.data))
            last = node
            node = node.next
        print("\nDari Belakang :")
        while (last is not None):
            print(" % d" %(last.data))
            last = last.prev
l1list = DoublyLinkedList()
l1list.awal(7)
l1list.awal(1)
```

Python 2.7.10 Shell

File Edit Shell Debug Options Window Help

Python 2.7.10 (default, May 23 2015, 09: n32
Type "copyright", "credits" or "license"
>>> ===== RES
>>>
(('menambah pada awal', 7)
(('menambah pada awal', 1)
(('menambah pada akhir', 6)
(('menambah pada akhir', 4)

Dari Depan :
1
7
6
4

Dari Belakang :
4
6
7
1
>>> |

4.py - C:\Users\viola\Documents\173_Modul1_G\4.py (2.7.10)

File Edit Format Run Options Window Help

```
class DoublyLinkedList:
    def __init__(self):
        self.head = None
    def awal(self, new_data):
        print("menambah pada awal", new_data)
        new_node = Node(new_data)
        new_node.next = self.head
        if self.head is not None:
            self.head.prev = new_node
        self.head = new_node
    def akhir(self, new_data):
        print("menambah pada akhir", new_data)
        new_node = Node(new_data)
        new_node.next = None
        if self.head is None:
            new_node.prev = None
            self.head = new_node
        return
    last = self.head
    while (last.next is not None):
        last = last.next
    last.next = new_node
    new_node.prev = last
    return
    def printList(self, node):
        print("\nDari Depan :")
        while (node is not None):
            print(" % d" %(node.data))
            last = node
            node = node.next
        print("\nDari Belakang :")
        while (last is not None):
            print(" % d" %(last.data))
            last = last.prev
l1list = DoublyLinkedList()
l1list.awal(7)
l1list.awal(1)
l1list.akhir(6)
l1list.akhir(4)
l1list.printList(l1list.head)
```

Python 2.7.10 Shell

File Edit Shell Debug Options Window Help

Python 2.7.10 (default, May 23 2015, 09: n32
Type "copyright", "credits" or "license"
>>> ===== RES
>>>
(('menambah pada awal', 7)
(('menambah pada awal', 1)
(('menambah pada akhir', 6)
(('menambah pada akhir', 4)

Dari Depan :
1
7
6
4

Dari Belakang :
4
6
7
1
>>> |

