

Bootstrap 5 · Class Cheat Sheet

A quick-reference guide to the most-used utility, layout, and component classes

■ Layout & Grid

Class	What it does	Example
<code>.container</code>	Fixed-width centered wrapper; responds to breakpoints.	
<code>.container-fluid</code>	Full-width wrapper that spans 100% of the viewport.	
<code>.container-{sm md lg xl xxl}</code>	Responsive container that becomes full-width below the given breakpoint.	
<code>.row</code>	Horizontal grouping of columns. Always lives inside a container.	
<code>.col</code>	Equal-width column; auto-divides available space.	<code><div class="row"><div class="col">A</div><div class="col">B</div></div></code>
<code>.col-{n}</code>	Column spanning n out of 12 units (1–12).	<code><div class="col-4">4/12 wide</div></code>
<code>.col-{bp}-{n}</code>	Column width applied only at breakpoint bp (sm/md/lg/xl/xxl).	<code><div class="col-md-6">Half on md+</div></code>
<code>.offset-{bp}-{n}</code>	Shifts a column right by n units.	<code><div class="col-4 offset-md-2">Offset</div></code>
<code>.g-{n}</code>	Sets gap (gutters) between rows & columns. n = 0–5.	<code><div class="row g-3"></code>
<code>.gx-{n} / .gy-{n}</code>	Horizontal / vertical gutters independently.	

■ Display & Flex

Class	What it does	Example
<code>.d-none</code>	Hides the element (display: none).	
<code>.d-block</code>	Forces display: block.	
<code>.d-flex</code>	Enables Flexbox on the element.	<code><div class="d-flex"></code>
<code>.d-{bp}-{value}</code>	Responsive display — e.g. <code>.d-md-flex</code> shows flex only on md+.	
<code>.flex-row</code> / <code>.flex-column</code>	Sets flex direction to horizontal or vertical.	
<code>.flex-wrap</code>	Allows flex items to wrap to the next line.	
<code>.justify-content-{val}</code>	Aligns items along the main axis (start/center/end/between/around/evenly).	<code><div class="d-flex justify-content-center"></code>
<code>.align-items-{val}</code>	Aligns items along the cross axis (start/center/end/stretch/baseline).	
<code>.align-self-{val}</code>	Overrides cross-axis alignment for one flex item.	
<code>.flex-grow-1</code>	Lets a flex item grow to fill remaining space.	
<code>.order-{n}</code>	Controls visual order of a flex/grid item (0–5, first, last).	

■ Spacing (Margin & Padding)

Class	What it does	Example
<code>.m-{n}</code>	Margin on all sides. n = 0–5 (or auto).	<code><div class="m-3"></code>
<code>.mt-{n}</code>	Margin top.	
<code>.mb-{n}</code>	Margin bottom.	
<code>.ms-{n}</code>	Margin start (left in LTR).	
<code>.me-{n}</code>	Margin end (right in LTR).	
<code>.mx-{n}</code>	Margin left & right.	
<code>.my-{n}</code>	Margin top & bottom.	
<code>.p-{n}</code>	Padding on all sides.	<code><div class="p-4"></code>
<code>.pt/pb/ps/pe/px/py-{n}</code>	Same as margin variants but for padding.	
<code>.mx-auto</code>	Centers a block element horizontally.	<code><div class="w-50 mx-auto">Centered</div></code>

■ Colors & Backgrounds

Class	What it does	Example
<code>.text-primary</code>	Text in Bootstrap primary blue (#0D6EFD).	
<code>.text-secondary</code>	Text in muted gray.	
<code>.text-success</code>	Text in green (success state).	
<code>.text-danger</code>	Text in red (error/danger state).	
<code>.text-warning</code>	Text in yellow-orange (warning state).	
<code>.text-info</code>	Text in teal/cyan.	
<code>.text-light</code>	Light gray text — use on dark backgrounds.	
<code>.text-dark</code>	Dark text.	
<code>.text-muted</code>	Subdued gray text for hints or secondary info.	
<code>.text-white</code>	White text.	
<code>.bg-primary</code>	Background in primary blue.	<code><div class="bg-primary text-white"></code>
<code>.bg-light</code>	Light gray background.	
<code>.bg-dark</code>	Dark/near-black background.	
<code>.bg-transparent</code>	Removes background color.	

■ Typography

Class	What it does	Example
.h1 – .h6	Apply heading font size/weight without semantic tag.	<code><p class="h2">Styled as H2</p></code>
.display-1–6	Extra-large display headings, progressively smaller.	<code><h1 class="display-4">Big Title</h1></code>
.lead	Slightly larger, lighter paragraph for intros.	<code><p class="lead">Intro text</p></code>
.fw-bold	Font weight bold.	
.fw-normal	Font weight normal (400).	
.fw-light	Font weight light.	
.fst-italic	Italic text.	
.text-uppercase	TRANSFORMS TEXT TO UPPERCASE.	
.text-lowercase	transforms text to lowercase.	
.text-capitalize	Capitalizes First Letter of Each Word.	
.text-start	Left-align text.	
.text-center	Center-align text.	
.text-end	Right-align text.	
.text-truncate	Truncates overflowing text with an ellipsis...	
.small	80% font size; useful for footnotes/captions.	<code><small class="small">Note</small></code>

■ Buttons

Class	What it does	Example
.btn	Base button class — always required with a variant.	
.btn-primary	Solid blue button (main CTA).	<code><button class="btn btn-primary">Save</button></code>
.btn-secondary	Solid gray button.	
.btn-success / -danger / -warning / -info	Semantic colored buttons.	
.btn-light / -dark	Light or dark solid buttons.	
.btn-outline-{variant}	Transparent button with a colored border & text.	<code><button class="btn btn-outline-primary"></code>
.btn-sm / .btn-lg	Smaller or larger button sizes.	
.btn-link	Styled as a hyperlink but behaves as a button.	
.w-100 on .btn	Makes button span full width of its container.	<code><button class="btn btn-primary w-100"></code>

■ Forms

Class	What it does	Example
<code>.form-control</code>	Styles text inputs, textareas, and file inputs.	<code><input class="form-control" type="text"></code>
<code>.form-select</code>	Styles a dropdown.	<code><select class="form-select"></code>
<code>.form-check</code>	Wrapper for checkboxes and radio buttons.	
<code>.form-check-input</code>	Styles the checkbox/radio input itself.	<code><input class="form-check-input" type="checkbox"></code>
<code>.form-check-label</code>	Label paired with a form-check-input.	
<code>.form-label</code>	Styled label for form fields.	<code><label class="form-label">Email</label></code>
<code>.form-text</code>	Small helper/hint text below an input.	<code><div class="form-text">We never share.</div></code>
<code>.is-valid</code> / <code>.is-invalid</code>	Green or red validation state on an input.	
<code>.valid-feedback</code> / <code>.invalid-feedback</code>	Shown text for valid/invalid state.	
<code>.input-group</code>	Wraps input + prepend/append add-ons together.	
<code>.input-group-text</code>	The add-on label inside an <code>.input-group</code> .	
<code>.form-control-sm</code> / <code>-lg</code>	Smaller or larger input size.	
<code>.form-switch</code>	Turns a checkbox into a toggle switch.	

■ Cards

Class	What it does	Example
<code>.card</code>	Container with border, rounded corners, and shadow.	<code><div class="card"></code>
<code>.card-body</code>	Padded content area inside a card.	<code><div class="card-body"></code>
<code>.card-title</code>	Bold heading within a card body.	<code><h5 class="card-title">Title</h5></code>
<code>.card-text</code>	Paragraph text inside a card body.	
<code>.card-header</code>	Top section of a card (e.g., tab label or title bar.)	
<code>.card-footer</code>	Bottom section of a card.	
<code>.card-img-top</code>	Image at the top of a card, above the body.	<code></code>
<code>.card-img-bottom</code>	Image at the bottom of a card.	
<code>.card-link</code>	Styled anchor tag inside a card.	
<code>.card-group</code>	Renders a set of cards side-by-side with equal height.	

■ Navigation

Class	What it does	Example
<code>.navbar</code>	Top-level navigation bar wrapper.	<code><nav class="navbar navbar-expand-lg"></code>
<code>.navbar-brand</code>	Logo or site name link inside a navbar.	
<code>.navbar-toggler</code>	Hamburger button for collapsing nav on small screens.	
<code>.navbar-collapse</code>	The collapsible nav links container.	
<code>.navbar-nav</code>	The list of nav items inside a navbar.	
<code>.nav-item</code>	Single item in a nav list.	
<code>.nav-link</code>	Anchor inside a nav-item; handles active/disabled.	
<code>.navbar-dark</code>	Use light text/icons on a dark navbar background.	
<code>.navbar-light</code>	Use dark text/icons on a light navbar background.	
<code>.nav-tabs</code>	Turns nav into tab-style navigation.	
<code>.nav-pills</code>	Turns nav into pill-shaped buttons.	
<code>.active</code>	Marks the current page/tab link as active.	<code>Home</code>
<code>.breadcrumb</code>	Wrapper for breadcrumb navigation list.	
<code>.breadcrumb-item</code>	Individual step in a breadcrumb trail.	

■ Modals

Class	What it does	Example
<code>.modal</code>	Outermost wrapper of the modal dialog.	
<code>.modal-dialog</code>	Positions and sizes the modal box.	
<code>.modal-dialog-centered</code>	Vertically centers the modal on screen.	
<code>.modal-content</code>	The visible white box with border/shadow.	
<code>.modal-header</code>	Top section — usually title + close button.	
<code>.modal-title</code>	Heading text inside modal-header.	
<code>.modal-body</code>	Main content area of the modal.	
<code>.modal-footer</code>	Bottom section — usually action buttons.	
<code>.modal-sm</code> / <code>.modal-lg</code> / <code>.modal-xl</code>	Size variants for the modal dialog.	
<code>.data-bs-toggle="modal"</code>	Attribute on a trigger element to open a modal.	<code><button data-bs-toggle="modal" data-bs-target="#myModal"></code>

■ Alerts & Badges

Class	What it does	Example
<code>.alert</code>	Base alert box — always combine with a variant.	
<code>.alert-primary / -success / -danger / -warning / -info</code>	Colored alert variants.	<code><div class="alert alert-success">Done!</div></code>
<code>.alert-dismissible</code>	Adds space for a close (×) button inside the alert.	
<code>.alert-link</code>	Styled anchor inside an alert.	
<code>.badge</code>	Small inline label for counts or status.	<code>3</code>
<code>.bg-{variant} on .badge</code>	Sets badge background color.	<code>New</code>
<code>.rounded-pill on .badge</code>	Makes the badge fully rounded (pill shape).	

■ Tables

Class	What it does	Example
<code>.table</code>	Base style — adds padding and bottom borders.	<code><table class="table"></code>
<code>.table-striped</code>	Alternating row shading for readability.	
<code>.table-bordered</code>	Borders on all cells and the outer edge.	
<code>.table-borderless</code>	Removes all borders.	
<code>.table-hover</code>	Highlights a row when hovered.	
<code>.table-sm</code>	Reduces cell padding for a compact table.	
<code>.table-dark</code>	Dark background with light text.	
<code>.table-responsive</code>	Wraps table in a scrollable container on small screens.	<code><div class="table-responsive"><table></code>
<code>.table-{variant}</code>	Colors a table: primary, success, danger, warning, info, etc.	
<code>.caption-top</code>	Moves above the table.	

■ Utilities (Sizing, Borders, Shadows)

Class	What it does	Example
.w-25 / -50 / -75 / -100	Sets width to 25%, 50%, 75%, or 100%.	<code><div class="w-50"></code>
.h-25 / -50 / -75 / -100	Sets height to 25%, 50%, 75%, or 100%.	
.mw-100	Max-width: 100% — prevents overflow.	
.mh-100	Max-height: 100%.	
.vw-100 / .vh-100	Full viewport width / height.	
.border	Adds a thin border on all sides.	
.border-{side}	Border on top/bottom/start/end only.	
.border-0	Removes all borders.	
.border-{variant}	Colors the border (primary, danger, etc.).	
.rounded	Slightly rounded corners (border-radius).	
.rounded-circle	Makes element a circle (works on square images).	<code></code>
.rounded-pill	Very large radius — pill/stadium shape.	
.shadow-sm / .shadow / .shadow-lg	Adds a small, default, or large drop shadow.	
.overflow-auto	Adds scrollbar when content overflows.	
.overflow-hidden	Clips content that overflows the box.	
.position-relative	Sets position: relative.	
.position-absolute	Sets position: absolute.	
.position-fixed	Sets position: fixed to viewport.	
.top-0 / .bottom-0 / .start-0 / .end-0	Pin element to edge (use with .position-absolute).	
.opacity-{n}	Sets opacity: n = 25, 50, 75, or 100.	
.visually-hidden	Hides element visually but keeps it for screen readers.	
.d-grid	Enables CSS Grid on an element.	
.gap-{n}	Sets gap between grid/flex children (0–5).	

Bootstrap 5 · {bp} breakpoints: sm ≥576px · md ≥768px · lg ≥992px · xl ≥1200px · xxl ≥1400px | Spacing scale: 0=0 · 1=0.25rem · 2=0.5rem · 3=1rem · 4=1.5rem · 5=3rem