LANDIS-II Biomass Output v2.0 Extension User Guide

Robert M. Scheller

Portland State University

Last Revised: July 31, 2013

Table of Contents

| 1 | IN | NTRODUCTION | . 2 |
|---|------------|---|-----|
| | | Major Releases | |
| | 1.1 | 1.1 Version 2.0 | . 4 |
| | | 1.2 Version 1.2 | |
| | 12 | Minor Releases | , z |
| | 1.2 | 2.1 Version 2.0.2 | 2 |
| | 1.3 | Acknowledgements | . 2 |
| | | | |
| 2 | INPUT FILE | | .3 |
| | 2.1 | LandisData | .3 |
| | 2.2 | Timestep | .3 |
| | 2.3 | Timestep | .3 |
| | 2.4 | Species List (Optional) | .3 |
| | 2.5 | Aboveground Live Biomass Map Names (Required) | |
| | 2.6 | Dead Pool List (Optional) | .4 |
| | 2.7 | Dead Biomass Map Names (Optional) | |

1 Introduction

This document describes the **Biomass Output** extension for the LANDIS-II model. Readers should read the *LANDIS-II Model User Guide* prior to reading this document.

The output module described herein is fairly simple and produces three types of map:

- The aboveground live biomass (g m⁻²) for individual species (assuming that the Biomass Succession extension ANPP inputs are g biomass m⁻²).
- The total aboveground live biomass for all species.

1.1 Major Releases

1.1.1 Version 2.0

Biomass Output is compatible with LANDIS v6.0. Because maps are no longer limited to 65,000 integers, maps are output with the same units as the inputs. Assuming that the Biomass Succession extension (or similar) is operating at **g m⁻²**, then the outputs are also **g m⁻²**.

1.1.2 Version 1.2

In this version, we cleared up confusing naming convention for total aboveground biomass maps. Previously, the names for total biomass maps were generated by substituting "all" for the "{species}" variable in the map-name template (see section 2.5). Now, the "{species}" variable is replaced with "TotalBiomass".

1.2 Minor Releases

1.2.1 Version 2.0.2

Fixed a bug and the species list and woody biomass pools are now truly optional.

1.3 Acknowledgements

Funding for the development of LANDIS-II has been provided by the North Central Research Station (Rhinelander, Wisconsin) of the U.S. Forest Service. Valuable contributions to the development of the model and extensions were made by Brian R. Sturtevant, Eric J. Gustafson, and David J. Mladenoff.

2 Input File

The input parameters for this extension are specified in one input file. This text file must comply with the general format requirements described in section 3.1 Text Input Files in the *LANDIS-II Model User Guide*.

By default, a combined total of aboveground biomass for all species will be output.

2.1 LandisData

The first parameter is the title of the input file:

```
LandisData "Output Biomass"
```

2.2 Timestep

The second parameter is the time step in years. For example:

```
Timestep 15
```

2.3 MakeTable (Optional)

This optional parameter determines whether a table with all species mean aboveground biomass (g m⁻²) by ecoregion will be produced. The parameter must be: yes, no, Y, or N.

```
MakeTable yes
```

2.4 Species List (Optional)

First is an optional species list of the desired species from which to create maps. There is a List parameter, Species, followed by a list of one to many species. Alternatively, the keyword **all** can be used to indicate biomass should be output for every species. If **all** is indicated, do not list any species. For example:

```
Species pinubank pinuresi pinustro poputrem piceglau
```

2.5 Aboveground Live Biomass Map Names (Required)

The next parameter, MapNames, describes where output maps are placed and their format. The first portion lists the directory where the

maps should be placed, relative the location of the scenario text file (e.g., agemaps/). The second portion includes two variables for creating file names. {species} will be replaced with the species name. {timestep} will be replaced with the output time step. Other characters can be inserted as desired. A meaningful file extension (e.g., .qis) should also be included. For example:

```
MapNames output/biomass/bio-{species}-{timestep}.img
```

Note: Biomass output maps are not compatible with the .gis map output type.

2.6 Dead Pool List (Optional)

Next is a list of the desired dead pools from which to create maps. There is a List parameter, DeadPools, followed by a list. There are only three options for this list: or woody, non-woody, or both. For example:

```
DeadPools woody >> or non-woody or both
```

2.7 Dead Biomass Map Names (Optional)

Finally, a second MapNames parameter describes where dead biomass output maps are placed and their format. The first portion lists the directory where the maps should be places, relative the location of the scenario text file (e.g., agemaps/). The second portion includes two variables for creating file names. {pool} will be replaced with the dead pool name. {timestep} will be replaced with the output time step. Other characters can be inserted as desired. A meaningful file extension (e.g., .gis) should also be included. For example:

```
MapNames output/biomass/{pool}-{timestep}.img
```

Note: Dead biomass output maps are not compatible with the .gis map output type.