

API DOCUMENTATION FOR BNI P@Y

API DOCUMENTATION FOR BNI P@Y.....	1
Load Payment Zone.....	2
Request.....	2
Response.....	6
IMN CALLBACK URL (Instant Merchant notification).....	7
Request.....	8
Responses.....	10

Load Payment Zone

This API call gives back a HTML code, generating the iframe. It allows the merchant to output an HTML payment zone within an iframe.

Important: The result of this API call is NOT a Token nor a payment result. The Token or the payment result will be sent to the IMN URL given by the merchant only when a tokenization or payment is successful.

The look & feel of the iFrame is automatically generated.

Request

URL: https://mypay.bni.mg/api/load_payment_zone

Authentication

First level of credentials is Basic Auth

Basic authentication is a simple authentication scheme built into the HTTP protocol. To use it, send your HTTP requests with an Authorization header that contains the word Basic followed by a space and a base64-encoded string `username:password`.

Example: `Authorization: Basic ZGVtbzpwQDU1dzByZA==`

Headers

Content-Type string **[required]** application/json

user-agent string **[required]**

example: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/60.0.3112.78 Safari/537.36

Parameters

Authenticate **[required]**

`id_merchant` string **[required]**

Provided by BNI. id_merchant is the unique ID to identify the merchant.

`id_entity` string **[required]**

Provided by BNI. The id entity is the unique ID to identify the payment form.

`id_operator` string **[required]**

Provided by BNI. id_operator is the unique id of a user.

`operator_password` string **[required]**

Provided by BNI. Together with id_operator, these are the merchant's credentials

`order` **[required]**

`id_order` string **[required]**

A unique ID of the merchant's order. This ID is important as it will be always used by BNI to synchronize the status with the Merchant.

`currency` string **[required]**

.Allowed values: EUR| MUR | ZAR | GBP | USD| MGA (1 value as configured at bank)

`amount` number **[required]**

Example: 10.25

iframe_behavior [optional]

The merchant can specify here some custom look behaviors for the generated iFrame.

Important: custom_redirection_url is NOT the callback URL after a successful payment. The callback is done by BNI to the IMN URL the merchant will provide us. The redirection url acts only as a success page for the user.

All these options are optional.

height integer [optional]

Height of the iframe in pixels

width integer [optional]

Width of the iframe in pixels

custom_redirection_url integer [optional]

The redirection page after a successful payment. A fail payment does not redirect. The try again option is displayed within the iframe

language integer [optional]

Display language of the iFrame, Allowed values: EN | FR

request_mode string required

If simple the payment request is made for a one shot payment only.

If "membership", the parameters inside membership is mandatory. All payment will be manage on our side and it will automatically go through as configured with the parameters.

Allowed values:

simple | membership

touchpoint [required]

On any API Call to generate a payment iFrame (touchpoint = 'web'), an HTML block is sent back. The merchant just needs to echo (print) this HTML without modification. The iFrame will appear within the HTML.

On any API Call to get the payment link to be used in a Webview (touchpoint = 'native_app'), a link is sent back. The merchant just needs to use the link to load the Webview.

membership object

interval number

Every INTERVAL month, day etc.

>= 0

Example: 1

Multiple of: 1

start_date string<date>

frequency string

<= 8 characters

Allowed values: day | week | month | year

end_date string<date>

day_to_process number

>= 1<= 28

Example: 5

Multiple of: 1

membership_amount number

Example: 1240.05

Sample Payload

```
{
  "authenticate": {
    "id_merchant": "[ID_MERCHANT]",
    "id_entity": "[ID_ENTITY]",
    "id_operator": "[ID_OPERATOR]",
    "operator_password": "[OPERATOR_PASSWORD]"
  },
  "order": {
    "id_order": "INV5026", //id order
    "currency": "MGA", // CURRENCY IN ISO 4217
    "amount": 100
  },
  "iframe_behavior": {
    "height": 400,
    "width": 350,
    "custom_redirection_url": "www.example.com",
    "language": "FR" // FR | EN
  }, "touchpoint": "web" // 'web' | 'native_app',
  "membership": {
    "interval": 1,
    "start_date": "2019-08-24",
    "frequency": "day",
    "end_date": "2019-08-24",
    "day_to_process": 5,
    "membership_amount": 1240.05
  }
}
```

Response

Body

The payment module loaded will contain all data needed to capture the means of payments.

original_message string

Contain the exact API Call that the merchant sent.

answer object

operation_status string

Contain the status do not contain the payment status, it is only the status of the API Call

Possible values: success | fail

payment_zone_data string

For 'web' touchpoint, this parameter will contain the HTML of the iFrame to show on the payment page.

For 'native_app' touchpoint, this parameter will contain the link to be used in the Webview.

IMN CALLBACK URL (Instant Merchant notification)

To notify the merchant of a successful payment, a URL is defined upfront and hosted on Merchants side.

An HTTP request (**POST**) is sent to the IMN URL **ONLY WHEN A SUCCESSFUL PAYMENT IS MADE.**

Payload Received on IMN CALLBACK URL:

The crypted callback contains the unique order ID used by the merchant on the payment request creation + other data.

MiPS PS sends you a HTTP request upon a successfull payment

<code>crypted_callback</code>	<code>string</code>	<code>required</code>
-------------------------------	---------------------	-----------------------

The IMN callback must be decrypted by the merchant using the "decrypt_imn_data" API endpoint

Body application/json

<code>> authenticate</code>	Authenticate	<code>required</code>
<code>salt</code>	<code>string</code> Provided by BNI	<code>required</code>
<code>cipher_key</code>	<code>string</code> Provided by BNI	<code>required</code>
<code>received_crypte</code>	<code>data</code> <code>string</code> The crypted data received through the IMN CALLBACK	<code>required</code>

Request

Authentication

First level of credentials is Basic Auth

Basic authentication is a simple authentication scheme built into the HTTP protocol. To use it, send your HTTP requests with an Authorization header that contains the word Basic followed by a space and a base64-encoded string `username:password`.

Example: `Authorization: Basic ZGVtbzpwQDU1dzByZA==`

Headers

Content-Type string **[required]** application/json

user-agent string **[required]**

example: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/60.0.3112.78 Safari/537.36

URL: https://mypay.bni.mg/api/decrypt_imn_data

Parameters

`authenticate` **[required]**

`id_merchant` string **[required]**

Provided by BNI. id_merchant is the unique ID to identify the merchant.

`id_entity` string **[required]**

Provided by BNI. The id entity is the unique ID to identify the payment form.

`id_operator` string **[required]**

Provided by BNI. id_operator is the unique id of a user.

`operator_password` string **[required]**

Provided by BNI. Together with id_operator, these are the merchant's credentials

`salt` **[required]**

Provided by BNI

`cipher_key` **[required]**

Provided by BNI

`received_crypted_data` **[required]**

The crypted data received through the IMN CALLBACK

Sample Payload

```
{  
  "authenticate": {  
    "id_merchant": "[IDMERCHANT]",  
    "id_entity": "[IDENTITY]",  
    "id_operator": "[IDOPERATOR]",  
    "operator_password": "[OPERATOR_PASSWORD]"  
  },  
  "salt": "[SALT]",  
  "cipher_key": "[CYPHER_KEY]",  
  "received_crypted_data": "[CRYPTED]"  
}
```

Responses

This is received by the merchant after decrypting the encrypted Instant Merchant notification callback.

This answer contains all needed data for the merchant to update his databases and process the operations after a successful payment (send invoices, update orders, etc.)

sample response

```
{
  "amount": "string",
  "currency": "string",
  "status": "success",
  "checksum": "string",
  "id_order": "string",
  "transaction_id": "string",
  "type": "string",
  "reference": "string",
  "payment_method": "string",
  "additional_param": "string",
  "reason_fail": "string",
  "card_details": {
    "masked_card_number": "123456xxxxxx1234",
    "expiry_date": "mm/yy",
    "card_brand": "string"
  },
  "transaction_details": {
    "APPROVAL_CODE": "string",
    "MID": "string",
    "TID": "string",
    "TVR": "string",
    "TSI": "string",
    "RECEIPT_NO": "string",
    "AID": "string",
    "APP_NAME": "string",
    "NAME_ON_CARD": "string",
    "APPL_VERSION": "string",
    "AC_INFO": "string",
    "AC": "string",
    "PAN_SEQ_NUMBER": "string"
  }
}
```