

Pmetrics Objects and Plots


Michael Neely, MD

Professor of Pediatrics and Clinical Scholar

Director, Laboratory of Applied Pharmacokinetics and Bioinformatics

University of Southern California, Children's Hospital Los Angeles

General Workflow



General Workflow

1. After a run is complete an HTML summary page is created and displayed
2. A sequentially numbered run folder is created
3. The results can be loaded into R with `PM_load(n)`, where `n` is the run number

PM_result

- A PM_result object is created by PM_load(1) after NPAG/IT2B run 1, with the following fields
 - op
 - final
 - cycle
 - cov
 - pop and post (NPAG only)
 - data
 - model
 - Npdata/ITdata

PMop objects

- Observed vs. Predicted
- class: PMop, data.frame
- methods: plot, summary
- examples: run1\$op, run2\$op

PMop Structure

- Data frame with the following columns
 - **id**: Subject ID
 - **time**: time of observation/prediction
 - **obs**: the observed output value
 - **pred**: the predicted output value
 - **pred.type**: type of prediction, population or posterior
 - **icen**: summary of parameter distribution used for prediction, mean or median
 - **outeq**: output equation number for the observation/prediction
 - **block**: dosing block defined by EVID=4 events
 - **outSD**: SD of the observation, based on C0, C1, C2, C3 and gamma/lambda
 - **d**: pred-obs
 - **ds**: (pred-obs) 2
 - **wd**: (pred-obs)/SD
 - **wds**: (pred-obs) / SD 2 2

Summarizing PMop

	Time	Obs	Pred
Min	120.00	1.86	1.96
25%	121.03	4.50	4.49
Median	126.00	6.56	6.61
75%	132.00	8.88	8.94
Max	144.98	20.15	20.39
Mean	127.69	7.24	7.09
SD	7.86	3.80	3.69

Mean prediction error: -0.1474

Mean weighted prediction error (bias): -0.0879 (P=0.9121 different than 0)

Mean squared prediction error: 0.7778

Root mean squared error (RMSE): 0.8819

Percent root mean squared error (%RMSE): 12.18


Mean weighed squared prediction error: 0.9965

Bias-adjusted mean squared prediction error: 0.7561


Bias-adjusted mean weighted squared prediction error (imprecision): 0.9888

```
run1$op$summary(pred.type="post", icen="median", outeq=1)
```

Plotting PMop



```
run1$op$plot()
```

```
run1$op$plot(pred.type="pop", marker = list(color = "green"), linear = T)
```

PMfinal objects

- Final cycle parameter values
- class: PMfinal, NPAG/IT2B, list
- methods: plot, summary
- examples: run1\$final, run2\$final

PMfinal Structure

- List with the following objects
 - **popPoints**: (NPAG only) Data frame of the final cycle grid points with column names equal to the name of each random parameter plus prob for the associated probability of that point
 - **popMean**: The final cycle mean for each random parameter distribution
 - **popSD**: The final cycle SD for each random parameter distribution
 - **popCV**: The final cycle coefficient of variation for each random parameter distribution
 - **popVar**: The final cycle variance for each random parameter distribution
 - **popCov**: The final cycle covariance matrix for each random parameter distribution
 - **popCor**: The final cycle correlation matrix for each random parameter distribution
 - **popMedian**: The final cycle median for each random parameter distribution
 - **gridpts**: (NPAG only) The initial number of support points
 - **ab**: Matrix of boundaries for random parameter values. For NPAG, this is specified by the user prior to the run; for IT2B, it is calculated as a user specified multiple of the SD for the parameter value distribution
 - **postPoints**: (NPAG only) Data frame of the Bayesian posterior parameter points for each of the first 100 subjects, with the columns **id**, subject ID; **point**, point number for that subject; **parameters**, parameters in the model; **prob**, probability of each point in the posterior for each patient

Summarizing PMfinal

	par	type	quantile	value
1	Ka	WtMed	0.025	4.608512e-01
2	Ka	WtMed	0.500	6.625952e-01
3	Ka	WtMed	0.975	8.958512e-01
4	Ka	MAWD	0.025	4.092800e-03
5	Ka	MAWD	0.500	1.498528e-01
6	Ka	MAWD	0.975	3.180688e-01
7	Ke	WtMed	0.025	3.519846e-02
8	Ke	WtMed	0.500	4.393907e-02
9	Ke	WtMed	0.975	6.755382e-02
10	Ke	MAWD	0.025	4.409361e-03
11	Ke	MAWD	0.500	1.369061e-02
12	Ke	MAWD	0.975	2.131143e-02
13	V	WtMed	0.025	6.287781e+01
14	V	WtMed	0.500	7.339845e+01
15	V	WtMed	0.975	1.018518e+02
16	V	MAWD	0.025	5.888538e+00
17	V	MAWD	0.500	2.025000e+01
18	V	MAWD	0.975	3.817413e+01
19	Tlag1	WtMed	0.025	6.866592e-01
20	Tlag1	WtMed	0.500	1.177336e+00
21	Tlag1	WtMed	0.975	1.791292e+00
22	Tlag1	MAWD	0.025	1.992990e-01
23	Tlag1	MAWD	0.500	4.906768e-01
24	Tlag1	MAWD	0.975	8.750000e-01


NPAG

	mean	se.mean	cv.mean	var	se.var
Ka	1.3579700	0.137701091	0.10140216	3.792318e-01	1.230390e-01
Ke	0.0444298	0.003619635	0.08146863	2.620352e-04	8.501543e-05
V0	88.8163000	8.490104143	0.09559173	1.441637e+03	4.677289e+02
Tlag1	1.6135400	0.084027186	0.05207630	1.412114e-01	4.581501e-02

IT2B

```
run1$final$summary(lower = 0.025, upper = 0.975) #NPAG
run1$final$summary() #IT2B
```

Confidence in NP



17 points



1000 sets
x
17 points




1000
medians
MADs

Median (2.5%, 97.5%)
MAWD (2.5%, 97.5%)





Parametric Confidence

- $SE(\text{mean}) = SD / \sqrt{n_{\text{sub}}}$
- $SE(\text{var}) = \text{var} * \sqrt{2 / (n_{\text{sub}} - 1)}$


Plot PMfinal







```
run1$final$plot()
```




```
run1$final$plot(density=T)
```

```
run1$final$plot(Ke~V)
```



```
run2$final$plot()
```




```
run2$final$plot(Ke~V0)
```

PMcycle objects

- Cycle log-likelihoods, gamma/lambda, AIC, BIC, normalized parameter means, medians, SD
- class: PMcycle, list
- methods: plot
- examples: run1\$cycle, run2\$cycle

PMcycle structure

- List with the following objects
 - **names** Vector of names of the random parameters
 - **cycnum** Vector cycle numbers, which may start at numbers greater than 1 if a non-uniform prior was specified for the run (NPAG only)
 - **ll** Matrix of cycle number and $-2 \times \text{Log-likelihood}$ at each cycle
 - **gamlam** A matrix of cycle number and gamma or lambda at each cycle
 - **mean** A matrix of cycle number and the mean of each random parameter at each cycle, normalized to initial mean
 - **sd** A matrix of cycle number and the standard deviation of each random parameter at each cycle, normalized to initial standard deviation
 - **median** A matrix of cycle number and the median of each random parameter at each cycle, normalized to initial median
 - **aic** A matrix of cycle number and Akaike Information Criterion at each cycle
 - **bic** A matrix of cycle number and Bayesian (Schwartz) Information Criterion at each cycle



```
run1$cycle$plot()
```

PMcov objects

- Covariate values for each subject at each time of a covariate entry in the data file, combined with mean and median Bayesian posterior parameter estimates to enable covariate analysis
- class: PMcov, data.frame
- methods: plot, summary
- examples: run1\$cov, run2\$cov

PMcov structure


- **id** Subject identification
- **time** Times of covariate observations
- **covnames...** Columns with each covariate observations in the dataset for each subject and time
- **parnames...** Columns with each parameter in the model and the icen summary for each subject, replicated as necessary for covariate observation times and duplicated for Bayesian parameter means and medians
- **icen** The type of summarized Bayesian posterior individual parameter values: mean or median.

Summarizing PMcov


	id	time	wt	africa	age	gender	height	Ka	Ke	V	Tlag1
1	1	48	46.7	1	21	1	160	0.4320615	0.02425739	65.55692	0.54030745
2	2	60	66.5	1	30	1	174	0.7438166	0.03913897	119.52821	0.02096844
3	3	60	46.7	1	24	0	164	0.8960000	0.04307500	108.75000	2.10000000
4	4	60	50.8	1	25	1	165	0.8959996	0.05594505	119.54995	0.65999780
5	5	60	65.8	1	22	1	181	0.1040152	0.06782312	113.25171	0.02007594
6	6	60	65.0	1	23	1	177	0.8959928	0.03515412	71.85080	1.97996420
7	7	60	51.7	1	27	0	161	0.2160000	0.08366500	34.95000	1.78000000
8	8	60	51.2	1	22	1	163	0.8959970	0.03515467	71.85030	1.97998490
9	9	60	55.0	1	23	1	174	0.7919426	0.04406498	101.55640	0.89971335
10	10	60	52.1	1	32	1	163	0.6560146	0.06188319	61.95165	0.82007268
11	11	60	56.5	1	34	1	165	0.5840032	0.06782538	73.64966	1.33998410
12	12	60	47.9	1	54	0	160	0.4641038	0.03021784	91.63832	1.01995260
13	13	60	60.5	1	24	1	180	0.2160000	0.08366500	34.95000	1.78000000
14	14	60	50.2	1	26	1	174	0.5760552	0.04406021	117.75225	0.33000576

```
run1$cov$summary( )
```


Plotting PMcov



```
run1$cov$plot(V~wt)
```



```
run1$cov$plot(Ke~age, lowess=F, reg=T, pch=3)
```



```
run1$cov$plot(I(V*wt)~time)
```

PMcov\$step()

- Checks each parameter against all covariates in stepwise multivariate linear regression
- Model selection is by AIC
- Default is backwards selection, i.e. start with a parameter and all covariates, then successively remove parameters associated with the greatest AIC drop until no further improvement in AIC
- Report P-value of retained parameters in multivariate linear regression

PMstep

	Ka	Ke	V	Tlag1
wt	NA	NA	NA	0.1484646
africa	NA	NA	NA	NA
age	NA	NA	NA	NA
gender	NA	NA	NA	NA
height	NA	NA	NA	NA

```
run1$cov$step( )
```

PMpop/post objects

- Predictions based on mean/median population or posterior Bayesian parameter values at `PM_fit$run(..., idelta)` frequency
- Only available after NPAG run
- class: PMpop/PMpost, data.frame
- methods: none (but can be plotted as argument to `plot.PMmdata`)
- examples: `run1$post`, `run1$pop`, `run2$post`, `run2$pop.2`

PMpop/post structure

- **id** Subject id
- **time** Time of predictions in decimal hours
- **icen** Prediction based on mean or median of Bayesian population/posterior parameter distribution
- **pred** Predicted output for each outeq
- **outeq** Output equation number
- **block** Observation blocks within subjects as defined by EVID=4 dosing events

PM_data objects

- The data file for the run
- class: PM_data
- methods: plot, summary
- examples: data1, data2

Summarizing PM_data

```
Number of subjects: 20
Number of inputs: 1
Number of outputs: 1
Total number of observations (outeq 1): 139, with 0 (0.000%) missing
Number of covariates: 5
```

```
THE FOLLOWING ARE MEAN (SD), MIN TO MAX
```

```
-----
```

INPUTS

```
Number of doses per subject (input 1): 6.000 (0.000), 6.000 to 6.000
Dose per subject (input 1): 585.000 (45.189), 450.000 to 600.000
```

OUTPUTS

```
Number of obs per subject (outeq 1): 6.950 (0.224), 6.000 to 7.000
Observation per subject (outeq 1): 7.241 (3.799), 1.860 to 20.150
```

COVARIATES

```
wt: 54.538 (7.173), 43.000 to 66.500
africa: 1.000 (0.000), 1.000 to 1.000
age: 27.035 (7.717), 19.000 to 54.000
gender: 0.749 (0.434), 0.000 to 1.000
height: 167.792 (7.562), 150.000 to 181.000
```

```
-----
Note: See help(summary.PMmatrix) for accessing specific items by name.
```


```
data1$summary()
```

Summarizing PM_data


id		I(dose/wt)	
Min.	: 1.00	Min.	: 9.023
1st Qu.:	5.75	1st Qu.:	10.081
Median	:10.50	Median	:10.764
Mean	:10.50	Mean	:10.844
3rd Qu.:	15.25	3rd Qu.:	11.742
Max.	:20.00	Max.	:12.848

```
dosekg <- data1$summary(formula = I(dose/wt)~id, FUN = mean)
summary(dosekg$formula)
```

Plotting PM_data



```
data1$plot()
```



```
data1$plot(overlay = F)
```

Getting help on plots

- `?PM_result`