MiMo – Model Mikroprogramirane CPE v0.5a

Naslov/ signal	Kontrolni (»Control«) ROM 256x32bitov (23 izkoriščenih)														Opis vsebine mikroprograma				Odločitveni (»Decision«) ROM 256x16bitov	
	1	2	1	2	2	1	1	1	1	2	2	1	2	4						
	swrite	datasel	indexsel	cond	regsrc	imload	irload	dwrite	pcload	pcsel	addrsel	datawrite	op2sel	aluop	Oznaka/ op.koda:	Oznaka: strojni ukaz ali »mikroukaz«	Opis mikroukaza	Mikroukaz	true 8bit	false 8bit
0							1				0				fetch:	»IR<-M[PC]«	IR<-M[PC],goto [1]	addrsel=pc irload=1	1	1
1			1						1	0						»PC<-PC+1«	PC++, goto »Op+2«	pcload=1 pcsel=pc, opcode_jump	2	2
2					2			1					0	0	0:	ADD Rd,Rs,Rt	ADD op. Rd,Rs,Rt, goto fetch:	aluop=add op2sel=treg dwrite=1 regsrc=aluout, goto fetch	0	0
42 0x2a						1					0				40:	JNEZ Rs,immed	immed<-M[PC], goto [0x82]	addrsel=pc imload=1	82	82
65 0x41					0			1			0				63:	LI Rd,Immed	Rd<-immed<-M[PC], goto pcincr:	addrsel=pc dwrite=1 regsrc=databus, goto pcincr	84	84
67 0x43						1					0				65:	SW Rd,immed	immed<-M[PC], goto [0x83]	addrsel=pc imload=1, goto 83	83	83
130 0x82				2									2	1		JNEZ Rs,immed	SUB op. Rs-0, if Z then pcincr: else jump:	aluop=sub op2sel=const0, if z then pcincr else jump	84	85
131 0x83		1									1	1				SW Rd,immed	Rd->M[immed]; goto pcincr:	addrsel=immed datawrite=1 datasel=dreg, goto pcincr	84	84
132 0x84									1	0					pcincr:	PC++, goto fetch:	PC<-PC+1, goto fetch:	pcload=1 pcsel=pc, goto fetch	0	0
133 0x85									1	1					jump:	PC<-immed, goto fetch:	immed->PC, goto fetch:	pcload=1 pcsel=immed, goto fetch	0	0

datasel:
- 0..PC
- 1..Dreg
- 2..Treg
- 3..ALU

regsrc:
- 0..DBus
- 1..IMM
- 2..ALU
- 3..Sreg

pcsel:
- 0..PC+1
- 1..IMM
- 2..PC+IMM
- 3..Sreg

addrsel:
- 0..PC
- 1..IMM
- 2..ALU
- 3..Sreg

op2sel:
- 0..Treg
- 1..IMM
- 2.."0"
- 3.."1"

cond:
- 0..z
- 1..nor
- 2..n
- 3..c

aluop:
- 0..+
- 1..-
- 2..*
- 3../
- ...

Format 1:

Op.koda	Treg	Sreg	Dreg
7	3	3	3

Format 2:
- Format 1 + 16-bitni tak. operand

v 0.5a


MiMo - Microprogrammed CPU Model v0.5a EVO
SysClk
CLKIN
Reset
Debug
Cycle
Stop
Instr
Addr
Cont
Instruction:
Address BUS
Data BUS
RAM
RAM 16K x 16
ImmReg
Registers
Debug Unit
Address, Data Bus
Spec. Registers
PCreg
IR
IMM
ALUOut
ALU
Flags
InsReg
ADDR DEC.
Status
New_CMD
ICycles
Cycles
Cmds
Quick tips:
Use ctrl+t to manually toggle global clock signal
Use Simulate->Ticks Enabled for automatic clock signal


Microcode Control Unit
Control ROM
Address of third uinstruction is "opcode+2"
ROM 256 x 32
Micro Instruction
MicroPC
Micro_Instr
Next_Instr
Frame Buffer LED 16x16
TTY
Clear_Screen
Decision ROM
ROM 256 x 16
Microcounter
CycleCounter
Based on: http://minnie.tuhs.org/Programs/UcodeCPU/index.html
v05: Migration to EVO, Debug, Counters, ImmReg Units
v05a: norz instead of corz

Spisek in opis podprtih ukazov v zbirniku

add Rd,Rs,Rt (0)
Rd <- Rs + Rt PC <- PC + 1

sub Rd,Rs,Rt (1)
Rd <- Rs - Rt PC <- PC + 1

mul Rd,Rs,Rt (2)
Rd <- Rs * Rt PC <- PC + 1

div Rd,Rs,Rt (3)
Rd <- Rs / Rt PC <- PC + 1

rem Rd,Rs,Rt (4)
Rd <- Rs % Rt PC <- PC + 1

and Rd,Rs,Rt (5)
Rd <- Rs AND Rt PC <- PC + 1

or Rd,Rs,Rt (6)
Rd <- Rs OR Rt PC <- PC + 1

xor Rd,Rs,Rt (7)
Rd <- Rs XOR Rt PC <- PC + 1

nand Rd,Rs,Rt (8)
Rd <- Rs NAND Rt PC <- PC + 1

nor Rd,Rs,Rt (9)
Rd <- Rs NOR Rt PC <- PC + 1

not Rd,Rs (10)
Rd <- NOT Rs PC <- PC + 1

lsl Rd,Rs,Rt (11)
Rd <- Rs << Rt PC <- PC + 1

lsr Rd,Rs,Rt (12)
Rd <- Rs >> Rt PC <- PC + 1

asr Rd,Rs,Rt (13)
Rd <- Rs >> Rt (filled bits are the sign bit) PC <- PC + 1

rol Rd,Rs,Rt (14)
Rd <- Rs rolled left by Rt bits PC <- PC + 1

ror Rd,Rs,Rt (15)
Rd <- Rs rolled right by Rt bits PC <- PC + 1

addi Rd,Rs,immed (16)
Rd <- Rs + immed PC <- PC + 2

subi Rd,Rs,immed (17)
Rd <- Rs - immed PC <- PC + 2

muli Rd,Rs,immed (18)
Rd <- Rs * immed PC <- PC + 2

divi Rd,Rs,immed (19)
Rd <- Rs / immed PC <- PC + 2

remi Rd,Rs,immed (20)
Rd <- Rs % immed PC <- PC + 2

andi Rd,Rs,immed (21)
Rd <- Rs AND immed PC <- PC + 2

ori Rd,Rs,immed (22)
Rd <- Rs OR immed PC <- PC + 2

xori Rd,Rs,immed (23)
Rd <- Rs XOR immed PC <- PC + 2

nandi Rd,Rs,immed (24)
Rd <- Rs NAND immed PC <- PC + 2

nori Rd,Rs,immed (25)
Rd <- Rs NOR immed PC <- PC + 2

lsli Rd,Rs,immed (26)
Rd <- Rs << immed PC <- PC + 2

lsri Rd,Rs,immed (27)
Rd <- Rs >> immed PC <- PC + 2

asri Rd,Rs,immed (28)
Rd <- Rs >> immed (filled bits are the sign bit) PC <- PC + 2

roli Rd,Rs,immed (29)
Rd <- Rs rolled left by immed bits PC <- PC + 2

rori Rd,Rs,immed (30)
Rd <- Rs rolled right by immed bits PC <- PC + 2

addc Rd,Rs,Rt,immed (31)
Rd <- Rs + Rt
if carry set, PC <- immed else PC <- PC + 2

subc Rd,Rs,Rt,immed (32)
Rd <- Rs - Rt
if carry set, PC <- immed else PC <- PC + 2

jeq Rs,Rt,immed (33)
if Rs == Rt, PC <- immed else PC <- PC + 2

jne Rs,Rt,immed (34)
if Rs != Rt, PC <- immed else PC <- PC + 2

jgt Rs,Rt,immed (35)
if Rs > Rt, PC <- immed else PC <- PC + 2

jle Rs,Rt,immed (36)
if Rs <= Rt, PC <- immed else PC <- PC + 2

jlt Rs,Rt,immed (37)
if Rs < Rt, PC <- immed else PC <- PC + 2

jge Rs,Rt,immed (38)
if Rs >= Rt, PC <- immed else PC <- PC + 2

jeqz Rs,immed (39)
if Rs == 0, PC <- immed else PC <- PC + 2

jnez Rs,immed (40)
if Rs != 0, PC <- immed else PC <- PC + 2

jgtz Rs,immed (41)
if Rs > 0, PC <- immed else PC <- PC + 2

jlez Rs,immed (42)
if Rs <= 0, PC <- immed else PC <- PC + 2

jltz Rs,immed (43)
if Rs < 0, PC <- immed else PC <- PC + 2

jgez Rs,immed (44)
if Rs >= 0, PC <- immed else PC <- PC + 2

jmp immed (45)
PC <- immed

beq Rs,Rt,immed (46)
if Rs == Rt, PC <- PC + immed else PC <- PC + 2

bne Rs,Rt,immed (47)
if Rs != Rt, PC <- PC + immed else PC <- PC + 2

bgt Rs,Rt,immed (48)
if Rs > Rt, PC <- PC + immed else PC <- PC + 2

ble Rs,Rt,immed (49)
if Rs <= Rt, PC <- PC + immed else PC <- PC + 2

blt Rs,Rt,immed (50)
if Rs < Rt, PC <- PC + immed else PC <- PC + 2

bge Rs,Rt,immed (51)
if Rs >= Rt, PC <- PC + immed else PC <- PC + 2

beqz Rs,immed (52)
if Rs == 0, PC <- PC + immed else PC <- PC + 2

bnez Rs,immed (53)
if Rs != 0, PC <- PC + immed else PC <- PC + 2

bgtz Rs,immed (54)
if Rs > 0, PC <- PC + immed else PC <- PC + 2

blez Rs,immed (55)
if Rs <= 0, PC <- PC + immed else PC <- PC + 2

bltz Rs,immed (56)
if Rs < 0, PC <- PC + immed else PC <- PC + 2

bgez Rs,immed (57)
if Rs >= 0, PC <- PC + immed else PC <- PC + 2

br immed (58)
PC <- PC + immed
 # Register 7 is used as the stack pointer. It points at the most-recently pushed value on the stack. M[ ] means the memory cell at the location in the brackets.

jsr immed (59)
R7--
M[R7] <- PC + 2, i.e. skip the current 2-word instruction
PC <- immed

rts (60)
PC <- M[R7]
R7++

inc Rs (61)
Rs <- Rs + 1 PC <- PC + 1

dec Rs (62)
Rs <- Rs - 1 PC <- PC + 1

li Rd,immed (63)
Rd <- immed PC <- PC + 2

lw Rd,immed (64)
Rd <- M[immed] PC <- PC + 2

sw Rd,immed (65)
M[immed] <- Rd PC <- PC + 2

lwi Rd,Rs,immed (66)
Rd <- M[Rs+immed] PC <- PC + 2

swi Rd,Rs,immed (67)
M[Rs+immed] <- Rd PC <- PC + 2

push Rd (68)
R7--
M[R7] <- Rd PC <- PC + 1

pop Rd (69)
Rd <- M[R7]
R7++ PC <- PC + 1

move Rd,Rs (70)
Rd <- Rs PC <- PC + 1

clr Rs (71)
Rs <- 0 PC <- PC + 1

neg Rs (72)
Rs <- -Rs PC <- PC + 1

lwri Rd,Rs,Rt (73)
Rd <- M[Rs+Rt] PC <- PC + 1

swri Rd,Rs,Rt (74)
M[Rs+Rt] <- Rd PC <- PC + 1