

Date: 27Apr26

Time: 14:16

mixed Turbofan

Alt=11582m / Mn=0.650 ISA , Rel GG Speed=0.972

Station	W kg/s	T K	P kPa	WRstd kg/s	FN	=	
amb		216.65	20.646				5.61 kN
1	14.277	235.00	27.430		TSFC	=	21.0179 g/(kN*s)
2	14.277	235.00	26.882	48.597	WF Burner	=	0.11797 kg/s
13	8.531	316.95	72.211	12.554	s NOX	=	0.2739
21	5.746	316.95	72.211	8.456	BPR	=	1.4846
25	5.746	316.95	71.523	8.538	Core Eff	=	0.4612
3	5.459	660.79	727.516	1.151	Prop Eff	=	0.4955
31	4.540	660.79	727.516		P3/P2	=	27.063
4	4.657	1550.69	705.550	1.552	P5/P2	=	3.1545 EPR
41	4.945	1503.85	705.550	1.622	P16/P6	=	0.84133
43	4.945	1157.43	200.087		A63	=	0.06136 m ²
44	5.232	1132.24	200.087		A163	=	0.09316 m ²
45	5.232	1132.24	196.084	5.359	A64	=	0.15451 m ²
49	5.232	941.49	84.800		XM63	=	0.64091
5	5.519	921.46	84.800	11.793	XM163	=	0.36496
6	5.807	909.37	83.145		XM64	=	0.50001
16	8.531	316.95	69.952		P63/P6	=	0.99025
64	14.337	569.43	73.927		P163/P16	=	0.98955
8	14.337	569.43	73.927	27.624	A8	=	0.12114 m ²
Bleed	0.057	660.79	727.516		CD8	=	0.95000
-----					Ang8	=	25.00 °
Efficiencies:	isent	polytr	RNI	P/P	P8/Pamb	=	3.58065
Outer LPC	0.9359	0.9442	0.337	2.686	WLkBy/W25	=	0.00000
Inner LPC	0.9359	0.9442	0.337	2.686	WCHN/W25	=	0.05000
HP Compressor	0.8415	0.8826	0.630	10.172	WCHR/W25	=	0.05000
Burner	0.9994			0.970	Loading	=	116.14 %
HP Turbine	0.9109	0.8979	1.010	3.526	WCLN/W25	=	0.00000
LP Turbine	0.9192	0.9112	0.389	2.312	WCLR/W25	=	0.05000
Mixer	0.5000				WBHD/W21	=	0.00000
-----					far7	=	0.00830
HP Spool mech Eff	0.9900	Speed	22162 rpm		WBLD/W25	=	0.01000
LP Spool mech Eff	0.9900	Speed	13937 rpm		PWX	=	110.0 kW
-----					P16/P13	=	0.9687
P2/P1=	0.9800	P25/P21=	0.9905	P45/P44=	P6/P5	=	0.9805

hum [%]	war0	FHV	Fuel				
0.0	0.00000	43.150	Generic				

Input Data File:

C:\Users\clardyj\Downloads\off Design\jet_optimized_2.CYM