

Date: 09Mar26

Time: 14:04

mixed Turbofan

Alt=11582m / Mn=0.650 ISA

Station	W kg/s	T K	P kPa	WRstd kg/s	FN	=	6.10 kN
amb		216.65	20.646				
1	14.689	235.00	27.430		TSFC	=	21.4619 g/(kN*s)
2	14.689	235.00	26.882	50.000	WF Burner	=	0.13092 kg/s
13	8.618	323.57	75.269	12.294	s NOX	=	0.3149
21	6.071	323.57	75.269	8.660	BPR	=	1.4196
25	6.071	323.57	74.516	8.747	Core Eff	=	0.4674
3	5.767	682.16	783.453	1.148	Prop Eff	=	0.4820
31	4.796	682.16	783.453		P3/P2	=	29.144
4	4.927	1606.68	759.949	1.551			
41	5.230	1557.99	759.949	1.622	P16/P6	=	0.82610
43	5.230	1201.10	215.599		A63	=	0.06136 m ²
44	5.534	1174.73	215.599		A163	=	0.09316 m ²
45	5.534	1174.73	211.287	5.358	A64	=	0.15451 m ²
49	5.534	975.81	90.184		XM63	=	0.65762
5	5.837	954.85	90.184	11.939	XM163	=	0.35537
6	6.141	942.15	88.381		XM64	=	0.50000
16	8.618	323.57	73.011		P63/P6	=	0.99000
64	14.759	595.23	77.873		P163/P16	=	0.99000
8	14.759	595.23	77.873	27.601	A8	=	0.12114 m ²
Bleed	0.061	682.16	783.453		CD8	=	0.95000
-----					Ang8	=	25.00 °
Efficiencies:	isent	polytr	RNI	P/P	P8/Pamb	=	3.77179
Outer LPC	0.9077	0.9200	0.337	2.800	WLkBy/W25	=	0.00000
Inner LPC	0.9077	0.9200	0.337	2.800	WCHN/W25	=	0.05000
HP Compressor	0.8375	0.8800	0.641	10.514	WCHR/W25	=	0.05000
Burner	0.9995			0.970	Loading	=	100.00 %
HP Turbine	0.9126	0.9000	1.044	3.525	WCLN/W25	=	0.00000
LP Turbine	0.9181	0.9100	0.402	2.343	WCLR/W25	=	0.05000
Mixer	0.5000				WBHD/W21	=	0.00000
-----					far7	=	0.00895
HP Spool mech Eff	0.9900	Nom Spd	22800 rpm		WBLD/W25	=	0.01000
LP Spool mech Eff	0.9900	Nom Spd	14600 rpm		PWX	=	110.0 kW
-----					P16/P13	=	0.9700
P2/P1=	0.9800	P25/P21=	0.9900	P45/P44=	P6/P5	=	0.9800

hum [%]	war0	FHV	Fuel				
0.0	0.00000	43.150	Generic				

Input Data File:

C:\Users\CLARDYJ\Desktop\gasturb\jet_optimized_1.CYM