

Date: 10Mar26

Time: 21:17

mixed Turbofan

Alt=11582m / Mn=0.650 ISA

Invalid Result:

Your input data do not lead to a reasonable cycle. Please check and correct your data!

Station	W kg/s	T K	P kPa	WRstd kg/s
amb		216.65	20.646	
1	14.689	235.00	27.430	
2	14.689	235.00	26.882	50.000
13	8.012	313.19	67.205	12.594
21	6.677	313.19	67.205	10.495
25	6.677	313.19	66.533	10.601
3	6.476	572.79	465.728	1.987
31	5.775	572.79	465.728	
4	5.969	1700.00	451.756	3.252
41	6.303	1647.01	451.756	3.380
43	6.303	1424.82	218.339	
44	6.636	1386.50	218.339	
45	6.636	1386.50	213.972	6.894
49	6.636	1247.67	128.716	
5	6.837	1227.35	128.716	11.107
6	6.837	1227.35	126.142	
16	8.012	313.19	65.188	
64	14.849	764.57	75.578	
8	14.849	764.57	75.578	32.428
Bleed	0.033	572.79	465.727	

Efficiencies:	isent	polytr	RNI	P/P
Outer LPC	0.9000	0.9120	0.337	2.500
Inner LPC	0.9000	0.9120	0.337	2.500
HP Compressor	0.8800	0.9073	0.595	7.000
Burner	0.9995			0.970
HP Turbine	0.9000	0.8924	0.581	2.069
LP Turbine	0.9100	0.9051	0.336	1.662
Mixer	0.5000			

HP Spool mech Eff	1.0000	Nom Spd	22800 rpm
LP Spool mech Eff	1.0000	Nom Spd	14600 rpm

P2/P1=	0.9800	P25/P21=	0.9900	P45/P44=	0.9800
--------	--------	----------	--------	----------	--------

hum [%]	war0	FHV	Fuel
0.0	0.00000	43.150	Generic

FN	=	7.39	kN
TSFC	=	26.1747	g/(kN*s)
WF Burner	=	0.19337	kg/s
s NOX	=	0.1457	
BPR	=	1.2000	
Core Eff	=	0.4889	
Prop Eff	=	0.4365	
P3/P2	=	17.325	
P16/P6	=	0.51679	
A63	=	0.04870	m ²
A163	=	0.28352	m ²
A64	=	0.33222	m ²
XM63	=	1.05004	
XM163	=	0.11183	
XM64	=	0.24709	
P63/P6	=	0.99000	
P163/P16	=	0.99000	
A8	=	0.14304	m ²
CD8	=	0.95000	
Ang8	=	25.00	°
P8/Pamb	=	3.66062	
WLkBy/W25	=	0.00000	
WCHN/W25	=	0.05000	
WCHR/W25	=	0.05000	
Loading	=	100.00	%
WCLN/W25	=	0.00000	
WCLR/W25	=	0.03000	
WBHD/W21	=	0.00000	
far7	=	0.01319	
WBLD/W25	=	0.00500	
PWX	=	50.0	kW
P16/P13	=	0.9700	
P6/P5	=	0.9800	

Input Data File:

C:\Users\CLARDYJ\Downloads\prelim.CYM