

PH3244
Experiment - 6
Ultrasonic Diffraction

Aumshree P. Shah
20231059^{a)}

(Dated: 2 April 2026)

Synopsis

In this experiment we determine the wavelength and velocity of ultrasonic wave in a liquid. We also find bulk modulus and compressibility of the given liquid.

CONTENTS

I. Theory and Procedure	2
A. Theory	2
B. Procedure	2
II. Observation	3
1. For 1st crystal	3
A. For 2nd crystal	3
III. Calculations, Analysis and Characteristics	4
A. Sources of Error	4
1. Systematic Errors	4
2. Random Errors	4
B. Error Propagation	4
C. Calculations	5
IV. Result and Conclusion	5
References	5
A. Theoretical values and comparison	6
B. Improvements in procedure	6

^{a)} aumshree.pinkalbenshah@students.iiserpune.ac.in

I. THEORY AND PROCEDURE

A. Theory

From FIG - 1 we see that the ultrasonic waves generated by the transducer travel down the medium (liquid), gets reflected at the bottom (flat glass plate) of the cell. The incident and reflected waves interfere and a stationary / standing wave pattern is formed.

The velocity of ultrasonic waves in a liquid is calculated using the formula:

$$V = \mu \Lambda \quad (1)$$

where μ is the frequency of the crystal oscillator and Λ is the wavelength of waves. We have

$$\Lambda = \frac{n\lambda}{\sin \theta} \quad (2)$$

where n is the order of diffraction, λ is the wavelength of the laser used and θ is the angle of diffraction.

We can find the angle of diffraction by the equation

$$\theta = \tan^{-1} \left(\frac{D}{L} \right) \quad (3)$$

where D is the order length and L is the distance measured from the crystal oscillator to the detector.

The bulk modulus of the liquid is

$$\beta = \rho V^2 \quad (4)$$

where ρ is the density of the liquid and V is the velocity of the ultrasonic wave.

The adiabatic compressibility of a liquid can also be calculated using the relation

$$K = \frac{1}{\rho V^2} \quad (5)$$




FIG. 1: Optical system for observation of diffraction by ultrasonic waves.

B. Procedure

Refer to the manual [Cat (2026)] for a look at procedure, although the required pages will be attached at the back for submition along with the signed report.

II. OBSERVATION

1. For 1st crystal¹

Here we use the plotting graphs method. We put a graph paper very far away and then mark the points in it to measure the distance.

$$\begin{aligned}\lambda &= 650\text{nm} \\ L &= 2.86\text{m} \\ \mu &= 3.25 \text{ MHz} \\ \rho &= 998 \text{ Kg/m}^3\end{aligned}$$

n (Index)	Distance (cm)	Type of Distance
1	0.9	peak to peak index fringe
2	1.7	peak to peak index fringe
3	1.3	From center
4	1.8	From center

TABLE I: Fringe readings for the above variables.

A. For 2nd crystal

Here we use the screw gauge method in which we compose the small L by taking a more precise measurement using an intensity detector.

$$\begin{aligned}\lambda &= 650\text{nm} \\ L &= 2.34\text{m} \\ \mu &= 3.09 \text{ MHz} \\ \rho &= 998 \text{ Kg/m}^3\end{aligned}$$

n (Index)	Distance (cm)
1	0.9
2	1.7

TABLE II: Fringe readings for the above variables using different method.

Data taken on 11 Mar 2026.

¹ The least count is to be interpreted from the significant figures written

III. CALCULATIONS, ANALYSIS AND CHARACTERISTICS

A. Sources of Error

1. Systematic Errors

1. In alignment of the beam with the crystal.
2. Improper standing wave produced than the theoretical.
3. Non Parallel Screen causing increase in distance.
4. Index of fringe being different than what is measured.

2. Random Errors

1. Human errors in measurement.
2. Uncertainty in instruments.
3. Shaking of table resulting in moving fringes.
4. Diffraction increasing the fringe width.

B. Error Propagation

To calculate the standard deviation from values we have measured with some least count, and the values we have applied digitally, we use the formula [Tewari (2016)]:

$$\sigma = \frac{\text{Least Count}}{\sqrt{12}} \quad (6)$$

and to calculate the standard deviation for values we have applied on analog instrument with some least count, we use the formula [Tewari (2016)]:

$$\sigma = \frac{\text{Least Count}}{\sqrt{24}} \quad (7)$$

Since all our observations only satisfy the criteria for Equation-6 we will be using that. Now from Equation-1,2,3 we can write V as :

$$V = \mu n \lambda \frac{\sqrt{D^2 + L^2}}{D} \quad (8)$$

to calculate the error of V we notice that it'll only (my only here I mean the most significant factor of error) will be the uncertainty in D , hence in error calculation we will assume other errors are negligible. Now using formula for error propagation [Taylor (1997)], for Equation-8 we see that:

$$\begin{aligned} \sigma_V / \sigma_D &= \frac{d}{dD} V \\ &= \mu n \lambda \frac{1}{D} \frac{d}{dD} (\sqrt{D^2 + L^2}) + \mu n \lambda \sqrt{D^2 + L^2} \frac{d}{dD} \left(\frac{1}{D} \right) \\ \Rightarrow \sigma_V &= \left(\mu n \lambda \frac{1}{\sqrt{D^2 + L^2}} - \mu n \lambda \sqrt{D^2 + L^2} \frac{1}{D^2} \right) \sigma_D \end{aligned} \quad (9)$$

Similarly from Equation-4,5 we get the uncertainty in β and K as:

$$\sigma_\beta = 2V \rho \sigma_V \quad (10)$$

$$\sigma_K = \frac{2}{\rho V^3} \sigma_V \quad (11)$$

C. Calculations

First we see that since the Table-2 has only 2 data points, where also there is a good chance that it might have high precision and low accuract, we wil not consider the data from Table-2 in our calculations. Using Equation-8,4,5 to calculate the variables and Equation-9,10,11 to calcualte their uncertainty, we get:

n	Distance (cm)	Least Count (cm)	SI Distance (m)	SI Uncertainty (m)	Velocity (m/sec)	Velocity Uncertainty (m/sec)
1	0.45	0.05	0.0045	0.00014	1343	42
2	0.85	0.05	0.0085	0.00014	1422	23
3	1.30	0.10	0.0130	0.00029	1394	29
4	1.80	0.10	0.0180	0.00029	1343	19

TABLE III: Calculating velocity from TABLE-1

Using the weighted average formula [sta (2026)] we can calculate V , β and K which will be discussed in results.

$$\bar{v} = \frac{\sum_{i=1}^N \frac{v_i}{\sigma_i^2}}{\sum_{i=1}^N \frac{1}{\sigma_i^2}} \quad (12)$$

$$\sigma_{\bar{v}} = \sqrt{\frac{1}{\sum_{i=1}^N \frac{1}{\sigma_i^2}}} \quad (13)$$

e weighted average we get is: From this

IV. RESULT AND CONCLUSION

By taking the weighted average of velocity and Equaiton 12,13 of each value from TABLE-3, we get value of V as $V = 1375 \pm 12 \text{ m/sec}$; From Equation-4,10 we get the bulk modulus as $\beta = 1.88 \pm 0.03 \text{ GPa}$ and finally from Equation-5,11 we get the compressiblity as $K = 53.67 \pm 0.08 \times 10^{-6} \text{ atm}$. We will compare this values with the theoratical values in Appendix-A.

REFERENCES

- L. M. Cat, Ph3244 3rd year sem 6 physics lab repo: <https://github.com/laughingcatmeme/ph3244> (2026).
G. M. Tewari, Measurement uncertainty, International Workshop and Training Program on Good Food Laboratory Practices (2016).
J. R. Taylor, *An Introduction to Error Analysis* (1997).
Standard error, Wikipedia (2026).

Appendix A: Theoretical values and comparison

The theoretical value for bulk modulus of water at 20°C is around 2.2 GPa, this is 16% different from the calculated while the uncertainty being only 1%. The reason for this are the systematic errors discussed in the error analysis section.

Appendix B: Improvements in procedure

We can measure the D on a fluorescent paper in dark room which will make the readings a lot easier and accurate. Furthermore we can calculate the D at very large L this will make the relative uncertainty of D small and thus giving more accurate readings. For the random error, we can take more readings to reduce them.