

What is tidy data?

RESHAPING DATA WITH TIDYR



Jeroen Boeye

Machine Learning Engineer, Faktion

Happy families are all alike, but every unhappy family is unhappy in its own way.

Leo Tolstoy

Tidy datasets are all alike, but every messy dataset is messy in its own way.

Hadley Wickham

Rectangular data

Structure

- Columns
- Rows
- Cells


name	homeworld	species
Luke Skywalker	Tatooine	Human
R2-D2	Naboo	Droid
Darth Vader	Tatooine	Human
Obi-Wan Kenobi	Stewjon	Human

Tidy data, variables

Structure

- **Columns hold variables**
- Rows
- Cells

name	homeworld	species
Luke Skywalker	Tatooine	Human
R2-D2	Naboo	Droid
Darth Vader	Tatooine	Human
Obi-Wan Kenobi	Stewjon	Human



Tidy data, observations

Structure

- Columns hold variables
- **Rows hold observations**
- Cells

name	homeworld	species
Luke Skywalker	Tatooine	Human
R2-D2	Naboo	Droid
Earth Vader	Tatooine	Human
Obi Wan Kenobi	Stewjon	Human

Tidy data, values

Structure

- Columns hold variables
- Rows hold observations
- **Cells hold values**

name	homeworld	species
Luke Skywalker	Tatooine	Human
R2-D2	Naboo	Droid
Darth Vader	Tatooine	Human
Obi-Wan Kenobi	Stewjon	Human

dplyr recap

```
character_df
```

```
# A tibble: 4 x 3
  name          homeworld species
  <chr>         <chr>      <chr>
1 Luke Skywalker Tatooine   Human
2 R2-D2         Naboo      Droid
3 Darth Vader   Tatooine   Human
4 Obi-Wan Kenobi Stewjon    Human
```

dplyr recap: select()

```
character_df %>%  
  select(name, homeworld)
```

```
# A tibble: 4 x 2  
  name          homeworld  
  <chr>         <chr>  
1 Luke Skywalker Tatooine  
2 R2-D2         Naboo  
3 Darth Vader   Tatooine  
4 Obi-Wan Kenobi Stewjon
```


dplyr recap: filter()

```
character_df %>%  
  filter(homeworld == "Tatooine")
```

```
# A tibble: 2 x 3  
  name          homeworld species  
  <chr>         <chr>    <chr>  
1 Luke Skywalker Tatooine  Human  
2 Darth Vader   Tatooine  Human
```

dplyr recap: mutate()

```
character_df %>%  
  mutate(is_human = species == "Human")
```

```
# A tibble: 4 x 4  
  name          homeworld species is_human  
  <chr>         <chr>    <chr>   <lgl>  
1 Luke Skywalker Tatooine   Human   TRUE  
2 R2-D2          Naboo     Droid   FALSE  
3 Darth Vader    Tatooine   Human   TRUE  
4 Obi-Wan Kenobi Stewjon   Human   TRUE
```

dplyr recap: group_by() and summarize()

```
character_df %>%  
  group_by(homeworld) %>%  
  summarize(n = n())
```

```
# A tibble: 3 x 2  
  homeworld      n  
  <chr>      <int>  
1 Naboo        1  
2 Stewjon      1  
3 Tatooine     2
```



¹ magrittr.tidyverse.org



¹ www.tidyverse.org

Multiple variables in a single column

```
population_df
```

```
# A tibble: 4 x 2
  country                population
  <chr>                  <dbl>
1 Brazil, South America 210.
2 Nepal, Asia           28.1
3 Senegal, Africa       15.8
4 Australia, Oceania    25.0
```

Separating variables over two columns

```
population_df %>%  
  separate(country, into = c("country", "continent"), sep = ", ")
```

```
# A tibble: 4 x 3  
  country    continent    population  
  <chr>      <chr>          <dbl>  
1 Brazil    South America    210.  
2 Nepal     Asia             28.1  
3 Senegal   Africa           15.8  
4 Australia Oceania          25.0
```

Columns with multiple values

RESHAPING DATA WITH TIDYR



Jeroen Boeye

Machine Learning Engineer, Faktion

Two variables in a single column

```
netflix_df
```

```
# A tibble: 637 x 3
```

	title	type	duration
	<chr>	<chr>	<chr>
1	Article 15	Movie	125 min
2	Kill Me If You Dare	Movie	100 min
3	The Spy	TV Show	1 Seasons
4	The World We Make	Movie	108 min
5	Watchman	Movie	93 min

Converting separated columns' data types

```
netflix_df %>%  
  separate(duration, into = c("value", "unit"), sep = ",", convert = TRUE)
```

```
# A tibble: 5 x 4  
  title                type    value unit  
  <chr>                <chr>  <int> <chr>  
1 Article 15          Movie    125 min  
2 Kill Me If You Dare Movie    100 min  
3 The Spy            TV Show     1 Seasons  
4 The World We Make   Movie    108 min  
5 Watchman            Movie     93 min
```

dplyr aggregation recap

```
netflix_df%>%  
  separate(duration, into = c("value", "unit"), convert = TRUE) %>%  
  group_by(type, unit) %>%  
  summarize(mean_duration = mean(value))
```

```
# A tibble: 2 x 3  
# Groups:   type [2]  
  type      unit  mean_duration  
  <chr>   <chr>         <dbl>  
1 Movie   min           98.6  
2 TV Show Seasons      1.85
```

Separating variables over columns

title	type	duration

title	type	value	unit

Combining multiple columns into one

```
star_wars_df
```

```
# A tibble: 4 x 2
  given_name family_name
  <chr>      <chr>
1 Luke      Skywalker
2 Han       Solo
3 Leia      Organa
4 R2        D2
```

Combining multiple columns into one

```
star_wars_df %>%  
  unite("name", given_name, family_name)
```

```
# A tibble: 4 x 1  
  name  
  <chr>  
1 Luke_Skywalker  
2 Han_Solo  
3 Leia_Organa  
4 R2_D2
```

Combining multiple columns into one

```
star_wars_df %>%  
  unite("name", given_name, family_name, sep = " ")
```

```
# A tibble: 4 x 1  
  name  
  <chr>  
1 Luke Skywalker  
2 Han Solo  
3 Leia Organa  
4 R2 D2
```

Multiple values in a single cell

```
drink_df
```

```
# A tibble: 2 x 2
  drink      ingredients
  <chr>      <chr>
1 Chocolate milk milk, chocolate, sugar
2 Orange juice oranges, sugar
```


Multiple values in a single cell

Netflix data

title	type	duration

Drinks data

drink	ingredients		
A	1	2	3
B	1	2	

Multiple values in a single cell

Netflix data

title	type	duration

Values to variables

title	type	value	unit

Drinks data

drink	ingredients		
A	1	2	3
B	1	2	

Multiple values in a single cell

Netflix data

title	type	duration

Values to variables

title	type	value	unit

Drinks data

drink	ingredients		
A	1	2	3
B	1	2	

Values to observations

drink	ingredients
A	1
A	2
A	3
B	1
B	2

Separating values over rows

```
drink_df %>%  
  separate_rows(ingredients, sep = ", ")
```

```
# A tibble: 5 x 2  
  drink      ingredients  
  <chr>      <chr>  
1 Chocolate milk milk  
2 Chocolate milk chocolate  
3 Chocolate milk sugar  
4 Orange juice oranges  
5 Orange juice sugar
```

Counting ingredients

```
drink_df %>%  
  separate_rows(ingredients, sep = ", ") %>%  
  count(drink)
```


```
# A tibble: 2 x 2  
  drink      n  
  <chr>    <int>  
1 Chocolate milk    3  
2 Orange juice     2
```

```
drink_df %>%  
  separate_rows(ingredients, sep = ", ") %>%  
  count(ingredients)
```

```
# A tibble: 4 x 2  
  ingredients      n  
  <chr>          <int>  
1 chocolate      1  
2 milk           1  
3 oranges        1  
4 sugar          2
```

Visualizing ingredients

```
drink_df %>%  
  separate_rows(ingredients, sep = ", ") %>%  
  ggplot(aes(x=drink, fill=ingredients)) +  
  geom_bar()
```



Missing values

RESHAPING DATA WITH TIDYR



Jeroen Boeye

Machine Learning Engineer, Faktion

Missing values in R

NA = Not Available

```
# A tibble: 5 x 4
  drink      ingredient quantity unit
<chr>      <chr>          <int> <chr>
1 Chocolate milk    milk           1 L
2 Chocolate milk    chocolate      100 g
3 Chocolate milk    sugar          20 g
4 Orange juice     oranges         3 NA
5 Orange juice     sugar          20 g
```


Imputing with a default value: `replace_na()`

```
moon_df
```

```
# A tibble: 4 x 2
  year people_on_moon
<int>      <int>
1  1969          4
2  1970         NA
3  1971          4
4  1972          4
5  1973         NA
```

Imputing with a default value: `replace_na()`

```
moon_df %>%  
  replace_na(list(people_on_moon = 0L))
```

```
# A tibble: 4 x 2  
  year people_on_moon  
  <int>         <int>  
1  1969             4  
2  1970             0  
3  1971             4  
4  1972             4  
5  1973             0
```

```
typeof(0L)
```

```
[1] "integer"
```

```
typeof(0)
```

```
[1] "double"
```

Imputing with the most recent value: fill()

```
cumul_moon_df
```

```
# A tibble: 5 x 3
  year people_on_moon total_people_on_moon
  <int>         <int>         <int>
1  1969             4             4
2  1970            NA            NA
3  1971             4             8
4  1972             4            12
5  1973            NA            NA
```

Imputing with the most recent value: fill()

```
cumul_moon_df %>%  
  fill(total_people_on_moon)
```

```
# A tibble: 5 x 3  
  year people_on_moon total_people_on_moon  
  <int>         <int>          <int>  
1  1969             4             4  
2  1970            NA             4  
3  1971             4             8  
4  1972             4            12  
5  1973            NA            12
```

fill() imputation options

```
cumul_moon_df %>%  
  fill(total_people_on_moon, .direction = "down")
```

```
# A tibble: 5 x 3  
  year people_on_moon total_people_on_moon  
  <int>         <int>         <int>  
1  1969             4             4  
2  1970            NA             4  
3  1971             4             8  
4  1972             4            12  
5  1973            NA            12
```

fill() imputation options

```
cumul_moon_df %>%  
  fill(total_people_on_moon, .direction = "up")
```

```
# A tibble: 5 x 3  
  year people_on_moon cumul_people_on_moon  
  <int>         <int>         <int>  
1  1969             4             4  
2  1970            NA             8  
3  1971             4             8  
4  1972             4            12  
5  1973            NA            NA
```

Removing rows with missing values: drop_na()

```
moon_df %>%  
  drop_na()
```

```
# A tibble: 3 x 2  
  year people_on_moon  
  <int>         <int>  
1  1969             4  
2  1971             4  
3  1972             4
```

drop_na() caveats

```
mars_df
```

```
# A tibble: 5 x 3
  year people_on_moon people_on_mars
<int>         <int> <int>
1  1969             4 NA
2  1970            NA NA
3  1971             4 NA
4  1972             4 NA
5  1973            NA NA
```


drop_na() caveats

```
mars_df %>%  
  drop_na()
```

```
# A tibble: 0 x 3  
# ... with 3 variables: year <int>, people_on_moon <int>, people_on_mars <int>
```

drop_na() caveats

```
mars_df %>%  
  drop_na(people_on_moon)
```

```
# A tibble: 3 x 3  
  year people_on_moon people_on_mars  
  <int>         <int> <int>  
1  1969             4 NA  
2  1971             4 NA  
3  1972             4 NA
```