

# 3. The C in C++

Hu Sikang  
skhu@163.com

School of Computer  
Beijing Institute of Technology

# Content

- **Operators**
- **Build\_in type**
- **Variables**
- **Scoping**
- **Array**
- **Const**
- **Cast**
- **Function and function pointer**

## 3.1 Creating functions

## 3.2 Controlling execution

- if-else
- while
- do-while
- for *--for*
- break
- continue
- switch-case
- *goto*

## 3.2 Controlling execution

```
for (data_type var : collection_to_loop) // the 11th version of C++  
{ // Here are codes... }
```

```
#include <iostream>  
using namespace std;
```

```
int main() {  
    int array[] = {10, 23, 45, 12, 56};  
  
    for (int a : array) // a is read-only  
        cout << a << endl;  
    return 0;  
}
```

## 3.2 Controlling execution

```
for (data_type var : collection_to_loop)
{ // Here are codes... }
```

```
#include <iostream>
#include <vector>
using namespace std;
```

```
int main() {
    vector<int> v;

    for (int i = 0; i < 5; i++)
        v.push_back(i * 3);

    for (int x : v)
        cout << x << endl;
    return 0;
}
```

## 3.3 Operators

### ➤ Unary Operators

new, delete, new[ ], delete[ ],  
++, --, (), [ ], +, -, \*, &, !, ~,

### ➤ Binary operators

+, -, \*, /, %, =, +=, -=, \*=, /=, %=  
&, |, ^, ^=, &=, |=, ==, !=, >, <, >=,  
<=, ||, &&, <<, >>, >>=, <<=, ->, ->\*

### ➤ Other operators

. member selection  
.\* member selection by a pointer  
:: scope resolution  
?: ternary conditional expression  
sizeof


## **3.4 Introduction to data types**

**3.4.1 Built-in types**

**3.4.2 Pointers**

**3.4.3 references**

## 3.4.1 Built-in types





## 3.4.2 Introduction to pointers

- Every element of your program occupies storage and has an address.
- C++ have a special type of variable that holds an address. This variable is called a *pointer*.

## 3.4.3 Argument Passing

- Pass by value
- Pass by address (pointer)
- Pass by reference

# (1) Pass by value

```
#include <iostream>
using namespace std;
void f(int a)
{
    cout << "a = " << a << endl;
    a = 5;
    cout << "a = " << a << endl;
}
```

```
int main()
{
    int x = 47;
    cout << "x = " << x << endl;
    f(x);
    cout << "x = " << x << endl;
    return 0;
}
```

## (2) Pass by address

```
#include <iostream>
using namespace std;
void f(int* p)
{
    cout << "p = " << p << endl;
    cout << "*p = " << *p << endl;
    *p = 5;
    cout << "p = " << p << endl;
}
```


```
int main()
{
    int x = 47;
    cout << "x = " << x << endl;
    cout << "&x = " << &x << endl;
    f(&x);
    cout << "x = " << x << endl;
    return 0;
}
```

## (3) references

- *Pass-by-reference* is an additional way to pass an **address** into a function.
- Pass-by-reference allows a function to modify the outside object, just like passing a pointer does.
- *Calling* a function that takes references is cleaner, syntactically, than calling a function that takes pointers.
- We must *initialize* the reference except as a parameters of the function.

```
int a=3;  
int& m=a;    //ok  
int& x;       //error
```

```
int& k=m;  
int n=m;  
int* p=&m;  
m=m+5;
```



```
//: C01:PassByValue.cpp
```

```
#include <iostream>
```

```
using namespace std;
```

```
void f(int a)
```

```
{  
    cout << "a = " << a << endl;  
    a = 5;  
    cout << "a = " << a << endl;  
}
```

```
int main( )
```

```
{  
    int x = 47;  
    cout << "x = " << x << endl;  
    f(x);  
    cout << "x = " << x << endl;  
    return 0;  
} ///:~
```

```
//: C02:PassReference.cpp
```

```
#include <iostream>
```

```
using namespace std;
```

```
int f(int& a)
```

```
{  
    cout << "a = " << a << endl;  
    a = 5;  
    cout << "a = " << a << endl;  
}
```

```
int main( )
```

```
{  
    int x = 47;  
    cout << "x = " << x << endl;  
    f(x);  
    cout << "x = " << x << endl;  
    return 0;  
} ///:~
```

//: C01:PassByValue.cpp

#include <iostream>

using namespace std;

**void f(int \*a)**

```
{
    cout << "a = " << a << endl;
    a = 5;
    cout << "a = " << a << endl;
}
```

int main( )

```
{
    int x = 47;
    cout << "x = " << x << endl;
    f(&x);
    cout << "x = " << x << endl;
    return 0;
} ///:~
```

//: C02:PassReference.cpp

#include <iostream>

using namespace std;

**void f(int& a)**

```
{
    cout << "a = " << a << endl;
    a = 5;
    cout << "a = " << a << endl;
}
```

int main( )

```
{
    int x = 47;
    cout << "x = " << x << endl;
    f(x);
    cout << "x = " << x << endl;
    return 0;
} ///:~
```



## 3.5 Scoping



- The scope of a variable is defined by its “nearest” set of brace.
- A variable can be used only when inside its scope.

```
int main( )
{
    int scp1;
    // scp1 visible here
    {    // scp1 still visible here
        int scp2;
        // scp2 visible here
        {    // scp1 & scp2 still visible here
            int scp3;
            // scp1, scp2 & scp3 visible here
        } // <-- scp3 destroyed here
        // scp3 not available here
        // scp1 & scp2 still visible here
    } // <-- scp2 destroyed here
    // scp3 & scp2 not available here
    // scp1 still visible here
    return 0;
} // <-- scp1 destroyed here
```

## 3.6 Specifying storage allocation

3.6.1 Global variables

3.6.2 Local variables

3.6.3 **Static** variables

3.6.4 Extern

**3.6.5 Constants**

## 3.6.5 Constants

- `#define PI 3.14159` // *replacement. Its scope is: from #define to #undef*
- `const double PI=3.14159 ;` // *a variable*
- A **const** is just like a variable, except that its value cannot be changed.

## 3.6.5 Constants

A const must always have an initialization value except as a parameters of the function.

```
int f(int& x)
{
    return ++x; //OK
}
int g(const int& x)
{
    return ++x; //ERROR
}
```

```
#include <iostream>
using namespace std;
int main()
{
    int a = 9;
    f(a);
    g(a);
    return 0;
}
```

## 3.7 Operators and their use

### 3.7.1 Assignment

$A = 4$

- **A**: an **lvalue**, a distinct, named **variable**
- **4**: an **rvalue**, a constant, variable, or expression that can produce a **value**

## 3.7.2 Mathematical operators

- addition (+)
- subtraction (-)
- division (/)
- multiplication (\*)
- modulus (%); this produces the remainder from **integer** division.
- `x = x + 4;`    `x += 4;`

## 3.7.3 Relational operators

- less than (<), greater than (>), less than or equal to (<=), greater than or equal to (>=), equivalent (==), and not equivalent (!=).
- They produce a Boolean **true** if the relationship is true, and **false** if the relationship is false.
- If you print a **bool**, you'll typically see a '1' for **true** and '0' for **false**.



## 3.7.4 Logical operators

- *and* (&&) ; *or* (||) ; *not* (!)
- The result is **true** if it has a non-zero value, and **false** if it has a value of zero.

```
int i = 10, j = 5;  
cout << ((i == 10) && (j > 10));  
cout << ((i < 10) || (j < 10));
```

## 3.7.5 Bitwise operators

- bitwise *and* (&)
- bitwise or (|)
- bitwise *not* / *complement* (~)
- bitwise *exclusive or* / *xor* (^)
- &=; |=; ^=

## 3.7.6 Shift operators

- left-shift (<<)
- right-shift (>>)
- <<= ; >>=

1, 16, 1, 8

```
#include <iostream>
using namespace std;
int main()
{
    unsigned int a=1;
    cout<<a<<',';
    unsigned int b=a<<4;
    cout<<b<<','<<a<<',';
    a=b>>1;
    cout<<a<<endl;
    return 0;
} ///:~
```

## 3.7.7 Unary operators

- Bitwise *not* ( $\sim$ )
- *logical not* (!)
- unary minus (-) ; unary plus (+)
- increment (++); decrement (--)
- address-of (&)
- dereference (\* and ->)
- **cast**
- **new ; delete**


## 3.7.8 The ternary operator

- $c = a > b ? a : b$
- ```
if (a > b) c = a;  
else      c = b;
```

## 3.7.9 The comma operator

## 3.7.11 Casting operators

- The compiler will automatically change one type of data into another if it makes sense.



## 3.7.12 sizeof– an operator

```
int main()
{
    cout<<"bool:"<<sizeof(bool)<<endl;
    cout<<"char:"<<sizeof(char)<<endl;
    cout<<"int:" <<sizeof(int)<<endl;
    cout<<"float:"<<sizeof(float)<<endl;
    cout<<"double:"<<sizeof(double)<<endl;
    cout<<"long double:"<<sizeof(long double)<<endl;
    return 0;
}
```

bool:1  
char:1  
int:4  
float:4  
double:8  
long double:8

The results may be *vary* with different machines/operating systems/compilers.

## 3.8 Composite type creation

- C++ provide tools that allow you to compose more sophisticated data types from the fundamental data types.
- The most important of these is **struct**, which is the foundation for **class** in C++.
- the simplest way to create more sophisticated types is simply to alias a name to another name via **typedef**.



## 3.8.1 Clarifying programs with enum

- An *enumeration* is a type that can hold a set of values specified by the user.

*enum* keyword {*ASM*, *AUTO*, *BREAK*};

- By *default*, the values of enumerators are initialized increasing from 0;

*ASM*=0, *AUTO*=1, *BREAK*=2;

*BREAK*==6

- An enumerator can be initialized by a *constant-expression* of integer type.

*enum* keyword {*ASM*=2, *AUTO*=5, *BREAK*};

## 3.9 Pointers and arrays

- The name of an array can be used as a *pointer to its initial elements*.
- Access array can be achieved either through a pointer to an array plus an index or through a pointer to an element.
- **Notion:** Most C++ implementations offer *no range checking* for arrays.

## 3.10 Function addresses

- Once a function is compiled and loaded into the computer to be executed, it occupies a chunk of memory, and has an address.
- You can use function addresses with pointers just as you can use variable addresses.

## 3.10.1 Defining a function pointer

`void (*funcPtr)();`

- **funcPtr** is a pointer to a function that has no arguments and no return value.
- **void\* funcPtr ();**
- **funcPtr** is a function that returns a void\* .

// Defining and using a pointer to a function

```
#include <iostream>
```

```
using namespace std;
```

```
void func()
```

```
{
```

```
    cout << "func() called..." << endl;
```

```
}
```

```
int main()
```

```
{
```

```
    void (*fp)( );
```

```
// Declare a function pointer
```

```
    fp = func;
```

```
// Initialize it
```

```
    (*fp)( );
```

```
// Call the function
```

```
    void (*fp2)( ) = func;
```

```
// Define and initialize
```

```
    (*fp2)( );
```

```
// Call the function
```

```
    return 0;
```

```
}
```

## 3.10.2 Call Function with Function Pointer

```
#include <iostream>
#include <tchar.h>
#include <windows.h>
using namespace std;
typedef int (*CallFunction) (int a, int b);
int main(void) {
    HINSTANCE hDLL;
    CallFunction JIA;
    hDLL = LoadLibrary(_T("MyDll.dll")); // _T: ANSI or Unicode
    if (hDLL == nullptr)
    {
        cout << "NULL" << endl;
        return 0;
    }
    // loading Dynamatic Link Libaray
    JIA = (CallFunction)GetProcAddress(hDLL, "Add");
    cout << (*JIA)(10, 20) << endl;
    FreeLibrary(hDLL);
    return 0;
}
```

**// unload DLL file**

# Summary

- **Operators**
- **Build\_in type**
- **Variables**
- **Scoping**
- **Array**
- **Const**
- **cast**
- **Function and function pointer**