


Distribution of **all** interactions ($\mathbf{A}^{(m),+}$, $\mathbf{A}^{(m),-}$)

$\mathcal{R} = \# \text{ samples (target DNN)} : \# \text{ samples (baseline DNN)}$


= Distribution of **Generalizable** interactions

+ Distribution of **Non-generalizable** interactions


A pair of (target DNN & baseline DNN)
trained by setting $\mathcal{R} = 1:2$




A pair of (target DNN & baseline DNN)
trained by setting $\mathcal{R} = 1:1$




A pair of (target DNN & baseline DNN)
trained by setting $\mathcal{R} = 2:1$




$k = 1$




$k = 3$




$k = 5$




$k = 1$




$k = 3$




$k = 5$




$k = 1$




$k = 3$




$k = 5$




$k = 1$




$k = 3$




$k = 5$




$k = 1$




$k = 3$




$k = 5$




$k = 1$



$k = 3$



$k = 5$



Caption: Ablation study on different training split ratios using CIFAR-10 and VGG11. $\mathcal{R}$ denotes the ratio of the number of samples used to train the target DNN to that used to train the baseline DNN. Across various $\mathcal{R}$, the generalizable interactions converge to decay-shaped, while the non-generalizable interactions converge to spindle-shaped. This conclusion is consistent with the results reported in our paper.