

LD4B-1510-DFB-2.5G-15-TEC

OVERVIEW

Laser diode with an integrated TEC and thermistor coupled to an optical fiber and packaged into a hermetic case.

MAIN FEATURES

- Wavelength: 1510 nm
- Cavity type: DFB
- Bandwidth: 2.5 GHz
- Optical power in CW mode in single-mode fiber: 15 mW
- Package type: coaxial with bracket
- Built-in monitor photodiode
- Built-in TEC and thermistor

ORDERING INFORMATION

LD4B-1510-DFB-2.5G-15-TEC-X-X-X-X-X-X

Case type

COAXB: compact coaxial with a bracket (TEC and thermistor)

Pinout code

27: see more details on page 5

Fiber type

SM1: SM, G.657.A1, [Corning SMF-28 Ultra](#), furcation tubing Ø0.9 mm or **BSM1** Ø0.25mm

SM3: SM, G.657.B3, [Corning ClearCurve ZBL](#), furcation tubing Ø0.9 mm or **BSM3** Ø0.25mm

SMP13: PM, [Corning PM1300](#), PANDA type, furcation tubing Ø0.9 mm

Other type on request

Connector type

FU: FC/UPC (SM1, SM3)

FA: FC/APC (SM1, SM3, SMP13)

SU: SC/UPC (SM1)

SA: SC/APC (SM1)

N: no connector (scissors cut)

Other type: on request

Test measurements

CW: CW mode (electro-optical parameters at T=25+/-5 C and spectrum)

P: Pulse mode (pulse duration 5 us, duty cycle 0.5%, at T=25+/-5 C)

CWP: both CW and pulse mode

Fiber length

0.5: 500+/-50 mm

1.0: 1000+/-100 mm

Other length on request

LD4B-1510-DFB-2.5G-15-TEC

ABSOLUTE MAXIMUM RATINGS





Parameter		Value	Unit	Conditions
Laser diode CW forward current	I _{max}	100	mA	CW, T = 40°C
Laser diode reverse voltage	V _{RL}	2	V	
Photodiode reverse voltage	V _{RP}	15	V	
Photodiode forward current	I _{RP}	5	mA	
Operating temperature*	T _{op}	-15 - +60	°C	Ambient (heat sink)
Storage temperature	T _{stg}	-40 - +85	°C	
Soldering temperature	T _{sold}	260	°C	Max. 5 seconds


*Operating temperature is defined for internal temperature stabilization at T_{st} = 25°C that corresponds to thermistor resistance R_t = 10 kOhm.

It is necessary to ensure sufficient heat dissipation so that the module's maximum operating temperature is not exceeded.

LD4B-1510-DFB-2.5G-15-TEC**ELECTRICAL-OPTICAL CHARACTERISTICS (T = 25 °C)**

Parameter		MIN	TYP	MAX	Unit	Conditions
Optical power (CW)	P _{CW}	15	18		mW	CW, I _{op} = 100 mA, T = 40°C
Mean wavelength	λ	1507	1510	1513	nm	CW, I _{op} = 100 mA, T = 40°C
Spectral width	Δλ		0.1		nm	CW, I _{op} = 100 mA, OSA, -20 dB
Wavelength-temperature coefficient	dλ/dT		0.1		nm/°C	
Side-mode suppression ratio	SMSR	40	55		dB	CW, I _{op} = 50 mA, T = 40°C
Threshold current	I _{th}		14	20	mA	CW
Slope efficiency	S _e	0.17	0.22		mW/mA	CW, SM1
Operating voltage	V _{op}		1.8	2.5	V	CW, I _{op} = 100 mA, T = 40°C
Monitor current	I _m	0.1	0.5	3	mA	CW, I _{op} = 100 mA, V _r = 5 V, T = 40°C
TEC voltage	V _{TEC}			1.1	V	I _{op} = 100 mA
TEC current	I _{TEC}			1.2	A	I _{op} = 100 mA
Thermistor resistance	R _{th}	9.5	10	10.5	kΩ	T = 25°C
Thermistor B constant	B	3800	3900	4000	k	
TEC set point temperature	T _{sp}		40		°C	
Polarization extinction ratio	PER	20			dB	CW, SMP13
Bandwidth	BW		2.5		GHz	

LD4B-1510-DFB-2.5G-15-TEC


LD4B-1510-DFB-2.5G-15-TEC

COAXB

BACK VIEW

PINOUT

#27



1. LD Cathode (-)/
Gnd/Thermistor
2. LD Anode (+)
3. PD Cathode (+)
4. TEC (-)
5. TEC (+)
6. PD Anode (-)
7. Thermistor

TEC: $I_{max} = 1.2 \text{ A}$, $V_{max} = 1.1 \text{ V}$
Thermistor: $R(25^\circ\text{C}) = 10 \text{ k}\Omega$, $B = 3900 \text{ K}$

Download more
information



Drawing



3D model



Application Notes

LD4B-1510-DFB-2.5G-15-TEC

Characteristics, data, materials and structures specified in this datasheet are subject to change without notice. Please refer to the latest specification before use of the products.

Safety and handling cautions

1. Avoid smashing and burning of the module. Avoid storing and using the module in conditions where water, organic solvents or aggressive acids or bases may contact the module or where there is a possibility of exposure to corrosive gases, explosive gases, dust, salinity or other harsh conditions. The module should be disposed as special industrial waste.
2. Exceeding absolute maximum ratings even for a short time can cause permanent damage of the module.
3. The module is sensitive to and can be broken by ESD (static electricity).

Conflict Minerals Policy Statement

LD4B achieves business objectives and customer needs with social responsibility. We do not support or contribute to the violence and human rights violations associated with the mining of conflict minerals coming from Conflict Regions according to US "Dodd-Frank Act". When possible, our suppliers' conflict mineral statements are reviewed. We do not directly purchase Conflict Minerals from any source and do not knowingly procure any parts and products containing Conflict Minerals from Conflict Regions.

RoHS Compliance Statement

Restriction of Hazardous Substances (RoHS) directive (Directive 2011/65/EC amended with Directive (EU) 2015/863) is the directive aimed at reducing the harmful environmental impact of waste electrical equipment by restricting the use of known dangerous substances. Based on information received from our supply sources, LD4B hereby states that the banned substances listed in the RoHS directive are not found in the parts and materials used above the threshold level listed other than exceptions approved by the European Commission.

REACH Compliance Statement

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) is a European Union regulation 1907/2006/EC that addresses the production and use of chemical substances, and their potential impacts on human health and the environment. Based on information received from our supply sources, LD4B hereby states compliance of the parts and materials used in manufacturing to REACH regulation. LD4B does not manufacture or import any substances or preparations as defined under REACH.