

원핫 인코딩 실습

학습 내용

- 기본 one-hot encoding 실습
- hello world 실습

01. 기본 실습 - One-hot encoding

간단한 데이터를 준비하여, 목표 feature인 'target'를 labelencode 후, 이 후, 결과값을 이용하여 one-hot-encoding를 수행한다.

In [16]:



```
### 01. 데이터 준비
import pandas as pd
data = { "feature1": [2,3,8,4],
         "feature2": [22,32,82,42],
         "target": ["b", "c", "a", "d"]
        }
df = pd.DataFrame(data)
df
```

Out[16]:

	feature1	feature2	target
0	2	22	b
1	3	32	c
2	8	82	a
3	4	42	d

In [17]:



```
from sklearn import preprocessing
```

In [18]:



```
label_encoder = preprocessing.LabelEncoder()  
df['lbl_en'] = label_encoder.fit_transform(df['target'])  
df
```

Out[18]:

	feature1	feature2	target	lbl_en
0	2	22	b	1
1	3	32	c	2
2	8	82	a	0
3	4	42	d	3

In [19]:



```
train_y = df['lbl_en'].values.reshape(len(df), 1)  
train_y
```

Out[19]:

```
array([[1],  
       [2],  
       [0],  
       [3]])
```

In [20]:



```
onehot_encoder = preprocessing.OneHotEncoder(sparse=False)  
train_y_onehot = onehot_encoder.fit_transform(train_y)  
print(train_y_onehot)  
print(train_y_onehot.shape)
```

```
[[0. 1. 0. 0.]  
 [0. 0. 1. 0.]  
 [1. 0. 0. 0.]  
 [0. 0. 0. 1.]]  
(4, 4)
```

In [21]:



```
onehot_val = pd.DataFrame(train_y_onehot, dtype=int)  
df_new = pd.concat([df, onehot_val], axis=1)  
df_new
```

Out[21]:

	feature1	feature2	target	lbl_en	0	1	2	3
0	2	22	b	1	0	1	0	0
1	3	32	c	2	0	0	1	0
2	8	82	a	0	1	0	0	0
3	4	42	d	3	0	0	0	1

02. 사계절 원핫 인코딩

In [28]:



```
from numpy import array
from numpy import argmax
from sklearn.preprocessing import LabelEncoder
from sklearn.preprocessing import OneHotEncoder

data = ['spring', 'spring', 'summer', 'spring', 'autumn',
        'autumn', 'winter', 'spring', 'summer', 'autumn']
values = array(data)
print(values)

# integer encode
label_encoder = LabelEncoder()
label_encoded = label_encoder.fit_transform(values)
print(label_encoded)

# binary encode
onehot_encoder = OneHotEncoder(sparse=False)
lbl_encoded = label_encoded.reshape(len(integer_encoded), 1)
onehot_encoded = onehot_encoder.fit_transform(lbl_encoded)
print(onehot_encoded)

# LabelEncoder에 입력하여 역변환 4번째 행의 값을 되돌리기
inverted = label_encoder.inverse_transform([argmax(onehot_encoded[4, :])])
print(inverted)
```

```
['spring' 'spring' 'summer' 'spring' 'autumn' 'autumn' 'winter' 'spring'
 'summer' 'autumn']
[1 1 2 1 0 0 3 1 2 0]
[[0. 1. 0. 0.]
 [0. 1. 0. 0.]
 [0. 0. 1. 0.]
 [0. 1. 0. 0.]
 [1. 0. 0. 0.]
 [1. 0. 0. 0.]
 [0. 0. 0. 1.]
 [0. 1. 0. 0.]
 [0. 0. 1. 0.]
 [1. 0. 0. 0.]]
['autumn']
```

In [30]:



```
df = pd.DataFrame({"season":data, "lbl_season":label_encoded }, dtype=int)
onehot_val = pd.DataFrame(onehot_encoded, dtype=int)
onehot_val
df_new = pd.concat([df, onehot_val], axis=1)
df_new
```

Out[30]:

	season	lbl_season	0	1	2	3
0	spring	1	0	1	0	0
1	spring	1	0	1	0	0
2	summer	2	0	0	1	0
3	spring	1	0	1	0	0
4	autumn	0	1	0	0	0
5	autumn	0	1	0	0	0
6	winter	3	0	0	0	1
7	spring	1	0	1	0	0
8	summer	2	0	0	1	0
9	autumn	0	1	0	0	0

03. 'hello world'를 원핫인코딩하기

In [2]:



```
import numpy as np
from numpy import argmax
# define input string
data = 'hello world'
print(data)
```

hello world

In [3]:



```
# define universe of possible input values
alphabet = 'abcdefghijklmnopqrstuvwxyz '
# define a mapping of chars to integers
char_to_int = dict((c, i) for i, c in enumerate(alphabet))
int_to_char = dict((i, c) for i, c in enumerate(alphabet))

print("char_to_int : ", char_to_int)
print()
print("int_to_char : ", char_to_int)
```

```
char_to_int : {'a': 0, 'b': 1, 'c': 2, 'd': 3, 'e': 4, 'f': 5, 'g': 6, 'h': 7, 'i': 8, 'j': 9, 'k': 10, 'l': 11, 'm': 12, 'n': 13, 'o': 14, 'p': 15, 'q': 16, 'r': 17, 's': 18, 't': 19, 'u': 20, 'v': 21, 'w': 22, 'x': 23, 'y': 24, 'z': 25, ' ': 26}
```

```
int_to_char : {'a': 0, 'b': 1, 'c': 2, 'd': 3, 'e': 4, 'f': 5, 'g': 6, 'h': 7, 'i': 8, 'j': 9, 'k': 10, 'l': 11, 'm': 12, 'n': 13, 'o': 14, 'p': 15, 'q': 16, 'r': 17, 's': 18, 't': 19, 'u': 20, 'v': 21, 'w': 22, 'x': 23, 'y': 24, 'z': 25, ' ': 26}
```

In [4]:



```
# integer encode input data
integer_encoded = [char_to_int[char] for char in data]
print(integer_encoded)
```

```
[7, 4, 11, 11, 14, 26, 22, 14, 17, 11, 3]
```

In [5]:



```
# one hot encode
onehot_encoded = list()
for value in integer_encoded:
    letter = [0 for _ in range(len(alphabet))]
    letter[value] = 1
    onehot_encoded.append(letter)

print(onehot_encoded)
```

```
[[0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]]
```

In [6]:



```
# invert encoding
inverted = int_to_char[argmax(onehot_encoded[0])]
print(inverted)
```

