> 🛠️ **2026.10 수정본 (v11)** — 원본: common_p01_firstmodel-v10.ipynb
>
> 캐글 노트북이면 `/kaggle/input/bike-sharing-demand/` 를, 그 밖(코랩·내 PC)에서는 저장소의 `bike/` 폴더를 읽도록 경로를 나눴어요.

In [1]:
```
# This Python 3 environment comes with many helpful analytics libraries inst
# It is defined by the kaggle/python docker image: https://github.com/kaggle
# For example, here's several helpful packages to load in

import numpy as np # linear algebra
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)

# Input data files are available in the "../input/" directory.
# For example, running this (by clicking run or pressing Shift+Enter) will l

import os
for dirname, _, filenames in os.walk('/kaggle/input'):
    for filename in filenames:
        print(os.path.join(dirname, filename))

# Any results you write to the current directory are saved as output.
```

In [2]:
```
# 2026.10 수정: 캐글이면 /kaggle/input 경로, 아니면(코랩·내 PC) bike/ 폴더를 사용
import os
DATA_DIR = "/kaggle/input/bike-sharing-demand/"
if not os.path.exists(DATA_DIR):
    DATA_DIR = "bike/"

train = pd.read_csv(DATA_DIR + "train.csv")
test = pd.read_csv(DATA_DIR + "test.csv")
sub = pd.read_csv(DATA_DIR + "sampleSubmission.csv")
```

In [3]:
```
print(train.shape)
print(test.shape)
print(sub.shape)
```

```
(10886, 12)
(6493, 9)
(6493, 2)
```

In [4]:
```
f_names = ['temp', 'atemp']
X_train = train[f_names]    # 학습용 데이터의 변수 선택
X_test = test[f_names]      # 테스트 데이터의 변수 선택
```

In [5]:
```
label_name = 'count'         # 렌탈 대수 (종속변수)
y_train = train[label_name] # 렌탈 대수 변수 값 선택
```

In [6]:
```
from sklearn.linear_model import LinearRegression
```

In [7]:
```
model = LinearRegression()
model.fit(X_train, y_train)
```

```
model.predict(X_test)   # 예측(새로운 데이터로)
```

Out[7]:
```
array([101.95625474, 104.0156171 , 104.0156171 , ..., 103.33067499,
       104.0156171 , 104.0156171 ], shape=(6493,))
```

In [8]:
```
model.coef_
```

Out[8]:
```
array([8.19865874, 0.90720808])
```

In [9]:
```
model.intercept_
```

Out[9]:
```
np.float64(4.248132645803537)
```

In [10]:
```
pred = model.predict(X_test)   # 예측
sub['count'] = pred
```

In [11]:
```
# 처음 만는 제출용 csv 파일, 행번호를 없애기
sub.to_csv("firstsubmission.csv", index=False)
```

In [ ]:
```

```