

01 라이브러리 불러오기

02 데이터 불러오기

03 데이터 전처리

범주형으로 변환

파생변수 생성

03 데이터 전처리

결측치 처리

04 데이터 나누기

05 데이터 모델 만들기

05 데이터 모델 학습 후, 예측

05 데이터 모델 학습 후, 예측, 모델 평가

06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델

06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델  
예측

06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델

07 가장 좋은 모델로 최종 예측

예측

제출

# Rproject02B\_Titanic

## 01 라이브러리 불러오기

- dplyr : 데이터 처리
- caret : 모델 평가
- rpart : 의사결정트리
- randomForest : 랜덤 포레스트(앙상블)

```
library(dplyr)
```

```
##  
## Attaching package: 'dplyr'
```

```
## The following objects are masked from 'package:stats':  
##  
## filter, lag
```

```
## The following objects are masked from 'package:base':  
##  
## intersect, setdiff, setequal, union
```

```
library(caret)
```

```
## Loading required package: lattice
```

```
## Loading required package: ggplot2
```

```
library(rpart)  
library(randomForest)
```

```
## randomForest 4.6-14
```

```
## Type rfNews() to see new features/changes/bug fixes.
```

```
##  
## Attaching package: 'randomForest'
```

```
## The following object is masked from 'package:ggplot2':  
##  
## margin
```

```
## The following object is masked from 'package:dplyr':  
##  
## combine
```

```
set.seed(1004)
```

## 02 데이터 불러오기

```
train <- read.csv("./R_Data/titanic_train.csv", stringsAsFactors=F, na.strings = c(  
  "", "NA"))  
test <- read.csv("./R_Data/titanic_test.csv", stringsAsFactors=F, na.strings = c("",  
  "NA"))  
sub <- read.csv("./R_Data/sample_submission.csv", stringsAsFactors=F)
```

## 03 데이터 전처리

- 학습용 데이터, 테스트 데이터를 하나로 만들어 처리.

```
test$Survived <- NA  
all <- rbind(train, test)  
colSums(is.na(all))
```

##	PassengerId	Survived	Pclass	Name	Sex	Age
##	0	418	0	0	0	263
##	SibSp	Parch	Ticket	Fare	Cabin	Embarked
##	0	0	0	1	1014	2

## 범주형으로 변환

- 성별(Sex)
- 생존 유무(Survived)
- 등급(Pclass)

```
all$Sex <- as.factor(all$Sex)
all$Survived <- as.factor(all$Survived)
all$Pclass <- as.ordered(all$Pclass)
str(all)
```

```
## 'data.frame': 1309 obs. of 12 variables:
## $ PassengerId: int 1 2 3 4 5 6 7 8 9 10 ...
## $ Survived : Factor w/ 2 levels "0","1": 1 2 2 2 1 1 1 1 2 2 ...
## $ Pclass : Ord.factor w/ 3 levels "1"<"2"<"3": 3 1 3 1 3 3 1 3 3 2 ...
## $ Name : chr "Braund, Mr. Owen Harris" "Cumings, Mrs. John Bradley (Floren
ce Briggs Thayer)" "Heikkinen, Miss. Laina" "Futrelle, Mrs. Jacques Heath (Lily May P
eel)" ...
## $ Sex : Factor w/ 2 levels "female","male": 2 1 1 1 2 2 2 2 1 1 ...
## $ Age : num 22 38 26 35 35 NA 54 2 27 14 ...
## $ SibSp : int 1 1 0 1 0 0 0 3 0 1 ...
## $ Parch : int 0 0 0 0 0 0 0 1 2 0 ...
## $ Ticket : chr "A/5 21171" "PC 17599" "STON/O2. 3101282" "113803" ...
## $ Fare : num 7.25 71.28 7.92 53.1 8.05 ...
## $ Cabin : chr NA "C85" NA "C123" ...
## $ Embarked : chr "S" "C" "S" "S" ...
```

## 파생변수 생성

- Pclass와 Sex를 이용한 변수 생성

```
all$PclassSex[all$Pclass=='1' & all$Sex=='male'] <- 'P1Male'
all$PclassSex[all$Pclass=='2' & all$Sex=='male'] <- 'P2Male'
all$PclassSex[all$Pclass=='3' & all$Sex=='male'] <- 'P3Male'
all$PclassSex[all$Pclass=='1' & all$Sex=='female'] <- 'P1Female'
all$PclassSex[all$Pclass=='2' & all$Sex=='female'] <- 'P2Female'
all$PclassSex[all$Pclass=='3' & all$Sex=='female'] <- 'P3Female'
all$PclassSex <- as.factor(all$PclassSex)
names(all); table(all$PclassSex)
```

```
## [1] "PassengerId" "Survived" "Pclass" "Name" "Sex"
## [6] "Age" "SibSp" "Parch" "Ticket" "Fare"
## [11] "Cabin" "Embarked" "PclassSex"
```

```
##
## P1Female P1Male P2Female P2Male P3Female P3Male
## 144 179 106 171 216 493
```

## 결측치 확인

- ```
all[is.na(all$Fare), ]
```

```
all[is.na(all$Embarked), ]
```

```
names(all)
```

```
str(all)
```

[illegible]

```
## # A tibble: 6 x 4
##   PclassSex      n mean_age median_age
##   <fct>      <int>    <dbl>    <dbl>
## 1 P1Female    144     37.0      36
## 2 P1Male     179     41.0      42
## 3 P2Female    106     27.5      28
## 4 P2Male     171     30.8     29.5
## 5 P3Female    216     22.2      22
## 6 P3Male     493     26.0      25
```

## 결측치 처리

- 정박항은 다수의 값으로
- 나이는 등급별/성별 중앙값으로

```
all[ is.na(all$Embarked), 'Embarked'] = 'S'
all[ is.na(all$Fare), 'Fare'] = median(all$Fare,na.rm=T)

all[ is.na(all$Age) & all$PclassSex=="P1Female", 'Age'] = 36
all[ is.na(all$Age) & all$PclassSex=="P1Male", 'Age'] = 42

all[ is.na(all$Age) & all$PclassSex=="P2Female", 'Age'] = 28
all[ is.na(all$Age) & all$PclassSex=="P2Male", 'Age'] = 29.5

all[ is.na(all$Age) & all$PclassSex=="P3Female", 'Age'] = 22
all[ is.na(all$Age) & all$PclassSex=="P3Male", 'Age'] = 25

colSums(is.na(all))
```

```
## PassengerId    Survived  Pclass     Name       Sex       Age
##           0         418         0         0         0         0
##      SibSp     Parch    Ticket   Fare      Cabin Embarked
##           0         0         0         0      1014         0
##   PclassSex
##           0
```

## 04 데이터 나누기

- 학습용
- 테스트용(제출)

```
all$Embarked <- as.factor(all$Embarked)
trainClean <- all[!is.na(all$Survived),]
nrow(trainClean);
```

```
## [1] 891
```

```
# 학습용(모델학습, 모델평가)
idx <- sample(1:nrow(trainClean), size=nrow(trainClean)*0.7, replace=F)
train_tr <- trainClean[idx, ]
train_test <- trainClean[-idx, ]

# 제출용(테스트용)
testClean <- all[is.na(all$Survived),]
nrow(testClean);
```

```
## [1] 418
```

## 05 데이터 모델 만들기

- 로지스틱 회귀 모델

```
m <- glm(Survived ~ Pclass + Sex + Age + SibSp + Embarked + PclassSex, family=binomial, data=train_tr)
summary(m)
```

```
##
## Call:
## glm(formula = Survived ~ Pclass + Sex + Age + SibSp + Embarked +
##      PclassSex, family = binomial, data = train_tr)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -3.0274  -0.6052  -0.4462   0.3616   2.6610
##
## Coefficients: (3 not defined because of singularities)
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    2.84101    0.48561   5.850 4.90e-09 ***
## Pclass.L       -2.73467    0.48455  -5.644 1.66e-08 ***
## Pclass.Q        1.44228    0.42491   3.394 0.000688 ***
## Sexmale        -1.77680    0.29907  -5.941 2.83e-09 ***
## Age            -0.04938    0.01061  -4.652 3.29e-06 ***
## SibSp          -0.35612    0.12639  -2.818 0.004837 **
## EmbarkedQ       0.08404    0.44383   0.189 0.849813
## EmbarkedS      -0.33632    0.29662  -1.134 0.256865
## PclassSexP1Male -1.94436    0.71090  -2.735 0.006237 **
## PclassSexP2Female 2.95269    0.70263   4.202 2.64e-05 ***
## PclassSexP2Male      NA         NA      NA      NA
## PclassSexP3Female      NA         NA      NA      NA
## PclassSexP3Male      NA         NA      NA      NA
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 824.69  on 622  degrees of freedom
## Residual deviance: 511.13  on 613  degrees of freedom
## AIC: 531.13
##
## Number of Fisher Scoring iterations: 5
```

## 05 데이터 모델 학습 후, 예측

```
pred <- predict(m, newdata=train_test, type = "response")
```

```
## Warning in predict.lm(object, newdata, se.fit, scale = 1, type = if (type
## == : prediction from a rank-deficient fit may be misleading
```

```
pred[0:15]
```

```
##           1           14           16           17           18           23
## 0.11310787 0.05221481 0.82694520 0.15188648 0.12939787 0.69836518
##           25           27           31           40           41           44
## 0.42468460 0.18018887 0.41759707 0.61033893 0.23661317 0.98388632
##           47           48           50
## 0.14342270 0.62102425 0.47874246
```

```
pred <- as.integer(pred > 0.5)
pred[0:15]
```

```
## [1] 0 0 1 0 0 1 0 0 0 1 0 1 0 1 0
```

```
length(pred)
```

```
## [1] 268
```

## 05 데이터 모델 학습 후, 예측, 모델 평가

```
actual <- train_test[, "Survived"]
xt = xtabs(~ pred + actual)
xt
```

```
##      actual
## pred    0    1
##    0 149  42
##    1   11  66
```

```
# library(caret)
pred <- as.factor(pred)
actual <- as.factor(actual)
confusionMatrix(pred, actual)
```

```
## Confusion Matrix and Statistics
##
##           Reference
## Prediction  0    1
##           0 149  42
##           1   11  66
##
##           Accuracy : 0.8022
##           95% CI   : (0.7494, 0.8482)
##           No Information Rate : 0.597
##           P-Value [Acc > NIR] : 5.961e-13
##
##           Kappa   : 0.5689
##
## Mcnemar's Test P-Value : 3.775e-05
##
##           Sensitivity : 0.9313
##           Specificity : 0.6111
##           Pos Pred Value : 0.7801
##           Neg Pred Value : 0.8571
##           Prevalence : 0.5970
##           Detection Rate : 0.5560
##           Detection Prevalence : 0.7127
##           Balanced Accuracy : 0.7712
##
##           'Positive' Class : 0
##
```

```
str(train_tr)
```

```
## 'data.frame':   623 obs. of  13 variables:
## $ PassengerId: int   395 760 854 673 845 517 272 52 355 298 ...
## $ Survived   : Factor w/ 2 levels "0","1": 2 2 2 1 1 2 2 1 1 1 ...
## $ Pclass     : Ord.factor w/ 3 levels "1"<"2"<"3": 3 1 1 2 3 2 3 3 3 1 ...
## $ Name       : chr   "Sandstrom, Mrs. Hjalmar (Agnes Charlotta Bengtsson)" "Rothe
s, the Countess. of (Lucy Noel Martha Dyer-Edwards)" "Lines, Miss. Mary Conover" "Mit
chell, Mr. Henry Michael" ...
## $ Sex        : Factor w/ 2 levels "female","male": 1 1 1 2 2 1 2 2 2 1 ...
## $ Age        : num   24 33 16 70 17 34 25 21 25 2 ...
## $ SibSp      : int    0 0 0 0 0 0 0 0 0 1 ...
## $ Parch      : int    2 0 1 0 0 0 0 0 0 2 ...
## $ Ticket     : chr    "PP 9549" "110152" "PC 17592" "C.A. 24580" ...
## $ Fare       : num   16.7 86.5 39.4 10.5 8.66 ...
## $ Cabin      : chr    "G6" "B77" "D28" NA ...
## $ Embarked   : Factor w/ 3 levels "C","Q","S": 3 3 3 3 3 3 3 3 1 3 ...
## $ PclassSex  : Factor w/ 6 levels "P1Female","P1Male",...: 5 1 1 4 6 3 6 6 6 1 ...
```

## 06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델

```
# library(randomForest)
m2 <- randomForest(Survived ~ Pclass + Sex + PclassSex + SibSp + Age + Fare + Embarke
d, data=train_tr)
summary(m2)
```



```
##           Length Class  Mode
## call           3  -none- call
## type           1  -none- character
## predicted      623  factor numeric
## err.rate      1500  -none- numeric
## confusion       6  -none- numeric
## votes         1246  matrix numeric
## oob.times       623  -none- numeric
## classes        2  -none- character
## importance      7  -none- numeric
## importanceSD    0  -none- NULL
## localImportance 0  -none- NULL
## proximity       0  -none- NULL
## ntree           1  -none- numeric
## mtry            1  -none- numeric
## forest          14  -none- list
## y              623  factor numeric
## test           0  -none- NULL
## inbag           0  -none- NULL
## terms           3   terms  call
```

## 06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델 예측

```
rf_pred <- predict(m2, newdata=train_test, type=c("prob"))
rf_pred[0:15]
```

```
## [1] 0.926 0.970 0.174 0.852 1.000 0.212 0.802 0.974 0.746 0.492 0.694
## [12] 0.096 0.866 0.082 0.504
```

```
rf_pred <- predict(m2, newdata=train_test, type=c("class"))
rf_pred[0:15]
```

```
## 1 14 16 17 18 23 25 27 31 40 41 44 47 48 50
## 0 0 1 0 0 1 0 0 0 1 0 1 0 1 0
## Levels: 0 1
```

```
length(pred)
```

```
## [1] 268
```

## 06 데이터 모델 학습 후, 예측, 모델 평가 - 앙상블 모델

```
# library(caret)
actual <- train_test[, "Survived"]
pred <- as.factor(rf_pred)
actual <- as.factor(actual)
confusionMatrix(pred, actual)
```

```
## Confusion Matrix and Statistics
##
##           Reference
## Prediction  0    1
##           0 143  36
##           1  17  72
##
##           Accuracy : 0.8022
##           95% CI : (0.7494, 0.8482)
##           No Information Rate : 0.597
##           P-Value [Acc > NIR] : 5.961e-13
##
##           Kappa : 0.5769
##
## Mcnemar's Test P-Value : 0.01342
##
##           Sensitivity : 0.8938
##           Specificity : 0.6667
##           Pos Pred Value : 0.7989
##           Neg Pred Value : 0.8090
##           Prevalence : 0.5970
##           Detection Rate : 0.5336
##           Detection Prevalence : 0.6679
##           Balanced Accuracy : 0.7802
##
##           'Positive' Class : 0
##
```

## 07 가장 좋은 모델로 최종 예측

### 예측

```
nrow(testClean)
```

```
## [1] 418
```

```
pred <- predict(m2, newdata=testClean, type="prob")
pred[0:15,2]
```

```
##      892      893      894      895      896      897      898      899      900      901      902      903
## 0.002 0.312 0.138 0.020 0.542 0.156 0.540 0.098 0.782 0.058 0.000 0.084
##      904      905      906
## 0.940 0.080 0.998
```

```
length(pred[,2])
```

```
## [1] 418
```

```
pred <- as.integer(pred[,2] > 0.5)
pred[0:15]
```

```
## [1] 0 0 0 0 1 0 1 0 1 0 0 0 1 0 1
```

```
length(pred)
```

```
## [1] 418
```

## 제출

```
sub[, 'Survived'] = pred  
sub[0:15,]
```

```
##      PassengerId Survived  
## 1           892         0  
## 2           893         0  
## 3           894         0  
## 4           895         0  
## 5           896         1  
## 6           897         0  
## 7           898         1  
## 8           899         0  
## 9           900         1  
## 10          901         0  
## 11          902         0  
## 12          903         0  
## 13          904         1  
## 14          905         0  
## 15          906         1
```

```
write.csv(sub, file="SecondSub.csv", row.names = F)  
list.files(path=".", pattern=NULL)
```

```
## [1] "df_score.csv"  
## [2] "df_score.rda"  
## [3] "firstSub.csv"  
## [4] "img"  
## [5] "pdf"  
## [6] "R_Data"  
## [7] "R_STAT_ANALYSIS"  
## [8] "RBasic_Source"  
## [9] "README.md"  
## [10] "RLevelUp_Source"  
## [11] "RProject_practice_withdoit.ipynb"  
## [12] "RProject01A_dplyr_withdoit_v11.ipynb"  
## [13] "RProject01B_dplyr_ggplot_withdoit.ipynb"  
## [14] "RProject01C_dplyr_ggplot_withdoit.ipynb"  
## [15] "RProject02A_Titanic.html"  
## [16] "RProject02A_Titanic.md"  
## [17] "RProject02A_Titanic.rmd"  
## [18] "RProject02A_Titanic_files"  
## [19] "RProject02B_Titanic.html"  
## [20] "RProject02B_Titanic.rmd"  
## [21] "SecondSub.csv"
```