

Minesweeper Solver

Project proposal

Chunxu Guo Jiahao Huang Qianyu Liu
Chenyang Zhang Tianyi Zhang

ShanghaiTech University

CS181: Artificial Intelligence I, Fall 2020



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver**
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



Notation

For any block x, y on the board, we have 3 states:

- 1 Undetected $U_{x,y} = \text{True/False}$
- 2 Detected with the number of mines around it $D_{x,y}^{num} = \text{True/False}$, $num \in (0, 1, \dots, 8)$
- 3 With mine underneath $M_{x,y} = \text{True/False}$

We could encode all the information on the board with these 3 states.



Translating the rules

- ① each block that is detected with the number have number of mines that are the same of number of this block $\forall (x, y), \text{mines_around}(x, y) == \text{num}(x, y)$
- ② each block contains exactly one number $\forall (x, y), \text{exactly_one}(D_{x,y}^{\text{num}}), \text{num} \in (0, 1, \dots, 8)$



Ask queries

We will query each block on the frontier whether it is mine. If it is possible to give a satisfiable assignment in limited steps, we will take this action and update knowledge base to keep inference which block is possible mine.

If SAT solver could not find satisfiable assignment in limited time, we would stop it and use other methods.



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model**
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



Minesweeper CSP Model

With current observation K (i.e. the knowledge matrix), we can enumerate all configurations compatible with K , then

- deduce for each cell c whether it is safe (no configuration where c is mined)
- deduce for each cell c whether it is mined (c is mined in all configurations)
- compute the probability for c to be mined as the ratio

$$p_m(c) = \frac{\# \text{ (cfgs where } c \text{ is mined)}}{\# \text{ (all cfgs)}}$$



CSP Formulation

Searching for a single configuration compatible with K can be formulated as a CSP as follows:

- $\forall c = (i, j), x_{i,j} \in \{0, 1\}$
- $\forall c = (i, j), (K_{i,j} \geq 0) \Rightarrow (x_{i,j} = 0)$
- $\forall c = (i, j), (K_{i,j} \geq 0) \Rightarrow (\sum_{c'=(i',j') \in a(c)} x_{i',j'} = K_{i,j})$
- $(\sum_{c=(i,j)} x_{i,j} = m)$



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View**
- 6 CNN Solver
- 7 \LaTeX example section



POMDP: Partially Observable Markov Decision Process

- Generalization of a Markov decision process (MDP)
- Agent cannot directly observe the underlying state
- Maintain a probability distribution over the set of possible states



Minesweeper POMDP Model

Minesweeper game can be modeled as a POMDP $\langle S, S_e, A, T, R, O, \Omega, b_0 \rangle$ where:

- set of states S : init state, normal states, failure state
- terminal state S_e : success state, failure state
- actions in A : try hidden cell c
- transition function T
- reward $R(s, a, s')$
- observations in O
- observation function Ω : updates the knowledge matrix according to the last action
- b_0 : initial probability distribution over states



POMDP Challenges

Belief space is huge:

- $2^{W \times H}$ states!
- Solving POMDPs exactly is computationally intractable
- MOMDP: Mixed Observability Markov Decision Process
 - we can derive a compact lower-dimensional representation of the belief space
- Monte-Carlo Tree Search



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver**
- 7 \LaTeX example section



Table of Contents

- 1 Topic and Motivation
- 2 Logic Inference
- 3 SAT Solver
- 4 CSP Probability Model
- 5 POMDP View
- 6 CNN Solver
- 7 \LaTeX example section



This is a text in second frame. For the sake of showing an example.

- Text 1
- Text 2
- Text 3
- Text 4



In this slide



In this slide
the text will be partially visible



In this slide
the text will be partially visible
And finally everything will be there



Sample frame title

In this slide, some important text will be highlighted because it's important. Please, don't abuse it.

Remark

Sample text

Important theorem

Sample text in red box

Examples

Sample text in green box. The title of the block is "Examples".



This is a text in first column.

$$E = mc^2$$

- First item
- Second item

This text will be in the second column and on a second thought this is a nice looking layout in some cases.

