

# CHAPTER 9

## Relational Database Design by ER-to-Relational Mapping

# Chapter Outline

## ■ ER-to-Relational Mapping Algorithm


- Step 1: Mapping of Regular Entity Types
- Step 2: Mapping of Weak Entity Types
- Step 3: Mapping of Binary 1:1 Relation Types
- Step 4: Mapping of Binary 1:N Relationship Types.
- Step 5: Mapping of Binary M:N Relationship Types.
- Step 6: Mapping of Multivalued attributes.
- Step 7: Mapping of N-ary Relationship Types.

# GOALS during Mapping



- Preserve all information (that includes all attributes)
- Maintain the constraints to the extent possible
- Minimize null values

*The mapping procedure described has been implemented in many commercial tools.*

**Figure 9.1** The ER conceptual schema diagram for the COMPANY database.



# Figure 9.2 Result of mapping the COMPANY ER schema into a relational database schema.



# ER-to-Relational Mapping Algorithm

- Step 1: Mapping of Regular Entity Types.
  - For each regular (strong) entity type  $E$  in the ER schema, create a relation  $R$  that includes all the simple attributes of  $E$ .
  - Choose one of the key attributes of  $E$  as the primary key for  $R$ .
  - If the chosen key of  $E$  is composite, the set of simple attributes that form it will together form the primary key of  $R$ .

# ER-to-Relational Mapping Algorithm

- Example: We create the relations EMPLOYEE, DEPARTMENT, and PROJECT in the relational schema corresponding to the regular entities in the ER diagram.
  - SSN, DNUMBER, and PNUMBER are the primary keys for the relations EMPLOYEE, DEPARTMENT, and PROJECT as shown.

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

## DEPARTMENT

Dname	<u>Dnumber</u>
-------	----------------

## PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------



# ER-to-Relational Mapping Algorithm (contd.)

## ■ Step 2: Mapping of Weak Entity Types

- For each weak entity type W in the ER schema with owner entity type E, create a relation R & include all simple attributes (or simple components of composite attributes) of W as attributes of R.
- Also, include as foreign key attributes of R the primary key attribute(s) of the relation(s) that correspond to the owner entity type(s).
- The primary key of R is the *combination* of the primary key(s) of the owner(s) and the partial key of the weak entity type W, if any.

# ER-to-Relational Mapping Algorithm (contd.)

- **Example:** Create the relation DEPENDENT in this step to correspond to the weak entity type DEPENDENT.
  - Include the primary key SSN of the EMPLOYEE relation as a foreign key attribute of DEPENDENT (renamed to ESSN).
  - The primary key of the DEPENDENT relation is the combination {ESSN, DEPENDENT\_NAME} because DEPENDENT\_NAME is the partial key of DEPENDENT.


**DEPENDENT**

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

# ER-to-Relational Mapping Algorithm (contd.)

- **Step 3: Mapping of Binary 1:1 Relation Types**
  - For each binary 1:1 relationship type R in the ER schema, identify the relations S and T that correspond to the entity types participating in R.
- There are three possible approaches:
  1. **Foreign Key ( 2 relations) approach:** Choose one of the relations-say S-and include a foreign key in S the primary key of T. It is better to choose an entity type with total participation in R in the role of S.
    - Example: 1:1 relation MANAGES is mapped by choosing the participating entity type DEPARTMENT to serve in the role of S, because its participation in the MANAGES relationship type is total.

# ER-to-Relational Mapping Algorithm (contd.)



## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

## PROJECT

Pname	<u>Pnumber</u>	<u>Plocation</u>	Dnum
-------	----------------	------------------	------

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

# ER-to-Relational Mapping Algorithm (contd.)



2. **Merged relation (1 relation) option:** An alternate mapping of a 1:1 relationship type is possible by merging the two entity types and the relationship into a single relation. This may be appropriate when both participations are total.
  
3. **Cross-reference or relationship relation ( 3 relations) option:** The third alternative is to set up a third relation R for the purpose of cross-referencing the primary keys of the two relations S and T representing the entity types.

# ER-to-Relational Mapping Algorithm (contd.)

- Step 4: Mapping of Binary 1:N Relationship Types.
  - For each regular binary 1:N relationship type R, identify the relation S that represent the participating entity type at the N-side of the relationship type.
  - Include as foreign key in S the primary key of the relation T that represents the other entity type participating in R.
  - Include any simple attributes of the 1:N relation type as attributes of S.

# ER-to-Relational Mapping Algorithm (contd.)

- Example: 1:N relationship types WORKS\_FOR, CONTROLS, and SUPERVISION in the figure.
  - For WORKS\_FOR we include the primary key DNUMBER of the DEPARTMENT relation as foreign key in the EMPLOYEE relation and call it DNO.





# ER-to-Relational Mapping Algorithm (contd.)

- **Step 5: Mapping of Binary M:N Relationship Types.**
  - For each regular binary M:N relationship type R, *create a new relation S to represent R. This is a relationship relation.*
  - Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types; *their combination will form the primary key of S.*
  - Also include any simple attributes of the M:N relationship type (or simple components of composite attributes) as attributes of S.



# ER-to-Relational Mapping Algorithm (contd.)

- Example: The M:N relationship type WORKS\_ON from the ER diagram is mapped by creating a relation WORKS\_ON in the relational database schema.
  - The primary keys of the PROJECT and EMPLOYEE relations are included as foreign keys in WORKS\_ON and renamed PNO and ESSN, respectively.
  - Attribute HOURS in WORKS\_ON represents the HOURS attribute of the relation type. The primary key of the WORKS\_ON relation is the combination of the foreign key attributes {ESSN, PNO}.



# ER-to-Relational Mapping Algorithm (contd.)

## ■ Step 6: Mapping of Multivalued attributes.

- For each multivalued attribute A, create a new relation R.
- This relation R will include an attribute corresponding to A, plus the primary key attribute K-as a foreign key in R-of the relation that represents the entity type of relationship type that has A as an attribute.
- The primary key of R is the combination of A and K. If the multivalued attribute is composite, we include its simple components.

# ER-to-Relational Mapping Algorithm (contd.)

- **Example:** The relation DEPT\_LOCATIONS is created.
  - The attribute DLOCATION represents the multivalued attribute LOCATIONS of DEPARTMENT, while DNUMBER-as foreign key-represents the primary key of the DEPARTMENT relation.
  - The primary key of R is the combination of {DNUMBER, DLOCATION}.



**DEPT\_LOCATIONS**

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

# ER-to-Relational Mapping Algorithm (contd.)

- **Step 7: Mapping of N-ary Relationship Types.**
  - For each n-ary relationship type R, where  $n > 2$ , create a new relationship S to represent R.
  - Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types.
  - Also include any simple attributes of the n-ary relationship type (or simple components of composite attributes) as attributes of S.



# Figure 9.2 Result of mapping the COMPANY ER schema into a relational database schema.




## FIGURE 3.17

# TERNARY RELATIONSHIP: SUPPLY

- This can be mapped to the relation SUPPLY shown in the relational schema, whose primary key is the combination of the three foreign keys {SNAME, PARTNO, PROJNAME}



# Mapping the *n*-ary relationship type SUPPLY



# Summary of Mapping constructs and constraints

**Table 9.1** Correspondence between ER and Relational Models

ER MODEL	RELATIONAL MODEL
Entity type	<i>Entity</i> relation
1:1 or 1:N relationship type	Foreign key (or <i>relationship</i> relation)
M:N relationship type	<i>Relationship</i> relation and <i>two</i> foreign keys
<i>n</i> -ary relationship type	<i>Relationship</i> relation and <i>n</i> foreign keys
Simple attribute	Attribute
Composite attribute	Set of simple component attributes
Multivalued attribute	Relation and foreign key
Value set	Domain
Key attribute	Primary (or secondary) key