LogicLab Programming Logic and Design

Questions and answers

229 numbered exercises covering the five learning units and task library. Use the same exercise numbers to match questions with the answer pack. Methods use zero-based arrays and inclusive FOR bounds. Written tasks can have other valid solutions.

Open revision material. Attempt each question before consulting the answer pack.

Unit 1 Algorithms and the development life cycle

Exercise 1 Knowledge check 1

Question

```
What should happen before choosing program statements?
A. Write the final code
B. Clarify inputs, outputs and requirements
C. Deploy the program
```

Model solution

```
B. Clarify inputs, outputs and requirements
Requirements establish what the solution must achieve before implementation choices are
made.
```

Exercise 2 Knowledge check 2

Question

```
Which activity belongs to requirements analysis?
A. Choose a button colour first
B. Ignore invalid data
C. Identify required inputs and outputs
```

Model solution

```
C. Identify required inputs and outputs
Identify required inputs and outputs. Review the related theory and work through a small
example to check the rule.
```

Exercise 3 Knowledge check 3

Question

```
Which statement describes an algorithm?
A. A particular graphics card
B. A finite ordered solution procedure
C. Only source code in C#
```

Model solution

```
B. A finite ordered solution procedure
A finite ordered solution procedure. Review the related theory and work through a small
example to check the rule.
```

Exercise 4 Knowledge check 4

Question

```
When should documentation happen?
A. Throughout development
B. Only after retirement
C. Never during design
```

Model solution

```
A. Throughout development
Throughout development. Review the related theory and work through a small example to
check the rule.
```

Exercise 5 Knowledge check 5

Question

```
A program runs without crashing. What follows?
A. It must be correct
B. All boundaries are covered
C. Its outputs still need testing
```

Model solution

```
C. Its outputs still need testing
Its outputs still need testing. Review the related theory and work through a small
example to check the rule.
```

Exercise 6 Find and fix the error

Question

```
Requirement: Calculate total price as unit price multiplied by quantity. Assume non-
negative numeric inputs.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. INPUT price
3. INPUT quantity
4. SET total = price + quantity
5. OUTPUT total
6. END
```

Model solution

Line 4 - Logic or Calculation
SET total = price * quantity
The total price is unit price multiplied by the quantity. Adding them does not represent the stated rule.

Exercise 7 Build or trace a solution

Question

Read a parcel weight and a rate per kilogram. Calculate and display the delivery charge. Assume valid non-negative input. Work independently before comparing your answer.

Model solution

```
BEGIN
INPUT weight
INPUT rate
SET charge = weight * rate
OUTPUT charge
END
```

Expected behaviour:
For weight 3 and rate 12, charge is 36. For weight 0 and rate 12, charge is 0.

Review:
Identify weight and rate as inputs.
Multiply the current inputs to obtain charge.
Display the result and test zero as a boundary.

Exercise 8 Apply the concept

Question

Add a fixed handling charge of R15. Give two test cases.

Model solution

SET charge = weight * rate + 15. For weight 3 and rate 12, expect 51; for weight 0, expect 15. Confirm whether zero-weight parcels are actually permitted in the requirements.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 1 Pseudocode and flowchart symbols

Exercise 9 Knowledge check 1

Question

```
Which symbol represents an input operation?
A. Rectangle
B. Diamond
C. Parallelogram
```

Model solution

```
C. Parallelogram
Input and output use parallelograms; a diamond is a decision.
```

Exercise 10 Knowledge check 2

Question

```
Which symbol should contain a calculation?
A. Decision diamond
B. Process rectangle
C. Input parallelogram
```

Model solution

```
B. Process rectangle
Process rectangle. Review the related theory and work through a small example to check
the rule.
```

Exercise 11 Knowledge check 3

Question

```
What does a flowchart arrow show?
A. Direction of control flow
B. The data type
C. The program title
```

Model solution

```
A. Direction of control flow
Direction of control flow. Review the related theory and work through a small example to
check the rule.
```

Exercise 12 Knowledge check 4

Question

```
Why label decision branches?
A. To sort values
B. To create variables
C. To distinguish condition outcomes
```

Model solution

```
C. To distinguish condition outcomes
To distinguish condition outcomes. Review the related theory and work through a small
example to check the rule.
```

Exercise 13 Knowledge check 5

Question

```
Is there one universal pseudocode syntax?
A. Only indentation is relevant
B. No, state the chosen conventions
C. Yes, every language uses one
```

Model solution

```
B. No, state the chosen conventions
No, state the chosen conventions. Review the related theory and work through a small
example to check the rule.
```

Exercise 14 Find and fix the error

Question

```
Requirement: Display Adult when age is at least 18. Close each selection with the
matching keyword.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. INPUT age
3. IF age &gt;= 18 THEN
4. OUTPUT "Adult"
5. ENDWHILE
6. END
```

Model solution

```
Line 5 - Syntax
ENDIF
An IF structure must close with ENDIF in the platform notation. ENDWHILE closes a
different structure.
```

Exercise 15 Build or trace a solution

Question

```
Read a temperature. Display "Cold" below 15 and "Mild or warm" otherwise. Draw the
corresponding flowchart. Work independently before comparing your answer.
```

Model solution

```
BEGIN
READ temperature
IF temperature &amp;lt; 15 THEN
DISPLAY "Cold"
ELSE
DISPLAY "Mild or warm"
END IF
END

Expected behaviour:
14 gives Cold; 15 gives Mild or warm.

Review:
Use a parallelogram for input.
Use a diamond for temperature &amp;lt; 15 and label both branches.
Join the paths after their output symbols.
```

Exercise 16 Apply the concept

Question

```
List the correct flowchart shapes for reading a mark, computing an average, testing a
pass condition and ending.
```

Model solution

```
Reading: parallelogram. Computing: process rectangle. Testing: decision diamond with
labelled branches. Ending: rounded terminal. A hierarchy chart would not show these
execution paths.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 1 Data types, variables and constants

Exercise 17 Knowledge check 1

Question

```
Which is usually the best type for a South African phone number?
A. INTEGER
B. STRING
C. BOOLEAN
```

Model solution

```
B. STRING
A phone number is an identifier, not a quantity; a string preserves leading zeroes and
formatting.
```

Exercise 18 Knowledge check 2

Question

```
What does initialisation do?
A. Gives a variable its starting value
B. Ends every loop
C. Changes the identifier type automatically
```

Model solution

```
A. Gives a variable its starting value
Gives a variable its starting value. Review the related theory and work through a small
example to check the rule.
```

Exercise 19 Knowledge check 3

Question

```
Which type represents TRUE or FALSE?
A. STRING only
B. REAL
C. BOOLEAN
```

Model solution

```
C. BOOLEAN
BOOLEAN. Review the related theory and work through a small example to check the rule.
```

Exercise 20 Knowledge check 4

Question

```
What value begins a multiplication accumulator?
A. -1 always
B. 1
C. 0
```

Model solution

```
B. 1
1. Review the related theory and work through a small example to check the rule.
```

Exercise 21 Knowledge check 5

Question

```
Can an INTEGER age be invalid?
A. Yes, a negative age can violate requirements
B. No, types guarantee all rules
C. Only if its name is age
```

Model solution

```
A. Yes, a negative age can violate requirements
Yes, a negative age can violate requirements. Review the related theory and work through
a small example to check the rule.
```

Exercise 22 Find and fix the error

Question

```
Requirement: Add an input price to an accumulator initialised to zero. Select the line
BEFORE which initialisation must be inserted.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. DECLARE total AS REAL
3. INPUT price
4. SET total = total + price
5. OUTPUT total
6. END
```

Model solution

```
Line 3 - Initialisation
SET total = 0, then INPUT price
Before accumulation, initialise total to zero. Keep the original INPUT price after the
initialisation.
```

Exercise 23 Build or trace a solution

Question

Calculate the product of three input numbers using an accumulator. Work independently before comparing your answer.

Model solution

```
BEGIN
DECLARE product AS REAL
product = 1
FOR i = 1 TO 3
INPUT value
product = product * value
NEXT i
OUTPUT product
END

Expected behaviour:
Inputs 2, 3, 4 give 24. Inputs 2, 0, 4 give 0.

Review:
Use REAL because inputs may have fractional parts.
Initialise multiplication to 1, not 0.
Multiply each value into product once.
```

Exercise 24 Apply the concept

Question

Choose types for student number, active flag, whole-item count and average mark. Justify each.

Model solution

Student number: STRING, to preserve leading zeroes. Active flag: BOOLEAN. Whole-item count: INTEGER. Average mark: REAL. Validate allowed values separately from choosing types.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 1 Expressions and operator precedence

Exercise 25 Knowledge check 1

Question

```
What is 4 + 3 * 2?
A. 14
B. 10
C. 11
```

Model solution

```
B. 10
Multiplication is performed before addition, so 3 * 2 is 6 and 4 + 6 is 10.
```

Exercise 26 Knowledge check 2

Question

```
What is (8 + 4) / 3?
A. 12
B. 9
C. 4
```

Model solution

```
C. 4
4. Review the related theory and work through a small example to check the rule.
```

Exercise 27 Knowledge check 3

Question

```
What is 17 MOD 5?
A. 5
B. 2
C. 3
```

Model solution

```
B. 2
2. Review the related theory and work through a small example to check the rule.
```

Exercise 28 Knowledge check 4

Question

```
What is 17 DIV 5?
A. 3
B. 2
C. 3.4
```

Model solution

```
A. 3
3. Review the related theory and work through a small example to check the rule.
```

Exercise 29 Knowledge check 5

Question

```
Which expression averages a and b?
A. a + b / 2
B. a * b / 2
C. (a + b) / 2
```

Model solution

```
C. (a + b) / 2
(a + b) / 2. Review the related theory and work through a small example to check the
rule.
```

Exercise 30 Find and fix the error

Question

```
Requirement: Calculate the average of two marks by dividing their sum by two.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. INPUT mark1
3. INPUT mark2
4. SET average = mark1 + mark2 / 2
5. OUTPUT average
6. END
```

Model solution

```
Line 4 - Calculation or Logic
SET average = (mark1 + mark2) / 2
Parentheses make the addition happen before dividing the total by two.
```

Exercise 31 Build or trace a solution

Question

Read price and quantity, then apply a 10% discount to the subtotal. Work independently before comparing your answer.

Model solution

```
BEGIN
INPUT price
INPUT quantity
SET subtotal = price * quantity
SET total = subtotal * (1 - 0.10)
OUTPUT total
END

Expected behaviour:
Price 20, quantity 3: subtotal 60 and total 54.

Review:
Calculate subtotal before applying the discount.
A 10% discount leaves 90% of subtotal.
Test no items and a simple positive quantity.
```

Exercise 32 Apply the concept

Question

Write an expression converting 135 minutes to whole hours and remaining minutes.

Model solution

hours = 135 DIV 60 gives 2; minutes = 135 MOD 60 gives 15. DIV and MOD are expressions displayed by the converter, not executed by it.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 1 Structured design and trace tables

Exercise 33 Knowledge check 1

Question

```
Which structure repeats a block of statements?
A. Sequence
B. Selection
C. Repetition
```

Model solution

```
C. Repetition
Repetition is the structure for repeated execution.
```

Exercise 34 Knowledge check 2

Question

```
What is a trace table used for?
A. List only method names
B. Record changing state and output
C. Replace every test
```

Model solution

```
B. Record changing state and output
Record changing state and output. Review the related theory and work through a small
example to check the rule.
```

Exercise 35 Knowledge check 3

Question

```
After x=2 and y=x+5, what is y?
A. 7
B. 2
C. 5
```

Model solution

```
A. 7
7. Review the related theory and work through a small example to check the rule.
```

Exercise 36 Knowledge check 4

Question

```
Which is a selection structure?
A. A single OUTPUT
B. An assignment alone
C. IF/ELSE
```

Model solution

```
C. IF/ELSE
IF/ELSE. Review the related theory and work through a small example to check the rule.
```

Exercise 37 Knowledge check 5

Question

```
Which is a feature of maintainable code?
A. All tasks in one enormous method
B. Clear names and focused responsibilities
C. Maximum duplication
```

Model solution

```
B. Clear names and focused responsibilities
Clear names and focused responsibilities. Review the related theory and work through a
small example to check the rule.
```

Exercise 38 Find and fix the error

Question

```
Requirement: Display the final value of x after all assignments.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. SET x = 3
3. SET y = x + 2
4. SET x = y * 2
5. OUTPUT y
6. END
```

Model solution

```
Line 5 - Logic
OUTPUT x
The requirement is to display the final x. Here y is 5 and the final x is 10.
```

Exercise 39 Build or trace a solution

Question

Dry-run the assignments and record the values after each statement. Work independently before comparing your answer.

Model solution

```
BEGIN
SET a = 4
SET b = a + 3
SET a = b - 2
SET b = a * 2
OUTPUT a, b
END

Expected behaviour:
After assignments: (a=4,b=unset), (4,7), (5,7), (5,10). Output: 5, 10.

Review:
Assignment changes only the variable on its left.
Use the latest values on the right-hand side.
Distinguish the current state from displayed output.
```

Exercise 40 Apply the concept

Question

Classify each action: read two marks, choose whether a mark passes, repeat input for ten learners.

Model solution

Reading the two marks in order is sequence. Choosing a result is selection. Processing ten learners uses repetition. A complete program can combine all three structures.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 2 Boolean expressions and basic selection

Exercise 41 Knowledge check 1

Question

```
When is A OR B false?
A. When both are false
B. When either is true
C. When both are true
```

Model solution

```
A. When both are false
Inclusive OR is false only when neither operand is true.
```

Exercise 42 Knowledge check 2

Question

```
When is A AND B true?
A. Only when both are true
B. When either is true
C. When both are false
```

Model solution

```
A. Only when both are true
Only when both are true. Review the related theory and work through a small example to
check the rule.
```

Exercise 43 Knowledge check 3

Question

```
What is NOT FALSE?
A. FALSE
B. Undefined
C. TRUE
```

Model solution

```
C. TRUE
TRUE. Review the related theory and work through a small example to check the rule.
```

Exercise 44 Knowledge check 4

Question

Which condition accepts 0 through 100?
A. mark > 0 AND mark < 100
B. mark >= 0 AND mark <= 100
C. mark >= 0 OR mark <= 100

Model solution

B. mark >= 0 AND mark <= 100
mark >= 0 AND mark <= 100. Review the related theory and work through a small example to check the rule.

Exercise 45 Knowledge check 5

Question

Which values best test a pass boundary of 50?
A. 49, 50 and 51
B. 1, 2 and 3
C. Only 100

Model solution

A. 49, 50 and 51
49, 50 and 51. Review the related theory and work through a small example to check the rule.

Exercise 46 Find and fix the error

Question

Requirement: A mark of 50 or more passes, including exactly 50.
Focused snippet: assume omitted declarations and input setup are supplied unless the task says otherwise.
Identify the faulty line, error category and correction.

```
1. BEGIN
2. INPUT mark
3. IF mark &gt; 50 THEN
4. OUTPUT "Pass"
5. ELSE
6. OUTPUT "Not yet passed"
7. ENDIF
8. END
```

Model solution

```
Line 3 - Boundary
IF mark &gt;= 50 THEN
A score of exactly 50 must pass. The &gt;= operator includes that boundary.
```

Exercise 47 Build or trace a solution

Question

```
Read a mark and display whether it is between 0 and 100 inclusive. Work independently
before comparing your answer.
```

Model solution

```
BEGIN
INPUT mark
IF mark &gt;= 0 AND mark &lt;= 100 THEN
OUTPUT "Valid"
ELSE
OUTPUT "Invalid"
ENDIF
END

Expected behaviour:
-1 invalid, 0 valid, 100 valid, 101 invalid.

Review:
Both the lower and upper bounds must hold.
Use AND for the intersection of the two conditions.
Check values at and just outside each endpoint.
```

Exercise 48 Apply the concept

Question

```
Write an invalid-range condition using OR, and another using NOT.
```

Model solution

```
Invalid: mark &lt; 0 OR mark &gt; 100. Equivalent: NOT (mark &gt;= 0 AND mark &lt;= 100). Parentheses
 make the negated range explicit.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 2 Precedence and nested decisions

Exercise 49 Knowledge check 1

Question

```
What is TRUE OR FALSE AND FALSE?
A. FALSE
B. TRUE
C. Invalid
```

Model solution

```
B. TRUE
AND is evaluated before OR: TRUE OR (FALSE AND FALSE) is TRUE.
```

Exercise 50 Knowledge check 2

Question

```
Which logical operator has highest precedence here?
A. OR
B. AND
C. NOT
```

Model solution

```
C. NOT
NOT. Review the related theory and work through a small example to check the rule.
```

Exercise 51 Knowledge check 3

Question

```
In nested IF, when is the inner branch considered?
A. Only at program end
B. Only after execution enters its outer branch
C. Before every outer condition
```

Model solution

```
B. Only after execution enters its outer branch
Only after execution enters its outer branch. Review the related theory and work through
a small example to check the rule.
```

Exercise 52 Knowledge check 4

Question

```
Why test a 75 distinction before a 50 pass band?
A. The more specific higher band should be checked first
B. It changes the input type
C. It removes the need for ELSE
```

Model solution

```
A. The more specific higher band should be checked first
The more specific higher band should be checked first. Review the related theory and work
 through a small example to check the rule.
```

Exercise 53 Knowledge check 5

Question

```
What does CASE typically compare?
A. Only two variables without values
B. Every array position automatically
C. One expression against listed values
```

Model solution

```
C. One expression against listed values
One expression against listed values. Review the related theory and work through a small
example to check the rule.
```

Exercise 54 Find and fix the error

Question

```
Requirement: Allow entry only when age is at least 18 AND the person has ID.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. INPUT age
3. INPUT hasID
4. IF age &gt;= 18 OR hasID = TRUE THEN
5. OUTPUT "Entry allowed"
6. ENDIF
7. END
```

Model solution

```
Line 4 - Logic
IF age &gt;= 18 AND hasID = TRUE THEN
Both conditions are required. OR would allow someone who meets only one condition.
```

Exercise 55 Build or trace a solution

Question

Display Distinction for marks of at least 75, Pass for marks of at least 50, otherwise Revise. Work independently before comparing your answer.

Model solution

```
BEGIN
INPUT mark
IF mark &gt;= 75 THEN
OUTPUT "Distinction"
ELSEIF mark &gt;= 50 THEN
OUTPUT "Pass"
ELSE
OUTPUT "Revise"
END IF
END

Expected behaviour:
75 -&gt; Distinction, 74 -&gt; Pass, 50 -&gt; Pass, 49 -&gt; Revise.

Review:
Test the highest band first.
ELSEIF is considered only after the preceding condition is false.
Check each exact threshold and the value immediately below.
```

Exercise 56 Apply the concept

Question

Rewrite the band selection using a nested IF inside ELSE.

Model solution

```
IF mark &gt;= 75 THEN
  OUTPUT "Distinction"
ELSE
  IF mark &gt;= 50 THEN
    OUTPUT "Pass"
  ELSE
    OUTPUT "Revise"
  ENDIF
ENDIF

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 2 Counted loops and accumulators

Exercise 57 Knowledge check 1

Question

```
How many times does FOR i = 1 TO 4 execute with STEP 1?
A. 3
B. 4
C. 5
```

Model solution

```
B. 4
Both endpoints are included: i is 1, 2, 3 and 4.
```

Exercise 58 Knowledge check 2

Question

```
What is a counter normally increased by when counting occurrences?
A. 0
B. 1
C. The total input value
```

Model solution

```
B. 1
1. Review the related theory and work through a small example to check the rule.
```

Exercise 59 Knowledge check 3

Question

```
When should a final grand total usually be displayed?
A. After accumulation finishes
B. Before initialisation
C. Only inside the first iteration
```

Model solution

```
A. After accumulation finishes
After accumulation finishes. Review the related theory and work through a small example
to check the rule.
```

Exercise 60 Knowledge check 4

Question

```
How many iterations does FOR i=2 TO 6 STEP 2 have?
A. 2
B. 6
C. 3
```

Model solution

```
C. 3
3. Review the related theory and work through a small example to check the rule.
```

Exercise 61 Knowledge check 5

Question

```
How many iterations does FOR i=5 TO 1 STEP -1 have?
A. 0
B. 5
C. 4
```

Model solution

```
B. 5
5. Review the related theory and work through a small example to check the rule.
```

Exercise 62 Find and fix the error

Question

```
Requirement: Read three values and display their sum, keeping a running total.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. SET total = 0
3. FOR i = 1 TO 3
4. INPUT value
5. SET total = value
6. ENDFOR
7. OUTPUT total
8. END
```

Model solution

```
Line 5 - Logic
SET total = total + value
Assigning value alone discards the previous total. An accumulator adds the new value to
the running total.
```

Exercise 63 Build or trace a solution

Question

Read four marks and count how many are at least 50. Work independently before comparing your answer.

Model solution

```
BEGIN
SET passes = 0
FOR i = 1 TO 4
INPUT mark
IF mark &gt;= 50 THEN
SET passes = passes + 1
ENDIF
ENDFOR
OUTPUT passes
END

Expected behaviour:
Inputs 40, 50, 70, 20 give 2 passes.

Review:
Initialise the counter once before the loop.
Increment by one only when the condition is true.
Display passes after all four inputs.
```

Exercise 64 Apply the concept

Question

Calculate the average of four marks. Include initialisation and final output.

Model solution

```
BEGIN
SET total = 0
FOR i = 1 TO 4
INPUT mark
SET total = total + mark
ENDFOR
SET average = total / 4
OUTPUT average
END

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 2 Conditional loops and priming input

Exercise 65 Knowledge check 1

Question

```
Which loop always executes its body at least once?
A. WHILE
B. REPEAT/UNTIL
C. Every FOR loop
```

Model solution

```
B. REPEAT/UNTIL
REPEAT/UNTIL tests after executing its body.
```

Exercise 66 Knowledge check 2

Question

```
Can a WHILE body run zero times?
A. Yes
B. No
C. Only with strings
```

Model solution

```
A. Yes
Yes. Review the related theory and work through a small example to check the rule.
```

Exercise 67 Knowledge check 3

Question

```
What should happen to a sentinel value?
A. It must be added to every total
B. It becomes the average
C. It should normally be excluded from data totals
```

Model solution

```
C. It should normally be excluded from data totals
It should normally be excluded from data totals. Review the related theory and work
through a small example to check the rule.
```

Exercise 68 Knowledge check 4

Question

```
When does REPEAT/UNTIL stop?
A. Before the first body execution
B. When its condition is true
C. While its condition is false before entry
```

Model solution

```
B. When its condition is true
When its condition is true. Review the related theory and work through a small example to
 check the rule.
```

Exercise 69 Knowledge check 5

Question

```
Why guard average calculation when count is zero?
A. To avoid division by zero
B. To change count into an array
C. To force one more valid value
```

Model solution

```
A. To avoid division by zero
To avoid division by zero. Review the related theory and work through a small example to
check the rule.
```

Exercise 70 Find and fix the error

Question

```
Requirement: Read and display values until a new input equals the sentinel -1.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. INPUT value
3. WHILE value &lt;&gt; -1 DO
4. OUTPUT value
5. SET value = value
6. ENDWHILE
7. END
```

Model solution

```
Line 5 - Logic
INPUT value
A new input allows the condition to change. Assigning value to itself cannot obtain the
next value.
```

Exercise 71 Build or trace a solution

Question

```
Read values until -1. Display their average, or No data when the first input is -1. Work
independently before comparing your answer.
```

Model solution

```
BEGIN
SET total = 0
SET count = 0
INPUT value
WHILE value &lt;&gt; -1 DO
SET total = total + value
SET count = count + 1
INPUT value
ENDWHILE
IF count &gt; 0 THEN
OUTPUT total / count
ELSE
OUTPUT "No data"
ENDIF
END

Expected behaviour:
10, 20, -1 gives 15. The input -1 alone gives No data.

Review:
Read the priming value before checking the condition.
Exclude the sentinel from total and count.
Guard division so count cannot be zero.
```

Exercise 72 Apply the concept

Question

```
Validate a non-negative age with a post-test loop.
```

Model solution

```
REPEAT
  INPUT age
UNTIL age &gt;= 0
OUTPUT age
The loop runs at least once and continues while invalid input is supplied.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 2 Nested loops

Exercise 73 Knowledge check 1

Question

```
How many pairs are output by the example?
A. 2
B. 3
C. 6
```

Model solution

```
C. 6
Each of the two outer iterations runs three inner iterations: 2 * 3 = 6.
```

Exercise 74 Knowledge check 2

Question

```
A 4 by 3 nested traversal visits how many cells?
A. 7
B. 4
C. 12
```

Model solution

```
C. 12
12. Review the related theory and work through a small example to check the rule.
```

Exercise 75 Knowledge check 3

Question

```
Where does a per-row total reset?
A. At every inner comparison after adding
B. At the start of each outer iteration
C. Only once after both loops
```

Model solution

```
B. At the start of each outer iteration
At the start of each outer iteration. Review the related theory and work through a small
example to check the rule.
```

Exercise 76 Knowledge check 4

Question

```
Why use distinct nested-loop counters?
A. So the inner loop does not overwrite the outer state
B. To prevent all arithmetic
C. Because counters must be text
```

Model solution

```
A. So the inner loop does not overwrite the outer state
So the inner loop does not overwrite the outer state. Review the related theory and work
through a small example to check the rule.
```

Exercise 77 Knowledge check 5

Question

```
The inner loop runs 5 times for each of 2 outer iterations. Body count?
A. 5
B. 2
C. 10
```

Model solution

```
C. 10
10. Review the related theory and work through a small example to check the rule.
```

Exercise 78 Find and fix the error

Question

```
Requirement: Use independent counters for a two-row, three-column nested loop. Identify
the inner header that overwrites the outer counter.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. FOR row = 1 TO 2
3. FOR row = 1 TO 3
4. OUTPUT row
5. ENDFOR
6. ENDFOR
7. END
```

Model solution

```
Line 3 - Logic
FOR column = 1 TO 3
Use a distinct inner counter, such as column. Adjust the body to use row and column as
required.
```

Exercise 79 Build or trace a solution

Question

```
Output the products for rows 1 to 3 and columns 1 to 2. Work independently before
comparing your answer.
```

Model solution

```
BEGIN
FOR row = 1 TO 3
FOR column = 1 TO 2
SET product = row * column
OUTPUT product
ENDFOR
ENDFOR
END

Expected behaviour:
Outputs in order: 1, 2, 2, 4, 3, 6.

Review:
Keep row and column counters separate.
For each row, complete both column iterations.
Multiply the number of iterations to check the six outputs.
```

Exercise 80 Apply the concept

Question

```
Where should a row total and a grand total be initialised?
```

Model solution

```
Initialise grandTotal once before both loops. Initialise rowTotal at the start of each
outer-loop iteration. Add each cell to both totals inside the inner loop; output each row
 total after the inner loop and the grand total after the outer loop.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 3 Arrays and element access

Exercise 81 Knowledge check 1

Question

```
What is the last valid index in a zero-based array of length 5?
A. 5
B. 4
C. 6
```

Model solution

```
B. 4
Indices are 0, 1, 2, 3 and 4.
```

Exercise 82 Knowledge check 2

Question

```
What is the first index in this platform?
A. -1
B. 0
C. 1
```

Model solution

```
B. 0
0. Review the related theory and work through a small example to check the rule.
```

Exercise 83 Knowledge check 3

Question

```
For n values, which bound is correct?
A. 0 TO n - 1
B. 0 TO n
C. 1 TO n + 1
```

Model solution

```
A. 0 TO n - 1
0 TO n - 1. Review the related theory and work through a small example to check the rule.
```

Exercise 84 Knowledge check 4

Question

```
What accesses row r, column c?
A. values[r + c] always
B. values[n]
C. values[r][c]
```

Model solution

```
C. values[r][c]
values[r][c]. Review the related theory and work through a small example to check the
rule.
```

Exercise 85 Knowledge check 5

Question

```
How does capacity differ from meaningful count?
A. Capacity is a variable name only
B. Capacity can exceed the number of used values
C. They must always be equal
```

Model solution

```
B. Capacity can exceed the number of used values
Capacity can exceed the number of used values. Review the related theory and work through
 a small example to check the rule.
```

Exercise 86 Find and fix the error

Question

```
Requirement: Display all five elements of an already populated array values[5]. Arrays
start at index 0.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. FOR i = 0 TO 5
3. OUTPUT values[i]
4. ENDFOR
5. END
```

Model solution

```
Line 2 - Boundary
FOR i = 0 TO 4
For an array of length five, index five is out of bounds. The last valid index is four.
```

Exercise 87 Build or trace a solution

Question

Total an existing zero-based array containing five values. Work independently before comparing your answer.

Model solution

```
BEGIN
SET total = 0
FOR i = 0 TO 4
SET total = total + values[i]
ENDFOR
OUTPUT total
END

Expected behaviour:
For [2,4,6,8,10], output 30. The last accessed index is 4.

Review:
The meaningful indices run from 0 to length - 1.
Initialise total before visiting any element.
Use each index exactly once.
```

Exercise 88 Apply the concept

Question

Write a traversal for a 2 by 3 zero-based array.

Model solution

```
FOR row = 0 TO 1
  FOR column = 0 TO 2
    OUTPUT values[row][column]
  ENDFOR
ENDFOR
There are six element accesses.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 3 Linear search

Exercise 89 Knowledge check 1

Question

```
Why initialise foundAt to -1?
A. It is a valid first index
B. It distinguishes not found from index 0
C. It sorts the array
```

Model solution

```
B. It distinguishes not found from index 0
-1 is outside the valid indices and can represent no match.
```

Exercise 90 Knowledge check 2

Question

```
Does linear search require sorted data?
A. No
B. Yes, always
C. Only in ascending order
```

Model solution

```
A. No
No. Review the related theory and work through a small example to check the rule.
```

Exercise 91 Knowledge check 3

Question

```
Worst-case linear search comparisons for n items?
A. 1 always
B. 0
C. n
```

Model solution

```
C. n
n. Review the related theory and work through a small example to check the rule.
```

Exercise 92 Knowledge check 4

Question

```
How do you find every occurrence?
A. Only compare index zero
B. Continue through all valid positions
C. Stop at the first match
```

Model solution

```
B. Continue through all valid positions
Continue through all valid positions. Review the related theory and work through a small
example to check the rule.
```

Exercise 93 Knowledge check 5

Question

```
What should happen before using foundAt as an index?
A. Check that a match was found
B. Replace it with zero
C. Add one without checking
```

Model solution

```
A. Check that a match was found
Check that a match was found. Review the related theory and work through a small example
to check the rule.
```

Exercise 94 Find and fix the error

Question

```
Requirement: Search a populated four-element array for target. Display -1 when absent;
otherwise display a matching index.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. SET foundAt = 0
3. FOR i = 0 TO 3
4. IF values[i] = target THEN
5. SET foundAt = i
6. ENDIF
7. ENDFOR
8. OUTPUT foundAt
9. END
```

Model solution

```
Line 2 - Initialisation
SET foundAt = -1
Zero is a valid position, so it cannot unambiguously mean not found. Use -1 for this
zero-based example.
```

Exercise 95 Build or trace a solution

Question

```
Find the first position of target in a four-value array, stopping after a match. Work
independently before comparing your answer.
```

Model solution

```
BEGIN
SET foundAt = -1
SET i = 0
WHILE i &lt; 4 AND foundAt = -1 DO
IF values[i] = target THEN
SET foundAt = i
ENDIF
SET i = i + 1
ENDWHILE
OUTPUT foundAt
END

Expected behaviour:
Array [7,3,7,2], target 7 -&gt; 0. Target 9 -&gt; -1.

Review:
Use -1 for not found because 0 is a valid index.
Check the bound before accessing values[i].
Stop when foundAt changes from -1.
```

Exercise 96 Apply the concept

Question

```
How would you find every matching position rather than only the first?
```

Model solution

```
Traverse all valid indices. Whenever values[i] = target, output or record i. Do not stop
after the first match. For [7,3,7,2] and target 7, the positions are 0 and 2.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 3 Parallel arrays

Exercise 97 Knowledge check 1

Question

```
Which name belongs to scores[2]?
A. names[0]
B. names[2]
C. The largest name
```

Model solution

```
B. names[2]
A shared index connects attributes belonging to the same record.
```

Exercise 98 Knowledge check 2

Question

```
What links parallel arrays?
A. Identical variable names
B. The largest array value
C. A shared record index
```

Model solution

```
C. A shared record index
A shared record index. Review the related theory and work through a small example to
check the rule.
```

Exercise 99 Knowledge check 3

Question

```
What must happen when a name is swapped?
A. Nothing else may change
B. Its related attributes must move too
C. All marks must be cleared
```

Model solution

```
B. Its related attributes must move too
Its related attributes must move too. Review the related theory and work through a small
example to check the rule.
```

Exercise 100 Knowledge check 4

Question

```
Which design can reduce parallel-array alignment errors?
A. Objects or records holding related attributes
B. More unrelated global variables
C. Sorting just one array
```

Model solution

```
A. Objects or records holding related attributes
Objects or records holding related attributes. Review the related theory and work through
 a small example to check the rule.
```

Exercise 101 Knowledge check 5

Question

```
names[1] belongs with which score?
A. scores[0] always
B. The highest score
C. scores[1]
```

Model solution

```
C. scores[1]
scores[1]. Review the related theory and work through a small example to check the rule.
```

Exercise 102 Find and fix the error

Question

```
Requirement: Each name and score at the same index belong to one learner. Display the
name and score of learner index 2.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. SET i = 2
3. OUTPUT names[i], scores[0]
4. END
```

Model solution

```
Line 3 - Logic
OUTPUT names[i], scores[i]
Use the same index for related attributes; scores[0] may belong to another learner.
```

Exercise 103 Build or trace a solution

Question

Search three learner names and output the matching mark. Work independently before comparing your answer.

Model solution

```
BEGIN
SET foundAt = -1
FOR i = 0 TO 2
IF names[i] = targetName THEN
SET foundAt = i
ENDIF
ENDFOR
IF foundAt &lt;&gt; -1 THEN
OUTPUT scores[foundAt]
ELSE
OUTPUT "Not found"
ENDIF
END

Expected behaviour:
names=[Lebo,Mpho,Ana], scores=[65,80,72], targetName=Mpho -&gt; 80.

Review:
Use the name array to locate an index.
Guard against the not-found result.
Use the same index in scores.
```

Exercise 104 Apply the concept

Question

Explain how to swap two parallel records at positions j and j+1.

Model solution

Swap names[j] with names[j+1] using a temporary name. Also swap scores[j] with scores[j+1] using a temporary score. Both swaps must happen together to preserve the name-mark relationship.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 3 Bubble sort

Exercise 105 Knowledge check 1

Question

```
Why use a temporary variable during a swap?
A. To preserve a value before overwriting it
B. To increase the array length
C. To avoid comparing values
```

Model solution

```
A. To preserve a value before overwriting it
Without temporary storage, the first overwritten value can be lost.
```

Exercise 106 Knowledge check 2

Question

```
After a full ascending left-to-right bubble pass, where is the largest value?
A. Removed from the array
B. At the end of the unsorted part
C. Always at index zero
```

Model solution

```
B. At the end of the unsorted part
At the end of the unsorted part. Review the related theory and work through a small
example to check the rule.
```

Exercise 107 Knowledge check 3

Question

```
Maximum basic passes for n values?
A. n - 1
B. n + 1
C. 1 for every input
```

Model solution

```
A. n - 1
n - 1. Review the related theory and work through a small example to check the rule.
```

Exercise 108 Knowledge check 4

Question

```
Which adjacent comparison causes an ascending swap?
A. values[j] &lt; values[j + 1]
B. values[j] = values[j + 1]
C. values[j] &gt; values[j + 1]
```

Model solution

```
C. values[j] &gt; values[j + 1]
values[j] &gt; values[j + 1]. Review the related theory and work through a small example to
check the rule.
```

Exercise 109 Knowledge check 5

Question

```
What can a swapped flag improve?
A. Increase array capacity
B. Stop after a pass with no swaps
C. Guarantee zero comparisons
```

Model solution

```
B. Stop after a pass with no swaps
Stop after a pass with no swaps. Review the related theory and work through a small
example to check the rule.
```

Exercise 110 Find and fix the error

Question

```
Requirement: Swap the adjacent elements values[j] and values[j + 1]. Assume j and j + 1
are valid indices and both elements contain data.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. BEGIN
2. SET temp = values[j]
3. SET values[j] = values[j + 1]
4. SET values[j + 1] = values[j]
5. END
```

Model solution

```
Line 4 - Logic
SET values[j + 1] = temp
The original left value is in temp. Using values[j] again duplicates the right value.
```

Exercise 111 Build or trace a solution

Question

```
Perform one left-to-right ascending pass through four existing values. Work independently
 before comparing your answer.
```

Model solution

```
BEGIN
FOR j = 0 TO 2
IF values[j] &gt; values[j + 1] THEN
SET temp = values[j]
SET values[j] = values[j + 1]
SET values[j + 1] = temp
ENDIF
ENDFOR
OUTPUT values
END

Expected behaviour:
[4,1,3,2] becomes [1,3,2,4] after one pass. It is not fully sorted yet.

Review:
Compare adjacent values in order.
Swap only when the left value exceeds the right.
The largest value reaches the last position after this full pass.
```

Exercise 112 Apply the concept

Question

```
Give a full bubble sort for a zero-based array with n values.
```

Model solution

```
FOR pass = 0 TO n - 2
  FOR j = 0 TO n - 2 - pass
    IF values[j] &gt; values[j + 1] THEN
      SET temp = values[j]
      SET values[j] = values[j + 1]
      SET values[j + 1] = temp
    ENDIF
  ENDFOR
ENDFOR

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 4 Decomposition and hierarchy charts

Exercise 113 Knowledge check 1

Question

```
What does a hierarchy chart primarily show?
A. Every loop iteration
B. Module organisation and calls
C. The current values of all variables
```

Model solution

```
B. Module organisation and calls
A hierarchy chart describes the module structure and call relationships.
```

Exercise 114 Knowledge check 2

Question

```
Which is good decomposition?
A. Separate focused responsibilities
B. Put every operation in one module
C. Use one method for unrelated tasks
```

Model solution

```
A. Separate focused responsibilities
Separate focused responsibilities. Review the related theory and work through a small
example to check the rule.
```

Exercise 115 Knowledge check 3

Question

```
What describes cohesion?
A. How many fonts a page uses
B. The total variable count only
C. How closely a module’s tasks belong together
```

Model solution

```
C. How closely a module’s tasks belong together
How closely a module’s tasks belong together. Review the related theory and work through
a small example to check the rule.
```

Exercise 116 Knowledge check 4

Question

```
Does a hierarchy chart show every Boolean path?
A. Only if methods return integers
B. No, it shows module organisation
C. Yes, that is its main purpose
```

Model solution

```
B. No, it shows module organisation
No, it shows module organisation. Review the related theory and work through a small
example to check the rule.
```

Exercise 117 Knowledge check 5

Question

```
What is coupling?
A. Dependencies between modules
B. The number of array elements
C. The multiplication operator
```

Model solution

```
A. Dependencies between modules
Dependencies between modules. Review the related theory and work through a small example
to check the rule.
```

Exercise 118 Find and fix the error

Question

```
Requirement: Call the method defined in this program, using its exact name.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. METHOD showResult()
2. OUTPUT "Result ready"
3. ENDMETHOD
4. BEGIN
5. CALL showResults()
6. END
```

Model solution

```
Line 5 - Syntax
CALL showResult()
The call name must match the defined method name in this example.
```

Exercise 119 Build or trace a solution

Question

Create separate modules for greeting and displaying a learning reminder. Work independently before comparing your answer.

Model solution

```
MODULE greet()
OUTPUT "Welcome"
ENDMODULE
MODULE remind()
OUTPUT "Try an exercise"
ENDMODULE
BEGIN
CALL greet()
CALL remind()
END

Expected behaviour:
The main module calls greet and remind. Output: Welcome, then Try an exercise.

Review:
Identify two separate responsibilities.
Define the modules with clear names.
Draw the main module above the two called modules.
```

Exercise 120 Apply the concept

Question

Draw a hierarchy where Main calls calculate and calculate calls validate. Describe what the links mean.

Model solution

Main -> calculate -> validate. The links mean that one module calls another. They do not show Boolean branches, variable values or every execution step. validate need not be a direct child of Main.

```
Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 4 Parameters, arguments and scope

Exercise 121 Knowledge check 1

Question

```
In CALL displayName("Lebo"), what is "Lebo"?
A. A parameter declaration
B. An argument
C. A method header
```

Model solution

```
B. An argument
The actual supplied value is an argument; name is the parameter in the method definition.
```

Exercise 122 Knowledge check 2

Question

```
What is a parameter?
A. Only a literal at the call site
B. The final program output
C. A placeholder in a method definition
```

Model solution

```
C. A placeholder in a method definition
A placeholder in a method definition. Review the related theory and work through a small
example to check the rule.
```

Exercise 123 Knowledge check 3

Question

```
What is local scope?
A. The whole computer network
B. The region where a local identifier is accessible
C. An automatic global variable
```

Model solution

```
B. The region where a local identifier is accessible
The region where a local identifier is accessible. Review the related theory and work
through a small example to check the rule.
```

Exercise 124 Knowledge check 4

Question

```
For pass-by-value INTEGER x, local reassignment changes what?
A. The local parameter copy
B. The caller variable automatically
C. Every integer in the program
```

Model solution

```
A. The local parameter copy
The local parameter copy. Review the related theory and work through a small example to
check the rule.
```

Exercise 125 Knowledge check 5

Question

```
What should match at a call?
A. Only parameter spelling
B. Only return-value colour
C. Argument count, order and compatible types
```

Model solution

```
C. Argument count, order and compatible types
Argument count, order and compatible types. Review the related theory and work through a
small example to check the rule.
```

Exercise 126 Find and fix the error

Question

```
Requirement: displayPair expects two STRING arguments. Supply a first and second name.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. METHOD displayPair(first, second)
2. OUTPUT first, second
3. ENDMETHOD
4. BEGIN
5. CALL displayPair("Lebo")
6. END
```

Model solution

```
Line 5 - Syntax
CALL displayPair("Lebo", "Mpho")
The method expects two arguments. Supply both in the required order.
```

Exercise 127 Build or trace a solution

Question

Write a method that displays a supplied learner name and mark. Work independently before comparing your answer.

Model solution

```
METHOD displayResult(name, mark)
OUTPUT name, mark
ENDMETHOD
BEGIN
CALL displayResult("Lebo", 68)
END
```

Expected behaviour:
Parameters: name and mark. Arguments: "Lebo" and 68. Output: Lebo, 68.

Review:
Declare placeholders in the method header.
Match the two actual arguments to their positions.
Do not confuse the local parameter names with caller variables.

Exercise 128 Apply the concept

Question

Explain what happens with pass-by-value when a method reassigns an INTEGER parameter.

Model solution

The parameter receives a copy of the integer value. Reassigning that local parameter does not reassign the caller’s original variable. Returning a result or an explicitly different passing mode is needed to communicate the new value.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 4 Functions and return values

Exercise 129 Knowledge check 1

Question

```
Which statement gives a function result back to its caller?
A. OUTPUT result
B. RETURN result
C. INPUT result
```

Model solution

```
B. RETURN result
RETURN supplies the result to the caller; OUTPUT displays it.
```

Exercise 130 Knowledge check 2

Question

```
Does OUTPUT necessarily return a usable function value?
A. Only for positive numbers
B. No
C. Yes, always
```

Model solution

```
B. No
No. Review the related theory and work through a small example to check the rule.
```

Exercise 131 Knowledge check 3

Question

```
What does RETURN do to its method invocation?
A. Supplies a result and exits that invocation
B. Always restarts it
C. Displays every local variable
```

Model solution

```
A. Supplies a result and exits that invocation
Supplies a result and exits that invocation. Review the related theory and work through a
 small example to check the rule.
```

Exercise 132 Knowledge check 4

Question

```
A function promises a result. Which paths need one?
A. Only the first branch
B. Only the ELSE branch
C. Every normal finishing path
```

Model solution

```
C. Every normal finishing path
Every normal finishing path. Review the related theory and work through a small example
to check the rule.
```

Exercise 133 Knowledge check 5

Question

```
Where can a returned result be used?
A. Only in a flowchart title
B. In an assignment or expression
C. Only in a comment
```

Model solution

```
B. In an assignment or expression
In an assignment or expression. Review the related theory and work through a small
example to check the rule.
```

Exercise 134 Find and fix the error

Question

```
Requirement: The add method promises to RETURN the sum to its caller. Select the output
statement to replace; displaying alone does not return a value.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. FUNCTION add(a, b) RETURNS REAL
2. SET result = a + b
3. OUTPUT result
4. ENDFUNCTION
```

Model solution

```
Line 3 - Logic
RETURN result
The function promises a returned value. Displaying the result alone does not fulfil that
contract.
```

Exercise 135 Build or trace a solution

Question

Write a method returning the larger of two values. Include an early return in each branch. Work independently before comparing your answer.

Model solution

```
METHOD larger(a, b) RETURNS REAL
IF a &gt;= b THEN
RETURN a
ELSE
RETURN b
ENDIF
ENDMETHOD
BEGIN
SET result = larger(8, 5)
OUTPUT result
END
```

Expected behaviour:
larger(8,5) -> 8; larger(3,9) -> 9; larger(4,4) -> 4.

Review:
State the return type and parameters.
Make every possible branch return a value.
The caller stores the returned value before displaying it.

Exercise 136 Apply the concept

Question

Write a method that returns whether a number is even.

Model solution

```
METHOD isEven(number) RETURNS BOOLEAN
  RETURN number MOD 2 = 0
ENDMETHOD
```

Tests: 4 -> TRUE; 5 -> FALSE; 0 -> TRUE. RETURN communicates the Boolean result; OUTPUT alone would only display it.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 4 Passing arrays to methods

Exercise 137 Knowledge check 1

Question

Why might a method need count as well as the array?
A. Count may differ from capacity
B. Arrays cannot contain numbers
C. It removes the need for bounds

Model solution

A. Count may differ from capacity
The method may need to process only the meaningful portion of a partially filled array.

Exercise 138 Knowledge check 2

Question

Which count bound should an array method require?
A. 0 <= count <= capacity
B. count > capacity
C. count must be -1

Model solution

A. 0 <= count <= capacity
0 <= count <= capacity. Review the related theory and work through a small example to check the rule.

Exercise 139 Knowledge check 3

Question

Should array mutation assumptions be documented?
A. No
B. Only for sorted arrays
C. Yes

Model solution

C. Yes
Yes. Review the related theory and work through a small example to check the rule.

Exercise 140 Knowledge check 4

Question

When a C# array reference is passed by value, can elements be updated?
A. Only if the array is empty
B. Yes, the reference copy can refer to the same array
C. No, all elements are copied automatically

Model solution

B. Yes, the reference copy can refer to the same array
Yes, the reference copy can refer to the same array. Review the related theory and work through a small example to check the rule.

Exercise 141 Knowledge check 5

Question

For count=3, which indices are processed?
A. 0, 1, 2
B. 1, 2, 3, 4
C. 0, 1, 2, 3

Model solution

A. 0, 1, 2
0, 1, 2. Review the related theory and work through a small example to check the rule.

Exercise 142 Find and fix the error

Question

Requirement: Display count populated elements, starting at index 0. Assume 0 <= count <= array capacity.
Focused snippet: assume omitted declarations and input setup are supplied unless the task says otherwise.
Identify the faulty line, error category and correction.

```
1. METHOD displayValues(values, count)
2. FOR i = 0 TO count
3. OUTPUT values[i]
4. ENDFOR
5. ENDMETHOD
```

Model solution

Line 2 - Boundary
FOR i = 0 TO count - 1
A zero-based collection containing count values ends at count - 1.

Exercise 143 Build or trace a solution

Question

Pass an array and meaningful count to a method that returns their total. Work independently before comparing your answer.

Model solution

```
METHOD totalValues(values, count) RETURNS REAL
SET total = 0
FOR i = 0 TO count - 1
SET total = total + values[i]
ENDFOR
RETURN total
ENDMETHOD
BEGIN
SET result = totalValues(marks, 3)
OUTPUT result
END

Expected behaviour:
For marks=[10,20,30,999], count=3, output 60. The spare capacity is ignored.

Review:
Use count rather than assuming capacity equals meaningful data.
Visit 0 through count - 1.
Return the accumulated total to the caller.
```

Exercise 144 Apply the concept

Question

What preconditions should an array-processing method document?

Model solution

Document the element type, zero-based indexing convention, meaningful count, capacity, whether count may be zero and whether the method changes the caller’s elements. Require 0 <= count <= capacity and test those boundaries.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 4 Overloading and method contracts

Exercise 145 Knowledge check 1

Question

```
Which change can create a valid overload?
A. Change only the return type
B. Change the parameter types
C. Change only parameter names
```

Model solution

```
B. Change the parameter types
A distinct parameter signature can distinguish an overload.
```

Exercise 146 Knowledge check 2

Question

```
Do parameter names alone distinguish overloads?
A. Yes
B. Only when uppercase
C. No
```

Model solution

```
C. No
No. Review the related theory and work through a small example to check the rule.
```

Exercise 147 Knowledge check 3

Question

```
Can return type alone distinguish a C# overload?
A. Only when REAL
B. No
C. Yes
```

Model solution

```
B. No
No. Review the related theory and work through a small example to check the rule.
```

Exercise 148 Knowledge check 4

Question

```
Which pair is distinct?
A. sum(a,b) and sum(a,b,c)
B. sum(INTEGER a) and sum(INTEGER b)
C. Two methods with identical parameter types
```

Model solution

```
A. sum(a,b) and sum(a,b,c)
sum(a,b) and sum(a,b,c). Review the related theory and work through a small example to
check the rule.
```

Exercise 149 Knowledge check 5

Question

```
What should overloaded operations usually share?
A. Completely unrelated behaviour
B. No understandable purpose
C. A closely related responsibility
```

Model solution

```
C. A closely related responsibility
A closely related responsibility. Review the related theory and work through a small
example to check the rule.
```

Exercise 150 Find and fix the error

Question

```
Requirement: Create two distinct overloaded signatures. Parameter names and return type
alone cannot distinguish overloads.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. FUNCTION calculate(INTEGER a) RETURNS INTEGER
2. RETURN a
3. ENDFUNCTION
4. FUNCTION calculate(INTEGER b) RETURNS REAL
5. RETURN b
6. ENDFUNCTION
```

Model solution

```
Line 4 - Syntax
Change the second header to calculate(REAL b) RETURNS REAL
The original parameter types and count are identical. Change the parameter type or count
to create a distinct signature.
```

Exercise 151 Build or trace a solution

Question

```
Compare two signatures and identify the selected overload for two calls. Work
independently before comparing your answer.
```

Model solution

```
// METHOD display(INTEGER value)
// METHOD display(STRING value)
// CALL display(42) uses INTEGER.
// CALL display("42") uses STRING.

Expected behaviour:
42 is numeric; "42" is text. The parameter type distinguishes the signatures.

Review:
Compare parameter types, not parameter names.
Match each actual argument to the compatible signature.
Return type alone cannot distinguish an overload.
```

Exercise 152 Apply the concept

Question

```
Design two valid overloads for a total method using different parameter counts.
```

Model solution

```
total(REAL first, REAL second) and total(REAL first, REAL second, REAL third) are
distinct signatures. total(REAL a, REAL b) and total(REAL x, REAL y) are not distinct
merely because parameter names differ.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 5 Classes, objects and constructors

Exercise 153 Knowledge check 1

Question

```
Which is an object rather than a class?
A. The Learner type definition
B. One particular Learner instance
C. The STRING type
```

Model solution

```
B. One particular Learner instance
An object is a specific instance with its own state.
```

Exercise 154 Knowledge check 2

Question

```
What does a constructor normally establish?
A. The user’s browser type
B. An initial valid object state
C. Every object’s final report
```

Model solution

```
B. An initial valid object state
An initial valid object state. Review the related theory and work through a small example
 to check the rule.
```

Exercise 155 Knowledge check 3

Question

```
Can two objects share equal values yet be distinct?
A. Yes
B. No
C. Only if they are different classes
```

Model solution

```
A. Yes
Yes. Review the related theory and work through a small example to check the rule.
```

Exercise 156 Knowledge check 4

Question

```
What describes an attribute?
A. Only an external file
B. A loop terminator
C. Object state
```

Model solution

```
C. Object state
Object state. Review the related theory and work through a small example to check the
rule.
```

Exercise 157 Knowledge check 5

Question

```
What describes a method?
A. A number type
B. Behaviour associated with a class or module
C. Only the object’s colour
```

Model solution

```
B. Behaviour associated with a class or module
Behaviour associated with a class or module. Review the related theory and work through a
 small example to check the rule.
```

Exercise 158 Find and fix the error

Question

```
Requirement: Initialise the name field with the newName parameter supplied by the caller.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. CLASS Learner
2. PRIVATE name AS STRING
3. METHOD initialise(newName)
4. SET name = name
5. ENDMETHOD
6. ENDCLASS
```

Model solution

```
Line 4 - Logic
SET name = newName
The incoming value should initialise the attribute. Assigning name to itself ignores
newName.
```

Exercise 159 Build or trace a solution

Question

```
Model two Book objects created from the same class. Describe their independent state.
Work independently before comparing your answer.
```

Model solution

```
// CLASS Book
// - title : STRING
// - borrowed : BOOLEAN
// + borrow()
// + returnBook()
// bookA: title="Algorithms", borrowed=TRUE
// bookB: title="Databases", borrowed=FALSE

Expected behaviour:
Both objects share the Book definition but hold different attribute values.

Review:
Separate the type definition from its instances.
Give each instance its own state.
Use methods to express actions that belong to a book.
```

Exercise 160 Apply the concept

Question

```
Describe a constructor for Book that requires a title and starts with borrowed = FALSE.
```

Model solution

```
Book(newTitle) stores newTitle in title and initialises borrowed to FALSE. Validate that
the title is not empty. Two constructor calls create two distinct instances even if their
 titles are equal.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Unit 5 Encapsulation, inheritance and polymorphism

Exercise 161 Knowledge check 1

Question

```
A Course contains Learner objects. Which relationship is suggested?
A. Course is a Learner
B. Course has learners
C. Learner is a number
```

Model solution

```
B. Course has learners
Containment suggests has-a, not an inheritance relationship.
```

Exercise 162 Knowledge check 2

Question

```
What is encapsulation intended to protect?
A. Valid state through controlled access
B. Only variable spelling
C. Every class from having methods
```

Model solution

```
A. Valid state through controlled access
Valid state through controlled access. Review the related theory and work through a small
 example to check the rule.
```

Exercise 163 Knowledge check 3

Question

```
Which phrase indicates inheritance?
A. Has-a in every case
B. Prints-a
C. Is-a
```

Model solution

```
C. Is-a
Is-a. Review the related theory and work through a small example to check the rule.
```

Exercise 164 Knowledge check 4

Question

```
What is overriding?
A. Creating an unrelated class variable
B. Specialising an inherited operation with the same contract
C. Changing only a parameter name
```

Model solution

```
B. Specialising an inherited operation with the same contract
Specialising an inherited operation with the same contract. Review the related theory and
 work through a small example to check the rule.
```

Exercise 165 Knowledge check 5

Question

```
What enables runtime polymorphic behaviour?
A. A common abstraction with specialised implementations
B. Sorting the object names
C. Making every attribute public
```

Model solution

```
A. A common abstraction with specialised implementations
A common abstraction with specialised implementations. Review the related theory and work
 through a small example to check the rule.
```

Exercise 166 Find and fix the error

Question

```
Requirement: Protect balance so callers cannot bypass controlled deposit rules. Assume
the account balance has already been initialised.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. CLASS Account
2. PUBLIC balance AS REAL
3. METHOD deposit(amount)
4. IF amount &gt; 0 THEN
5. SET balance = balance + amount
6. ENDIF
7. ENDMETHOD
8. ENDCLASS
```

Model solution

Line 2 - Design
PRIVATE balance AS REAL, with controlled access methods
Unrestricted public balance allows callers to bypass the deposit rules. Encapsulation controls updates through an appropriate interface.

Exercise 167 Build or trace a solution

Question

Compare inheritance and containment in a school model. Work independently before comparing your answer.

Model solution

```
// Person is a general type.
// Learner is a Person.
// Course has Learners.
// A Course is not a Learner.
```

Expected behaviour:
Use inheritance for the justified Learner-Person is-a relationship and association for Course-Learner.

Review:
Ask whether the specialised type fulfils the general contract.
Use has-a for a class containing or referring to other objects.
Keep private state protected by appropriate operations.

Exercise 168 Apply the concept

Question

Explain polymorphism with Shape, Circle and Rectangle without confusing it with overloading.

Model solution

A Shape reference can refer to a Circle or Rectangle. Each overrides area() with its own implementation. The call uses the same operation signature; runtime object type determines the behaviour. Overloading instead distinguishes different parameter signatures.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.

Unit 5 Class diagrams and class organisation

Exercise 169 Knowledge check 1

Question

```
In a basic UML class diagram, what does - indicate?
A. Public visibility
B. Private visibility
C. An arithmetic error
```

Model solution

```
B. Private visibility
A minus prefix denotes private visibility; a plus prefix denotes public visibility.
```

Exercise 170 Knowledge check 2

Question

```
What does + indicate in a basic UML class diagram?
A. Private visibility
B. An addition instruction to execute
C. Public visibility
```

Model solution

```
C. Public visibility
Public visibility. Review the related theory and work through a small example to check
the rule.
```

Exercise 171 Knowledge check 3

Question

```
What does 0..* indicate?
A. A negative array index
B. Zero or more related objects
C. Exactly one object
```

Model solution

```
B. Zero or more related objects
Zero or more related objects. Review the related theory and work through a small example
to check the rule.
```

Exercise 172 Knowledge check 4

Question

```
Where does an inheritance triangle point?
A. The general superclass
B. The specialised subclass
C. Both directions simultaneously
```

Model solution

```
A. The general superclass
The general superclass. Review the related theory and work through a small example to
check the rule.
```

Exercise 173 Knowledge check 5

Question

```
Which diagram fits a class’s attributes and operations?
A. A procedural call hierarchy only
B. A loop trace table only
C. Class diagram
```

Model solution

```
C. Class diagram
Class diagram. Review the related theory and work through a small example to check the
rule.
```

Exercise 174 Find and fix the error

Question

```
Requirement: Draw inheritance from SavingsAccount to its superclass Account. Identify the
 direction of the hollow triangle.
Focused snippet: assume omitted declarations and input setup are supplied unless the task
 says otherwise.
Identify the faulty line, error category and correction.
1. Class diagram: SavingsAccount inherits Account
2. Inheritance triangle points to SavingsAccount
```

Model solution

```
Line 2 - Design
Point the hollow triangle to Account
The inheritance triangle points toward the more general superclass, Account.
```

Exercise 175 Build or trace a solution

Question

Describe a Library associated with zero or more Books and its public borrow operation.
Work independently before comparing your answer.

Model solution

```
// Library
// - name : STRING
// + borrow(book : Book) : BOOLEAN
// Book
// - title : STRING
// Association: Library 1 -- 0..* Book

Expected behaviour:
The library has a private name; borrow is public and returns a Boolean. Multiplicity 0..*
 permits no books or many.

Review:
Read the class name, attributes and operations separately.
Interpret visibility and return types.
Explain the association and its multiplicity without claiming an execution order.
```

Exercise 176 Apply the concept

Question

Describe the direction of the inheritance triangle between SavingsAccount and Account.

Model solution

```
Draw a solid line from SavingsAccount to Account with a hollow triangle pointing at
Account, the general type. A procedural hierarchy chart is a different diagram and should
 not be substituted for a class diagram.

Review:
Check that your answer addresses every part of the question.
State assumptions and relevant boundary cases.
Equivalent correct solutions may use different names or structure.
```

Task library Methods

Exercise 177 Return the larger value

Question

Write Maximum(first, second) to return the larger of two integers. Return either when equal. Call it with (17, 9) and (8, 8).

Model solution

```
METHOD Maximum(first, second) RETURNS INTEGER
  IF first &gt;= second THEN
    RETURN first
  ELSE
    RETURN second
  ENDIF
ENDMETHOD
BEGIN
  OUTPUT Maximum(17, 9)
  OUTPUT Maximum(8, 8)
END
```

Check your result: 17 and 8.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 178 A method that counts

Question

Write a method DisplayNumbers() that displays 1 to 5 using WHILE. Call it from the main program.

Model solution

```
METHOD DisplayNumbers()
  SET number = 1
  WHILE number &lt;= 5 DO
    OUTPUT number
    SET number = number + 1
  ENDWHILE
ENDMETHOD
BEGIN
  CALL DisplayNumbers()
END
```

Check your result: 1, 2, 3, 4, 5. The counter reaches 6 before the loop ends.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 179 Rectangle area

Question

Write RectangleArea(length, width) to return an area. Assume non-negative dimensions.
Show calls for (6, 4) and (0, 4).

Model solution

```
METHOD RectangleArea(length, width) RETURNS REAL
  RETURN length * width
ENDMETHOD
BEGIN
  OUTPUT RectangleArea(6, 4)
  OUTPUT RectangleArea(0, 4)
END
```

Check your result: 24 and 0.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 180 Input and average five marks

Question

Write a method that inputs exactly five marks using FOR and returns their average. Call it and display the returned value. Assume valid marks.

Model solution

```
METHOD ReadAverage() RETURNS REAL
  SET total = 0
  FOR i = 1 TO 5
    INPUT mark
    SET total = total + mark
  ENDFOR
  RETURN total / 5.0
ENDMETHOD
BEGIN
  OUTPUT ReadAverage()
END
```

Check your result: For 50, 60, 70, 80, 90 the average is 70. Initialise total once before the loop.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 181 RETURN or OUTPUT?

Question

Explain RETURN versus OUTPUT. Write Square(number), then display Square(6).

Model solution

```
METHOD Square(number) RETURNS INTEGER
  RETURN number * number
ENDMETHOD
BEGIN
  SET result = Square(6)
  OUTPUT result
END
```

Check your result: 36. RETURN supplies a value to the caller; OUTPUT displays it.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 182 Average through parameters

Question

Write CalculateAverage(a, b, c) to return the average of three REAL marks. Test 60, 75 and 90.

Model solution

```
METHOD CalculateAverage(a, b, c) RETURNS REAL
  RETURN (a + b + c) / 3.0
ENDMETHOD
BEGIN
  OUTPUT CalculateAverage(60, 75, 90)
END
```

Check your result: 75. Use parentheses so addition happens before division.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 183 A Boolean returning method

Question

Write HasPassed(mark) returning TRUE for marks of at least 50. Use it in an IF for 48.
Assume valid marks.

Model solution

```
METHOD HasPassed(mark) RETURNS BOOLEAN
  RETURN mark &gt;= 50
ENDMETHOD
BEGIN
  IF HasPassed(48) THEN
    OUTPUT "Passed"
  ELSE
    OUTPUT "Failed"
  ENDIF
END
```

Check your result: Failed. Check marks 49, 50 and 51 to test the boundary.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Exercise 184 Return a factorial

Question

Write Factorial(number) with a FOR loop. Assume a non-negative integer small enough to avoid overflow. Explain the case number = 0.

Model solution

```
METHOD Factorial(number) RETURNS INTEGER
  SET product = 1
  FOR counter = 1 TO number
    SET product = product * counter
  ENDFOR
  RETURN product
ENDMETHOD
BEGIN
  OUTPUT Factorial(4)
  OUTPUT Factorial(0)
END
```

Check your result: 24 and 1. The FOR loop has no iterations for 0.

Review:
Use METHOD or MODULE with a matching end.
Check the parameters, return value and call.
Trace normal, boundary and equal-value cases where relevant.

Task library Overloading

Exercise 185 Overload by parameter count

Question

Create two Add methods: one accepts two integers, the other three. Show calls and expected outputs.

Model solution

```
METHOD Add(a AS INTEGER, b AS INTEGER) RETURNS INTEGER
  RETURN a + b
ENDMETHOD
METHOD Add(a AS INTEGER, b AS INTEGER, c AS INTEGER) RETURNS INTEGER
  RETURN a + b + c
ENDMETHOD
```

Add(4, 6) returns 10. Add(4, 6, 2) returns 12.

Review:
Differentiate the parameter count or types.
State the selected signature for each call.
Overload exercises are for written practice; duplicate method names are not supported by the diagram lab.

Exercise 186 Overload by parameter type

Question

Write Multiply for two INTEGER arguments and for two REAL arguments. Explain how the caller selects a method.

Model solution

```
METHOD Multiply(a AS INTEGER, b AS INTEGER) RETURNS INTEGER
  RETURN a * b
ENDMETHOD
METHOD Multiply(a AS REAL, b AS REAL) RETURNS REAL
  RETURN a * b
ENDMETHOD
```

Multiply(3, 4) returns 12. Multiply(2.5, 4.0) returns 10.0. Argument types select the overload.

Review:
Differentiate the parameter count or types.
State the selected signature for each call.
Overload exercises are for written practice; duplicate method names are not supported by the diagram lab.

Exercise 187 One name, two shapes

Question

Write CalculateArea for a square and a rectangle using overloaded methods. Explain the distinguishing parameter lists.

Model solution

```
METHOD CalculateArea(side AS REAL) RETURNS REAL
  RETURN side * side
ENDMETHOD
METHOD CalculateArea(length AS REAL, width AS REAL) RETURNS REAL
  RETURN length * width
ENDMETHOD
```

CalculateArea(5.0) returns 25.0. CalculateArea(6.0, 4.0) returns 24.0.

Review:
Differentiate the parameter count or types.
State the selected signature for each call.
Overload exercises are for written practice; duplicate method names are not supported by the diagram lab.

Exercise 188 Trace nested calls

Question

Calculate(a, b) returns a + b. Calculate(a, b, c) returns a * b * c. Trace Calculate(2, 3), Calculate(2, 3, 4) and Calculate(Calculate(1, 2), 5). Explain each selection.

Model solution

Outputs: 5, 24, 8.
The first call has two arguments. The second has three. In the nested call the inner result is 3, so the outer two-argument call is Calculate(3, 5).

Review:
Differentiate the parameter count or types.
State the selected signature for each call.
Overload exercises are for written practice; duplicate method names are not supported by the diagram lab.

Exercise 189 Repair an invalid overload

Question

GetPrice(price AS REAL) RETURNS REAL and GetPrice(price AS REAL) RETURNS INTEGER have identical parameter lists. Explain the problem. Design a discount version with a valid overload.

Model solution

Changing only the return type does not distinguish calls. Add a second parameter:

```
METHOD GetPrice(price AS REAL) RETURNS REAL
  RETURN price
ENDMETHOD
METHOD GetPrice(price AS REAL, discountPercent AS REAL) RETURNS REAL
  RETURN price - price * discountPercent / 100.0
ENDMETHOD
```

Assume a non-negative price and discount 0 to 100. GetPrice(200.0, 10.0) returns 180.0.

Review:
Differentiate the parameter count or types.
State the selected signature for each call.
Overload exercises are for written practice; duplicate method names are not supported by the diagram lab.

Task library Loops

Exercise 190 Count students who passed

Question

Input a positive student count and each mark. Count marks at least 50. Write a FOR solution, then rewrite it using WHILE. Assume valid input.

Model solution

```
BEGIN
  INPUT n
  SET count = 0
  FOR i = 1 TO n
    INPUT mark
    IF mark &gt;= 50 THEN
      SET count = count + 1
    ENDIF
  ENDFOR
  OUTPUT count
END

Equivalent WHILE solution:
BEGIN
  INPUT n
  SET count = 0
  SET i = 1
  WHILE i &lt;= n DO
    INPUT mark
    IF mark &gt;= 50 THEN
      SET count = count + 1
    ENDIF
    SET i = i + 1
  ENDWHILE
  OUTPUT count
END

For 45, 50, 82: 2 passed.

Review:
Initialise count before the loop.
Use identical bounds in both versions.
Increment the WHILE counter exactly once per iteration.
```

Exercise 191 Count even numbers

Question

Input a positive number count and each integer. Count the even integers. Write a FOR solution, then rewrite it using WHILE. Assume valid input.

Model solution

```
BEGIN
  INPUT n
  SET count = 0
  FOR i = 1 TO n
    INPUT number
    IF number MOD 2 = 0 THEN
      SET count = count + 1
    ENDIF
  ENDFOR
  OUTPUT count
END

Equivalent WHILE solution:
BEGIN
  INPUT n
  SET count = 0
  SET i = 1
  WHILE i &lt;= n DO
    INPUT number
    IF number MOD 2 = 0 THEN
      SET count = count + 1
    ENDIF
    SET i = i + 1
  ENDWHILE
  OUTPUT count
END

For -2, 0, 3, 8: 3 are even.

Review:
Initialise count before the loop.
Use identical bounds in both versions.
Increment the WHILE counter exactly once per iteration.
```

Exercise 192 Count salaries above a threshold

Question

```
Input a positive employee count and each salary. Count salaries strictly above R15 000.
Write a FOR solution, then rewrite it using WHILE. Assume valid input.
```

Model solution

```
BEGIN
  INPUT n
  SET count = 0
  FOR i = 1 TO n
    INPUT salary
    IF salary &gt; 15000 THEN
      SET count = count + 1
    ENDIF
  ENDFOR
  OUTPUT count
END

Equivalent WHILE solution:
BEGIN
  INPUT n
  SET count = 0
  SET i = 1
  WHILE i &lt;= n DO
    INPUT salary
    IF salary &gt; 15000 THEN
      SET count = count + 1
    ENDIF
    SET i = i + 1
  ENDWHILE
  OUTPUT count
END

For 15000, 15001, 22000: 2 qualify.

Review:
Initialise count before the loop.
Use identical bounds in both versions.
Increment the WHILE counter exactly once per iteration.
```

Exercise 193 Calculate a class average

Question

```
Input a student count n. If n is positive, read n marks and display their average. Handle
 n = 0. Write FOR and WHILE versions.
```

Model solution

```
BEGIN
  INPUT n
  IF n &gt; 0 THEN
    SET total = 0
    FOR i = 1 TO n
      INPUT mark
      SET total = total + mark
    ENDFOR
    OUTPUT total / n
  ELSE
    OUTPUT "No students"
  ENDIF
END

WHILE conversion: set i = 1 before the loop, use WHILE i &lt;= n DO, keep the same body, add
 SET i = i + 1, then ENDWHILE. The average remains after the loop.

Review:
Avoid division by zero.
Accumulate every mark once.
For 50, 70, 90 the average is 70.
```

Exercise 194 Positive, negative or zero?

Question

```
Read n integers for a positive n. Count positive and negative values separately. Zero
belongs to neither count. Give FOR and WHILE versions.
```

Model solution

```
BEGIN
  INPUT n
  SET positive = 0
  SET negative = 0
  FOR i = 1 TO n
    INPUT value
    IF value &gt; 0 THEN
      SET positive = positive + 1
    ELSEIF value &lt; 0 THEN
      SET negative = negative + 1
    ENDIF
  ENDFOR
  OUTPUT positive, negative
END

WHILE conversion: initialise i to 1, test i &lt;= n, execute the same body and increment i
each time.
For -4, 0, 3, 7, -1: positive = 2, negative = 2.

Review:
Use two separate counters.
Do not classify zero as negative.
Keep input inside the loop.
```

Task library Parallel arrays

Exercise 195 Capture names and marks

Question

Use parallel arrays to input names and marks for five students. Then display each name with its corresponding mark. Use zero-based indices.

Model solution

```
BEGIN
  DECLARE names[5] AS STRING
  DECLARE marks[5] AS REAL
  FOR i = 0 TO 4
    INPUT names[i]
    INPUT marks[i]
  ENDFOR
  FOR i = 0 TO 4
    OUTPUT names[i], marks[i]
  ENDFOR
END

Review:
Both arrays have five elements.
The same index identifies one student in both arrays.
The valid indices are 0 through 4.
```

Exercise 196 Filter employee salaries

Question

Input names and salaries of four employees into parallel arrays. Display only employees earning more than R20 000.

Model solution

```
BEGIN
  DECLARE names[4] AS STRING
  DECLARE salaries[4] AS REAL
  FOR i = 0 TO 3
    INPUT names[i]
    INPUT salaries[i]
  ENDFOR
  FOR i = 0 TO 3
    IF salaries[i] &gt; 20000 THEN
      OUTPUT names[i], salaries[i]
    ENDIF
  ENDFOR
END

Review:
Use indices 0 through 3.
R20 000 does not qualify; R20 001 does.
Display the name and salary from the same index.
```

Exercise 197 Show all passing students

Question

```
Given names [Lebo, Thabo, Naledi, Peter, Maria] and marks [65, 48, 72, 55, 81], display
all names and marks with a mark of at least 50. Give a FOR solution and explain its WHILE
 conversion.
```

Model solution

```
BEGIN
  SET names = ["Lebo", "Thabo", "Naledi", "Peter", "Maria"]
  SET marks = [65, 48, 72, 55, 81]
  FOR i = 0 TO 4
    IF marks[i] &gt;= 50 THEN
      OUTPUT names[i], marks[i]
    ENDIF
  ENDFOR
END

WHILE: initialise i = 0, loop while i &lt; 5, keep the IF body and increment i.
Output: Lebo 65; Naledi 72; Peter 55; Maria 81.

Review:
Visit all five indices.
Include exactly 50.
Preserve the name-mark pairing.
```

Exercise 198 Search by student name

Question

Use names ["Lebo", "Thabo", "Naledi", "Peter", "Maria"] and marks [65, 48, 72, 55, 81]. Ask for a name. Display its paired value when found, otherwise display Not found. Use a WHILE loop; assume unique, case-sensitive names.

Model solution

```
BEGIN
  SET names = ["Lebo", "Thabo", "Naledi", "Peter", "Maria"]
  SET marks = [65, 48, 72, 55, 81]
  INPUT target
  SET foundAt = -1
  SET i = 0
  WHILE i &lt; 5 DO
    IF names[i] = target THEN
      SET foundAt = i
    ENDIF
    SET i = i + 1
  ENDWHILE
  IF foundAt &lt;&gt; -1 THEN
    OUTPUT names[foundAt], marks[foundAt]
  ELSE
    OUTPUT "Not found"
  ENDIF
END

Review:
Initialise foundAt to an invalid index.
Never read an array at index -1.
Test an existing name and a missing name.
```

Exercise 199 Find a product price

Question

Use names ["Keyboard", "Mouse", "Monitor", "Printer", "Laptop"] and prices [250, 150, 2500, 1800, 9500]. Ask for a name. Display its paired value when found, otherwise display Not found. Use a WHILE loop; assume unique, case-sensitive names.

Model solution

```
BEGIN
  SET names = ["Keyboard", "Mouse", "Monitor", "Printer", "Laptop"]
  SET prices = [250, 150, 2500, 1800, 9500]
  INPUT target
  SET foundAt = -1
  SET i = 0
  WHILE i &lt; 5 DO
    IF names[i] = target THEN
      SET foundAt = i
    ENDIF
    SET i = i + 1
  ENDWHILE
  IF foundAt &lt;&gt; -1 THEN
    OUTPUT names[foundAt], prices[foundAt]
  ELSE
    OUTPUT "Not found"
  ENDIF
END

Review:
Initialise foundAt to an invalid index.
Never read an array at index -1.
Test an existing name and a missing name.
```

Exercise 200 Find the top mark

Question

Use the five student names and marks [65, 48, 72, 55, 81]. Find the highest mark and its matching name. Keep the first student if there is a tie.

Model solution

```
BEGIN
  SET names = ["Lebo", "Thabo", "Naledi", "Peter", "Maria"]
  SET marks = [65, 48, 72, 55, 81]
  SET best = 0
  FOR i = 1 TO 4
    IF marks[i] &gt; marks[best] THEN
      SET best = i
    ENDIF
  ENDFOR
  OUTPUT names[best], marks[best]
END

Result: Maria, 81.

Review:
Initialise the best index to an existing element.
Use &gt; to preserve the first occurrence of a tie.
Use best to access both arrays.
```

Exercise 201 A complete results report

Question

Use names [John, Mary, David, Sarah, Peter] and marks [45, 78, 66, 82, 39]. Display every pair, count passes and failures (pass >= 50), and show the top student. Assume a non-empty class.

Model solution

```
BEGIN
  SET names = ["John", "Mary", "David", "Sarah", "Peter"]
  SET marks = [45, 78, 66, 82, 39]
  SET passed = 0
  SET failed = 0
  SET best = 0
  FOR i = 0 TO 4
    OUTPUT names[i], marks[i]
    IF marks[i] &gt;= 50 THEN
      SET passed = passed + 1
    ELSE
      SET failed = failed + 1
    ENDIF
    IF marks[i] &gt; marks[best] THEN
      SET best = i
    ENDIF
  ENDFOR
  OUTPUT passed, failed
  OUTPUT names[best], marks[best]
END

Review:
Expected: 3 passed, 2 failed, Sarah 82.
Check that passed + failed equals 5.
Initialise counters outside the loop.
```

Task library Revision

Exercise 202 Build a salary flowchart

Question

```
For a practice sales report, input a basic salary, sales total and commission percentage.
 Calculate salary = basic + sales * percentage / 100. Write pseudocode and create a
flowchart. Test basic 5000, sales 20000 and rate 5.
```

Model solution

```
BEGIN
  INPUT basic
  INPUT sales
  INPUT rate
  SET salary = basic + sales * rate / 100.0
  OUTPUT salary
END

Review:
Expected salary: R6 000.
Use a parallelogram for input/output.
Use a process rectangle for the calculation.
```

Exercise 203 Stop on a sentinel

Question

```
Read numbers while they are greater than zero. Display three times each positive input.
Stop when zero or a negative number is entered, without displaying its triple.
```

Model solution

```
BEGIN
  INPUT number
  WHILE number &amp;gt; 0 DO
    OUTPUT number * 3
    INPUT number
  ENDWHILE
END

Review:
Include the first input before the loop.
Read a new value each iteration.
For 2, 5, 0: display 6 and 15 only.
```

Exercise 204 Explain Boolean decisions

Question

A fictional club offers a discount to members aged 65 or older. Write the Boolean condition. Explain AND, OR and NOT using this scenario. State the outcome for a member aged 64 and a non-member aged 70.

Model solution

Eligible: isMember AND age >= 65.
AND requires both conditions. OR would accept either condition, so it would not implement this rule. NOT reverses a Boolean result; NOT isMember is true for a non-member.
Both specified people are ineligible. A member aged 65 is eligible.

Review:
Check age 65 as the inclusive boundary.
Explain why OR changes the policy.
Use Boolean values rather than quoted strings for isMember.

Exercise 205 Return a practice contribution

Question

For a fictional exercise only, a company uses a contribution rate of 3%. Write Contribution(salary, rate) returning salary * rate / 100. Call it for salary 10000 and rate 3. This is a programming example, not a real payroll rule.

Model solution

```
METHOD Contribution(salary, rate) RETURNS REAL
  RETURN salary * rate / 100.0
ENDMETHOD
BEGIN
  OUTPUT Contribution(10000, 3)
END
```

Review:
Expected: 300.
The rate is passed as a parameter.
RETURN makes the result available to the caller.

Exercise 206 Plan before coding

Question

In a fictional leave exercise, staff earn 1.5 days per month worked. Assume monthsRemaining is already known. Identify input, processing and output, then give two test cases.

Model solution

```
Input: employee name and monthsRemaining.
Processing: leaveDays = monthsRemaining * 1.5.
Output: employee name and leaveDays.
Tests: 4 months -&gt; 6 days; 0 months -&gt; 0 days.
Validate monthsRemaining as an integer from 0 to 12 if validation is required.

Review:
Identify the formula separately from inputs.
Include units in the output.
Test zero months.
```

Task library OOP

Exercise 207 A class that prints numbers

Question

Design NumberPrinter with DisplayNumbers() using FOR to display 1 to 10. Show an object creation and method call.

Model solution

```
CLASS NumberPrinter
  METHOD DisplayNumbers()
    FOR i = 1 TO 10
      OUTPUT i
    ENDFOR
  ENDMETHOD
ENDCLASS
BEGIN
  SET printer = NEW NumberPrinter()
  CALL printer.DisplayNumbers()
END

Review:
Separate the class definition from object use.
Check member visibility and loop bounds.
Class syntax is written practice; the flowchart converter does not parse classes.
```

Exercise 208 Even numbers through an object

Question

Design EvenPrinter with a WHILE method displaying even numbers from 2 to 20. Create an object and call it.

Model solution

```
CLASS EvenPrinter
  METHOD DisplayEven()
    SET number = 2
    WHILE number &amp;lt;= 20 DO
      OUTPUT number
      SET number = number + 2
    ENDWHILE
  ENDMETHOD
ENDCLASS
BEGIN
  SET printer = NEW EvenPrinter()
  CALL printer.DisplayEven()
END

Review:
Separate the class definition from object use.
Check member visibility and loop bounds.
Class syntax is written practice; the flowchart converter does not parse classes.
```

Exercise 209 A class with an array

Question

```
Design MarkBook with a private marks array containing 60, 75 and 90. A public method must
 display all marks with FOR. Explain encapsulation.
```

Model solution

```
CLASS MarkBook
  PRIVATE marks = [60, 75, 90]
  PUBLIC METHOD DisplayMarks()
    FOR i = 0 TO 2
      OUTPUT marks[i]
    ENDFOR
  ENDMETHOD
ENDCLASS

Encapsulation keeps marks private and exposes a public operation. A MarkBook object can
call DisplayMarks().

Review:
Separate the class definition from object use.
Check member visibility and loop bounds.
Class syntax is written practice; the flowchart converter does not parse classes.
```

Exercise 210 Return a total from a class

Question

```
Design NumberStore with values [4, 6, 10]. Use a WHILE method Total() returning the sum.
Explain the counter and accumulator.
```

Model solution

```
CLASS NumberStore
  PRIVATE values = [4, 6, 10]
  PUBLIC METHOD Total() RETURNS INTEGER
    SET total = 0
    SET i = 0
    WHILE i &amp;lt; 3 DO
      SET total = total + values[i]
      SET i = i + 1
    ENDWHILE
    RETURN total
  ENDMETHOD
ENDCLASS
```

i is the index counter. total is the accumulator. The returned result is 20.

Review:
Separate the class definition from object use.
Check member visibility and loop bounds.
Class syntax is written practice; the flowchart converter does not parse classes.

Exercise 211 Model a person and student

Question

Design Person with a protected address and Student inheriting from Person with number, firstName and surname. Explain protected versus private. Sketch a class relationship.

Model solution

```
CLASS Person
  PROTECTED address AS STRING
ENDCLASS
CLASS Student INHERITS Person
  PRIVATE number AS STRING
  PRIVATE firstName AS STRING
  PRIVATE surname AS STRING
ENDCLASS
```

Student is a Person. Draw a generalisation line from Student towards Person with a hollow triangle at Person. Protected allows direct subclass access; private restricts direct access to the declaring class. Prefer controlled methods when exposing data.

Review:
Separate the class definition from object use.
Check member visibility and loop bounds.
Class syntax is written practice; the flowchart converter does not parse classes.

Task library Arrays

Exercise 212 Visit every array element

Question

Declare an INTEGER array of five elements. Input each element, then display every value with its zero-based index.

Model solution

```
BEGIN
  DECLARE values[5] AS INTEGER
  FOR i = 0 TO 4
    INPUT values[i]
  ENDFOR
  FOR i = 0 TO 4
    OUTPUT i, values[i]
  ENDFOR
END
```

Review:
The indices are 0, 1, 2, 3 and 4.
Input fills each element before it is displayed.
Use one array rather than separate variables.

Exercise 213 Array total and average

Question

Given values [12, 8, 20, 10], compute their total and average using a loop. Explain the accumulator.

Model solution

```
BEGIN
  SET values = [12, 8, 20, 10]
  SET total = 0
  FOR i = 0 TO 3
    SET total = total + values[i]
  ENDFOR
  OUTPUT total, total / 4.0
END
```

Review:
The total is 50 and the average is 12.5.
Initialise total once before the loop.
For an unknown length, check it is positive before division.

Exercise 214 Maximum in a single array

Question

Find the maximum of [-8, -3, -12, -5]. Initialise from an array element so the solution works for negative values.

Model solution

```
BEGIN
  SET values = [-8, -3, -12, -5]
  SET maximum = values[0]
  FOR i = 1 TO 3
    IF values[i] &gt; maximum THEN
      SET maximum = values[i]
    ENDIF
  ENDFOR
  OUTPUT maximum
END

Review:
Expected maximum: -3.
Starting at zero would give an incorrect result.
Assume a non-empty array.
```

Exercise 215 Find every matching index

Question

Search [4, 7, 4, 9, 4] for an input target. Display every matching index and the total match count.

Model solution

```
BEGIN
  SET values = [4, 7, 4, 9, 4]
  INPUT target
  SET count = 0
  FOR i = 0 TO 4
    IF values[i] = target THEN
      OUTPUT i
      SET count = count + 1
    ENDIF
  ENDFOR
  OUTPUT count
END

Review:
For target 4: indices 0, 2, 4 and count 3.
A missing target gives count 0.
Continue searching after the first match.
```

Exercise 216 Reverse an array in place

Question

Reverse [2, 4, 6, 8, 10] in place using a left and right index. Use a temporary variable when swapping.

Model solution

```
BEGIN
  SET values = [2, 4, 6, 8, 10]
  SET left = 0
  SET right = 4
  WHILE left &lt; right DO
    SET temp = values[left]
    SET values[left] = values[right]
    SET values[right] = temp
    SET left = left + 1
    SET right = right - 1
  ENDWHILE
  OUTPUT values
END

Review:
Expected: [10, 8, 6, 4, 2].
Stop when the indices meet or cross.
The middle element remains in place.
```

Exercise 217 Traverse a two-dimensional array

Question

Input a 2 by 3 INTEGER matrix. Use nested loops to calculate and display the sum of each row. State valid row and column indices.

Model solution

```
BEGIN
  DECLARE matrix[2][3] AS INTEGER
  FOR row = 0 TO 1
    SET rowTotal = 0
    FOR col = 0 TO 2
      INPUT matrix[row][col]
      SET rowTotal = rowTotal + matrix[row][col]
    ENDFOR
    OUTPUT row, rowTotal
  ENDFOR
END

Review:
Rows are 0 to 1 and columns 0 to 2.
Reset rowTotal at the start of each row.
Rows [1, 2, 3] and [4, 5, 6] give 6 and 15.
```

Task library IF / ELSE

Exercise 218 IF ELSE pass decision

Question

Input a valid mark from 0 to 100. Display Pass if it is at least 50, otherwise display Revise.

Model solution

```
BEGIN
  INPUT mark
  IF mark &gt;= 50 THEN
    OUTPUT "Pass"
  ELSE
    OUTPUT "Revise"
  ENDIF
END

Review:
49 gives Revise.
50 gives Pass.
Use ELSE for the alternative path.
```

Exercise 219 Odd or even

Question

Input an integer. Use IF ELSE and MOD to report whether it is even or odd.

Model solution

```
BEGIN
  INPUT number
  IF number MOD 2 = 0 THEN
    OUTPUT "Even"
  ELSE
    OUTPUT "Odd"
  ENDIF
END

Review:
0 is even.
8 is even and 7 is odd.
MOD returns the remainder.
```

Exercise 220 Validate a mark range

Question

Read a mark. Display Valid only when the mark lies between 0 and 100 inclusive, otherwise display Invalid. Use AND.

Model solution

```
BEGIN
  INPUT mark
  IF mark &gt;= 0 AND mark &lt;= 100 THEN
    OUTPUT "Valid"
  ELSE
    OUTPUT "Invalid"
  ENDIF
END

Review:
0 and 100 are valid.
-1 and 101 are invalid.
Both bounds must hold at the same time.
```

Exercise 221 An ELSEIF grade ladder

Question

Assume a valid mark. Display Distinction for 75 or above, Pass for 50 to 74, and Revise below 50. Use IF ELSEIF ELSE.

Model solution

```
BEGIN
  INPUT mark
  IF mark &gt;= 75 THEN
    OUTPUT "Distinction"
  ELSEIF mark &gt;= 50 THEN
    OUTPUT "Pass"
  ELSE
    OUTPUT "Revise"
  ENDIF
END

Review:
Test 49, 50, 74 and 75.
The first true branch runs.
Check the highest threshold first.
```

Exercise 222 Nested eligibility decisions

Question

A fictional activity requires age at least 16 and guardian approval. Use nested IF statements to display Too young, Approval required or Eligible. Assume age is valid and approval is Boolean.

Model solution

```
BEGIN
  INPUT age
  INPUT approved
  IF age &gt;= 16 THEN
    IF approved = TRUE THEN
      OUTPUT "Eligible"
    ELSE
      OUTPUT "Approval required"
    ENDIF
  ELSE
    OUTPUT "Too young"
  ENDIF
END

Review:
Aged 15: Too young.
Aged 16 and FALSE: Approval required.
Aged 16 and TRUE: Eligible.
```

Exercise 223 Calculate a conditional discount

Question

Read a non-negative total and a Boolean membership value. Members spending at least 500 receive 10% off. Everyone else pays the original total. Display the amount due.

Model solution

```
BEGIN
  INPUT total
  INPUT isMember
  IF isMember AND total &gt;= 500 THEN
    SET due = total * 0.9
  ELSE
    SET due = total
  ENDIF
  OUTPUT due
END

Review:
Member spending 500 pays 450.
Non-member spending 500 pays 500.
Set due on both paths before OUTPUT.
```

Task library SWITCH / CASE

Exercise 224 SWITCH menu

Question

Input menu option 1, 2 or 3. Display Add, View or Exit. Other values must display Invalid option. In this pseudocode dialect branches do not fall through and BREAK is unnecessary.

Model solution

```
BEGIN
  INPUT option
  SWITCH option
    CASE 1:
      OUTPUT "Add"
    CASE 2:
      OUTPUT "View"
    CASE 3:
      OUTPUT "Exit"
    DEFAULT:
      OUTPUT "Invalid option"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```

Exercise 225 Day name lookup

Question

Input a number from 1 to 3 to select Monday, Tuesday or Wednesday. Use DEFAULT for unsupported values. In this pseudocode dialect branches do not fall through and BREAK is unnecessary.

Model solution

```
BEGIN
  INPUT day
  SWITCH day
    CASE 1:
      OUTPUT "Monday"
    CASE 2:
      OUTPUT "Tuesday"
    CASE 3:
      OUTPUT "Wednesday"
    DEFAULT:
      OUTPUT "Unsupported day"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```

Exercise 226 Text values in SWITCH

Question

```
Input size S, M or L. Display Small, Medium or Large. Use case-sensitive exact matches
and handle unsupported sizes. In this pseudocode dialect branches do not fall through and
 BREAK is unnecessary.
```

Model solution

```
BEGIN
  INPUT size
  SWITCH size
    CASE "S":
      OUTPUT "Small"
    CASE "M":
      OUTPUT "Medium"
    CASE "L":
      OUTPUT "Large"
    DEFAULT:
      OUTPUT "Unknown size"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```

Exercise 227 A small calculator

Question

```
Read two numbers and an operator + or *. Use SWITCH to display their sum or product.
Reject other operators. In this pseudocode dialect branches do not fall through and BREAK
 is unnecessary.
```

Model solution

```
BEGIN
  INPUT a
  INPUT b
  INPUT operator
  SWITCH operator
    CASE "+":
      OUTPUT a + b
    CASE "*":
      OUTPUT a * b
    DEFAULT:
      OUTPUT "Unsupported operator"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```

Exercise 228 Select a delivery charge

Question

```
Input zone 1, 2 or 3. Their delivery charges are R30, R50 and R80 respectively. Display
the charge or Invalid zone. In this pseudocode dialect branches do not fall through and
BREAK is unnecessary.
```

Model solution

```
BEGIN
  INPUT zone
  SWITCH zone
    CASE 1:
      OUTPUT 30
    CASE 2:
      OUTPUT 50
    CASE 3:
      OUTPUT 80
    DEFAULT:
      OUTPUT "Invalid zone"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```

Exercise 229 Trace a SWITCH decision

Question

```
Create a SWITCH for option 1 = Start and 2 = Help. Other values display Try again. Trace
inputs 2 and 9 and explain why exactly one branch runs. In this pseudocode dialect
branches do not fall through and BREAK is unnecessary.
```

Model solution

```
BEGIN
  INPUT option
  SWITCH option
    CASE 1:
      OUTPUT "Start"
    CASE 2:
      OUTPUT "Help"
    DEFAULT:
      OUTPUT "Try again"
  ENDSWITCH
END

Review:
Match the selector against exact CASE values.
Use DEFAULT when no value matches.
Execute only the matching branch, then continue after ENDSWITCH.
```