

CSIT5410 HW4 Report

LIN Jialiang 20656855

Catalog:

1. A brief explanation of my weak classifiers
2. A brief explanation of my preprocessing chain
3. The selected weak classifiers and its weight after the Adaboost algorithm
4. The classification accuracy of each weak classifier and strong classifier on images specified in csit5410_test.txt
5. The detection results of the given images in the "test_images" folder, a maximum of 3 bounding boxes per image
6. Addition work that I have tried

Content:

1. Weak Classifiers:

I utilize six weak classifiers based on LBP feature with different window sizes and different classifiers.

- LBP feature is obtained from several regions of original image, and it is also computed with multi-resolution images. Concatenating the histogram of LBP values in all small regions forms the LBP feature vector of this original image.
- The window sizes I use are 128*128 and 64*64.
- The classifiers I use are random forest, svm and knn.
- So the combination of them is 6 weak classifiers.

2. Preprocessing Chain:

- Turn color image into gray image
- Histogram equalization
- Resize the image into a fixed size: 128*128
- After extracting features from images, perform PCA technique to reduce the dimensionality

3. The selected weak classifiers and its weight after the Adaboost algorithm:

```
Selected weak classifiers: (in order)

model_list =

    3    4    1    6    2

Alpha value for each selected weak classifier:

alpha_list =



    0.4426    0.2654    0.1956    0.0680    0.0281
```



4. The classification of strong classifier and weak classifiers:



Accuracy of the Strong Classifier:	0.72648
Accuracy of the Weak Classifier 1:	0.70751
Accuracy of the Weak Classifier 2:	0.65296
Accuracy of the Weak Classifier 3:	0.70791
Accuracy of the Weak Classifier 4:	0.67826
Accuracy of the Weak Classifier 5:	0.61186
Accuracy of the Weak Classifier 6:	0.63083



5. The detection results of the given images:



Since the size of cats in the images are varied, I use image pyramid to capture them:











6. Additional work that I have tried:

Since there are still several windows, I utilize non-maximum suppression to filter them and then combine into one single window.

In the implementation, I choose the best 10 windows in the original resolution image to do the above work. The codes are commented in the last of `csit5410_assignment4.m` and you can try if you are interested.

Here are the merging results (single window) in the original resolution image:

