

Pricing and Advertising

Project for the Data Intelligence Application Class
PoliMi 2019-2020

Bacarella Mattia - 999999

Corda Francesco - 920212

Damato Davide - 920616

Franchin Luciano - 921093

Massini Luca - 999999

August 19, 2020

Objective of the Project

The goal is to model a scenario in which a seller exploits advertising tools to attract more and more users to its website, thus increasing the number of possible buyers. The seller needs to learn simultaneously the conversion rate and the number of users the advertising tools can attract.

Project Structure

- ▶ Repository:
<https://github.com/francescocorda/dia-project>

- ▶ Structure:

```
dia_project
├── assignment_2
├── assignment_3
├── assignment_4
├── assignment_5
├── assignment_6
├── assignment_7
└── utils
```

- ▶ The project is organized in modules, one for each assignment. To execute the code and reproduce our results, run the file `assignment_x.py` in each module.

Assignment 1

Imagine one product to sell:

- ▶ *three classes of users, where, for every user, we can observe the values of two binary features (feel free to choose the features and their domains);*
- ▶ *the conversion rate curve of each class of users;*
- ▶ *three subcampaigns, each with a different ad, to advertise the product, and each targeting a different class of users;*
- ▶ *three subcampaigns, each with a different ad, to advertise the product, and each targeting a different class of users;*
- ▶ *there are three abrupt phases;*
- ▶ *for every abrupt phase and for every subcampaign, the probability distribution over the daily number of clicks for every value of budget allocated to that subcampaign.*

Assignment 2

Design a combinatorial bandit algorithm to optimize the budget allocation over the three subcampaigns to maximize the total number of clicks when, for simplicity, there is only one phase. Plot the cumulative regret.

Assignment 2 - Pseudocode

```
1 initialize click envs
2 for exp in n_experiments:
3     initialize gp-ts learners
4     for t in time_horizon:
5         draw samples for each subcampaign
6         find super-arm by solving knapsack problem
7         pull arms given by super-arm
8         update gp-ts learners
9 calculate clairvoyant value
10 plot rewards and regrets
```

Assignment 3

Design a sliding-window combinatorial bandit algorithm for the case, instead, in which there are the three phases aforementioned. Plot the cumulative regret and compare it with the cumulative regret that a non-sliding-window algorithm would obtain.

Assignment 3 - Pseudocode

```
1 initialize click envs
2 for exp in n_experiments:
3     initialize gp-ts and gp-ts-sw learners
4     for t in time_horizon:
5         if abrupt_phase is changed:
6             reset memory of the learners
7             draw samples for each subcampaign
8             find super-arm by solving knapsack problem
9             pull arms given by super-arm
10            update gp-ts and gp-ts-sw learners
11 calculate clairvoyant value
12 plot rewards and regrets for the 2 learners
```


Assignment 4

Design a learning algorithm for pricing when the users that will buy the product are those that have clicked on the ads. Assume that the allocation of the budget over the three subcampaigns is fixed and there is only one phase (make this assumption also in the next steps). Plot the cumulative regret.

Assignment 4 - Pseudocode

```
1 initialize pricing envs
2 for exp in n_experiments:
3     initialize ts and greedy learners
4     for t in time_horizon:
5         draw samples for each subcampaign (ts learner)
6         update ts learner
7         draw samples for each subcampaign (greedy learner)
8         update greedy learner
9 calculate clairvoyant value
10 plot rewards and regrets for the 2 learners
```

Assignment 5

Design and run a context generation algorithm for the pricing when the budget allocated to each single subcampaign is fixed. At the end of every week, use the collected data to generate contexts and then use these contexts for the following week. Plot the cumulative regret as time increases. In the next steps, do not use the generated contexts, but use all the data together.

Assignment 5 - Pseudocode

```
1 initialize pricing envs
2 for exp in n_experiments:
3     initialize context generator
4     for t in time_horizon:
5         if week is ended:
6             generate new contexts (greedy approach)
7             for context in n_contexts:
8                 run ts algorithm
9 calculate clairvoyant value
10 plot rewards and regrets
```

Assignment 6

Design an optimization algorithm combining the allocation of budget and the pricing when the seller a priori knows that every subcampaign is associated with a different context and charges a different price for every context. Suggestion: the value per click to use in the knapsack-like problem depends on the pricing, that depends on the number of users of a specific class interested in buying the product. Notice that the two problems, namely, pricing and advertising, can be decomposed since each subcampaign targets a single class of users, thus allowing the computation of the value per click of a campaign only on the basis of the number of clicks generated by that subcampaign. Plot the cumulative regret when the algorithm learns both the conversion rate curves and the performance of the advertising subcampaigns.

Assignment 6 - Pseudocode

```
1 initialize pricing and click envs
2 for exp in n_experiments:
3     initialize ts and gp-ts learners
4     for t in time_horizon:
5         for s in subcampaign:
6             draw a (price, conversion_rate) sample with ts
              learner
7             get return from the pricing env, given the price
8             update ts learner
9             draw click samples with gp-ts learner
10            weight the clicks with price and conversion_rate
              previously selected by the ts learner
11            find super-arm by solving knapsack problem
12            get revenues = clicks * price * conversion_rate
              from the click envs by pulling the super-arm
13            update gp-ts learners
14 calculate clairvoyant value
15 plot rewards and regrets
```

Assignment 7

Do the same of Step 6 under the constraint that the seller charges a unique price to all the classes of users. Suggestion: for every possible price, fix this price and repeat the algorithm used in Step 6. Plot the cumulative regret when the algorithm learns both the conversion rate curves and the performance of the advertising subcampaigns.

Assignment 7 - Pseudocode

```
1 initialize pricing and click envs
2 for exp in n_experiments:
3     for price in n_prices:
4         initialize ts and gp-ts learners
5         for t in time_horizon:
6             for s in subcampaign:
7                 select current price and conversion_rate
8                 get return from the pricing env, given the
9                 price
10                update ts learner
11                draw click samples with gp-ts learner
12                weight the clicks with price and
13                conversion_rate previously selected
14                find super-arm by solving knapsack problem
15                collect revenues = clicks * price *
16                conversion_rate from the click envs by pulling
17                the super-arm
18                update gp-ts learners
19 calculate clairvoyant value
20 plot rewards and regrets
```