

Slots 30...

Practices

Problem 1

- Data about an employee: Code(char 8), name(char 20), salary(double), allowance(double)
- Develop a C-program that allows user:
 - Adding a new employee
 - Find data about employees using a name inputted.
 - Remove an employee based on a code inputted
 - Print the list in descending order based on salary + allowance.

Problem 1... Analysis

- Data:
 - Constant: $MAXN = 50$
 - 4 arrays for the employee list: char codes[MAXN][9], names[MAXN][21], double salaries[MAXN], double allowances[MAXN].
 - `int n=0; /* current number of employees */`
 - `char code[9]; /* inputted code */`
 - `char name[21]; /* name inputted */`
 - `int choice; /* user choice */`

Problem 1... Analysis

- Operations:

```
/* Getting a user choice */
```

```
int menu()
```

```
/* Add a new employee, inputted data are local variables */
```

```
void add (char codes[][9],char names[][21], double salaries[], double allowances[], int*pn)
```

```
/* Print out data about employees bases on a known name */
```

```
void printBasedName( char name[], char codes[][9],char names[][21], double salaries[],  
    double allowances[], int n)
```

```
/* Find the position of a known code */
```

```
int findCode (char code[], char codes[][9], int n)
```

```
/* Remove the employee at the position pos */
```

```
void removePos (int pos, char codes[][9],char names[][21], double salaries[], double  
    allowances[], int *pn)
```

```
/* Sort the list based on salary+allowance*/
```

```
void sort(char codes[][9],char names[][21], double salaries[], double allowances[], int n)
```

```
/* Print all the list to the monitor */
```

```
void print(char codes[][9],char names[][21], double salaries[], double allowances[], int n)
```

Problem 1... Analysis

```
/* Sort the list based on salary + allowance*/
```

```
void sort(char codes[][9], char names[][21], double salaries[],
```

```
double allowances[], int n)
```

```
{ for (i=0; i<n-1; i++)
```

```
    for (j=n-1; j>i; j-- )
```

```
        if ( salaries[j] + allowances[j] <  salaries[j-1] + allowances[j-1] )
```

```
            { swap codes[j], codes[j-1];
```

```
              swap names[j], names[j-1];
```

```
              swap salaries[j], salaries[j-1];
```

```
              swap allowances[j], allowances[j-1];
```

```
            }
```

```
        }
```

```
    }
```

Problem 2

- Data about an item: Code(char 8), name (char 20), price(double), category (char 12)
- Develop a C-program that allows user:
 - Adding a new item
 - Print out items which belong to a known category.
 - Remove an item based on a code inputted
 - Print the list in ascending order based on categories then names

Problem 2... Analysis

- Data:
 - Constant: $MAXN = 50$
 - 4 arrays for the employee list: char codes[MAXN][9], names[MAXN][21], int prices[MAXN], char categories[MAXN][13].
 - int n=0; /* current number of items */
 - char category[13]; /* inputted category */
 - char code[9]; /* name inputted */
 - int choice; /* user choice */
- Operations:

Problem 2... Analysis

- Operations:

```
/* Getting a user choice */
```

```
int menu()
```

```
/* Add a new item, inputted data are local variables */
```

```
void add (char codes[][9], char names[][21], int prices[], char categories[][13], int*pn)
```

```
/* Print out items of a known category */
```

```
void printACategory( char cat[], char codes[][9], char names[][21], int prices[], char  
categories[][13], int n)
```

```
/* Find the position of a known code */
```

```
int findCode (char code[], char codes[][9], int n)
```

```
/* Remove the item at the position pos */
```

```
void removePos (int pos, char codes[][9], char names[][21], int prices[], char  
categories[][13], int* pn)
```

```
/* Sort the list based on categories then names*/
```

```
void sort(char codes[][9], char names[][21], int prices[], char categories[][13], int n)
```

```
/* Print all the list to the monitor */
```

```
void print(char codes[][9], char names[][21], int prices[], char categories[][13], int n)
```


Problem 2... Analysis

/* Sort the list based on categories then names*/

void sort(char codes[][9], char names[][21], int prices[],

char categories[][13], int n)

{ for (i=0; i<n-1; i++)

for (j=n-1; j>i; j--)

{ int dCat = strcmp(categories[j], categories[j-1]); /* Category difference */

int dName = strcmp(names[j], names[j-1]); /* name difference */

if (dCat<0 || (dCat==0 && dName <0))

{ swap codes[j], codes[j-1];

swap names[j], names[j-1];

swap prices[j], prices[j-1];

swap categories[j], categories[j-1];

}

}

}

Problem 3

- Data about a clock: make(char 20), color (char 20), price(int), guarantee (int- bảo hành)
- Develop a C-program that allows user:
 - Adding a new clock
 - Printing out clocks which belong to a known make.
 - Printing out clocks whose prices are between p1 and p2 (integers)
 - Printing the list in descending order based on prices.

Problem 4

- Data about a soft drink: name (char 20), make(char 20), volume (int), price(int), duration (int- số ngày có thể dùng)
- Develop a C-program that allows user:
 - Adding a new soft drink
 - Printing out items which belong to a known make.
 - Printing out items whose volumes are between v1 and v2 (integers)
 - Printing the list in ascending order based on volumes then prices.