

Lab05: LinkedList - Stack - Queue

1 Singly Linkedlist

Following is a representation of a singly linked list

```
class Node:
def __init__(self, data):
    self.data = data
    self.next = None
```

```
class SingleLinkedList:
def __init__(self, data):
    self.head = None
    self.tail = None
```

1. Insert an integer to the head of a given linkedlist:
 - def addHead(self, data)
2. Insert an integer to the tail of a given linkedlist:
 - def addTail(self, data)
3. Remove the first NODE of a given linkedlist:
 - def removeHead(self)
4. Remove the last NODE of a given linkedlist:
 - def removeTail(self)
5. Remove all NODE from a given linkedlist:
 - def removeAll(self)
6. Remove an integer before a value of a given linkedlist:
 - def removeBefore(self, val)
7. Remove an integer after a value of a given linkedlist:
 - def removeAfter(self, val)
8. Insert an integer at a position of a given linkedlist:
 - def addPos(self, data, pos)
9. Remove an integer at a position of a given linkedlist:
 - def removePos(self, pos)
10. Insert an integer before a value of a given linkedlist:
 - def addBefore(self, data, val)
11. Insert an integer after a value of a given linkedlist:
 - def addAfter(self, data, val)
12. Print all elements of a given linkedlist:
 - def printList(self, head)
13. Count the number of elements linkedlist:
 - def countElements(self, head)
14. Count the number of appearances of a value in a given linkedlist:
 - def countAppearance(self, value)
15. Create a new List by reverse a given linkedlist:
 - def reverseList(self)
16. Remove all duplicates from a given linkedlist:
 - def removeDuplicate(self)
17. Remove all key value from a given linkedlist:
 - def removeElement(self, key)

2 Doubly Linkedlist

Following is representation of a doubly linked list:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
```

```
class DoublyLinkedList:
    def __init__(self):
        self.head = None
        self.prev = None
```

Implement functions to execute the operations from a singly linkedlist section.

3 Stack - Queue

Following is the representation of a Singly linked list node:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
```

Utilize the Linked list above, define the data structure of Stack and Queue, then implement functions to execute the following operations:

1. Stack

- **Initialize** a stack from a given key.
- **Push** a key into a given stack.
- **Pop** an element out of a given stack, return the key's value.
- **Count** the number of elements of a given stack.
- Determine if a given stack **is empty**.

2. Queue

- **Initialize** a queue from a given key.
- **Enqueue** a key into a given queue.
- **Dequeue** an element out of a given queue, return the key's value.
- **Count** the number of elements of a given queue.
- Determine if a given queue **is empty**.